BROWNELLS UNIVERSAL REAR SIGHT ELEVATOR KIT



Handy Assortment Of 24 Popular Elevators


Universal Elevator Kit contains 24 elevators, covering the most common ones you get calls for. Included are six double-step short elevators: 6 double-step long elevators; 6 standard width (.080") single-step elevators and six special narrow width (.050") single-step elevators. Don't pass this kit up - a real money maker and lifesaver for any gun shop. SPECS: Length and width varies. Blued steel

STOCK #	QUANTITY	FITS		
#080-506-001AK	6 .080" wide single-s			
#080-506-002AK	6	.050" wide single-step		
#080-506-003AK	6	short double-step		
#080-506-004AK	6	long double-step		
Advise #	Circlet Elementes De	£11 0V07400		

Sight Elevator Refill 8K07A99 ... \$ 10.99 #080-506-000AK Rear Sight Elevator Kit,

> BROWNELLS **DECORATIVE SLOT BLANK**

Finely Crafted, Custom Pattern Looks Good On Modern & Classic Rifles



dovetail on your favorite sporter rifle. Stylish, diamond shape with decorative, milled edges blends naturally into the barrel contour for a truly finished look. Polished and blued with enough room for custom engraving, if so desired. Fits standard, .375" x 60° dovetails without fitting.

SPECS: Steel, polished blue finish, 1" (2.5cm) long x %6" (1.4cm) wide. Fits .375" x 60° dovetail.

#080-000-193AK Decorative Slot Blank 8K14H24...\$ 17.99

BROWNELLS SIGHT DOVETAIL SLOT BLANK



Fill Empty Dovetails For A Clean, Finished Appearance

The perfect cure when removing factory sights or restoring antiques to original space. Mild steel blanks machined slightly oversize for a close, perfectly blended fit

in barrel sight dovetails. Easy to shape, file and blue. SPECS: Mild steel, blued finish. 12" (30.4cm) long, fits nominal 3/8 (9.52mm) x 60° dovetails.

#080-770-375AK Dovetail Slot Blanks 8K11C23 ... \$ 15.75

MARBLE NO. 87 SLOT BLANK

Ready-Made To Fill Sight Dovetails

Polished blue flat-top blank fills empty sight

dovetails. SPECS: Steel, polish blued. Fits nominal 3/8" (9.5mm), 60° dovetails. Approximately 5/8" (15.8mm) wide overall.

#579-087-100AK No. 87 Dovetail Slot Blank.

9G04C15......\$ **6.99**

Selection • Service • Satisfaction

WILLIAMS ALUMINUM SLOT BLANK



Fills Empty Sight Dovetail Without Fitting

Machined, aluminum, slot blank dropsin easily to fill the empty sight dovetail for a clean-looking barrel. 5-40 set screw

locks blank in place and makes removal easy. Black anodized to blend well with most blue finishes.

SPECS: Aluminum, black anodized. 3/8" (9.5mm) x 5/8" (15.9mm). Fits standard, .375" (9.5mm) x 60° dovetails.

#962-000-034AK Aluminum Slot Blank 2F04B50... \$ 6.95

HERITAGE ARMS REMINGTON 600 VENTILATED RIB


Replace Soft Factory Plastic With Steel Or Aluminum

Fits and looks like the original rib, with greatly improved strength. Fully finished for easy installation; exactly replaces the now obsolete and unavailable factory, plastic rib. SPECS: Steel, blue, matte finish. Aluminum, black, anodized, matte, finish. 17½" (44.5cm) long. Uses existing screws.

#425-000-00 TAK Steel Item. 000 Vent Itib,	
$9B99A95\dots$. \$ 124.95
#429-000-002AK Aluminum Rem. 600 Vent Rib,	
9B84A95	109.95

— MISCELLANEOUS RIFLE SIGHTS —

RUGER® HIGH VISIBILITY SIGHT - Direct replacement for factory front sights on No. 1 and M77° rifles. White bead draws your eve to the front sight. Retained by existing plunger or a set screw; minor fitting is required for models with plunger toward



#661-834-330AK .330" Front Bead for Ruger, 1F23A31 \$ 26.00

OVERSIZE DOVETAIL FRONT SIGHT - Plenty of extra meat and blade height to finish into the exact front sight vou need. Oversize 60° x .395" dovetail base: available in two blade widths for short- and long-barrel applications.

SPEC: Cast steel, in-the-white, Dovetail - 60° x .395" x .100". Blade - .590" (15mm) high, .065" (1.6mm) or .100" (2.5mm) wide.

	1A00XCH	\$ 8.99
- 5 or More -	.065" Oversize Front Sight 1A	00HDZ. 6.32
#011-001-100AK	.100" Oversize Front Sight 1A	00ZAY . 8.99
 5 or More – 	.100" Oversize Front Sight 1A	00YTP . 8.99



AMERIGLO M14/M1A TRITIUM FRONT SIGHT

For Fast Sight Acquisition In Low Light

Self-illuminating, green, Trijicon® tritium dot allows rapid, front sight acquisition during low light conditions. Blade is extra wide for increased contrast and visibility during

bright light. Machined steel ears protect the tritium insert from damage. Parkerized finish helps prevent corrosion. Dovetailed base with steel, Allen head screw holds tight under heavy recoil. Drop-in fit with original issue flash suppressor.

SPECS: Machined steel, Parkerized finish. Base - .625" (1.6cm) long, .630" (1.6cm) wide. Blade - .4" (1cm) long, .11" (2.8mm) wide, .25" (6.3mm) high. .07" (1.7mm) O.D. green tritium center. Includes setscrew. Replaces standard issue front sight.

#100-004-184AK M14/M1A Tritium Front Sight,

4K55C12.....\$69.99

AMERIGLO AK-47 TRITIUM NIGHT SIGHTS



Replace Original Factory Sights With Easy-To-Acquire, Green Tritium Dots For Fast Targeting In Low Light

self-illuminating, green, Trijicon® tritium inserts in the rear sight and one in the front post provide an easy-to-acquire, 3-dot sight picture during low light operations. Rear sight features click ad-

justments for windage and uses the same elevation increments as a standard issue AKM tangent rear sight. Elevation settings are calibrated for 7.62 x 39mm trajectory up to 1000 meters. Fine line serrations on rear blade surface cuts light reflection to enhance sight pick up. Front post has M6 x .075" tpi thread for easy replacement with any standard issue front sight post. Front sight post and rear sight available separately.

SPECS: Machined steel, black, matte finish. Front sight - M6 x .075 tpi thread. .33" (8.4mm) long, .12" (3mm) wide, .95" (24mm) high. .07" (1.8mm) O.D. green tritium dot. Rear sight - 21/2" (6.3cm) long, .75" (19mm) wide, .11" (2.8mm) wide notch. Two .07" O.D. green tritium dots. Calibrated for 7.62 x 39. Front Sight fits all AK-47 style rifles with M6x.075" tpi front sight post. **Rear Sight** fits AK-47 style rifles in 7.62 x 39mm.

#100-004-187AK	AK-47 Tritium Front Sight,	
	4K46C37	\$ 59.99
#100-004-186AK	AK-47 Tritium Rear Sight,	
	AK101C30	120 00

Brownells MAUSER FRONT SIGHT BLANK

Ready To Fit & Shape For Custom Applications; Fits The Unique, Metric Dovetail

.375" high blade lets you zero the military Mausers, like the Model 96 Swede and 98, and other rifles with a metric dovetail, to point of aim.

Square post blade gives an easy-to-see, well defined sight picture with the original, issue rear sights. Plenty of extra material so you can file and shape the blade to original contour or a custom shape - and just the right height. 5.26mm dovetail fits the Mauser front sight base. Fits most Mauser 91 through 98 rifles with military sight base.

SPECS: Steel, blued, matte finish. .077" (1.9mm) wide, .375" (9.5mm) high above 81° x .207" x .062" dovetail. May require minor

#078-050-000AK Mauser Front Sight Blank, 8G11A59..... \$ 14.99



BROCKMAN'S MARLIN REAR PEEP SIGHT

Steel Ghost Ring Gets You On Target Fast

Machined from steel bar stock to withstand the rigors of everyday use. Sturdy, steel wings protect aperture from damage. Furnished with .125" replaceable aperture; threaded to accept Williams and Merit aperture discs. Fully adjustable for windage and elevation. Serrated rear sight surface reduces glare for easier sighting. No gunsmithing installation. SPECS: Steel, matte blued. 7/32" - 40 aperture thread. 1.35" (3.4cm) long, ½" (12.7mm) wide, .736" (18.7mm) tall. Fits Marlin 336, 1895, 1894 with $lac{1}{2}$ " c-to-c hole spacing. Requires front sight higher than factory front; use one of the front sights listed below.

#127-000-003AK Rear Peep Sight 7B117P53..... \$ 146.99

MARLIN FRONT SIGHT - Machined from steel bar stock with serrated rear face. Available in two widths: .125" for hunters and .080" for Cowboy Action Shooters. Fits nominal 3/8" dovetail. SPECS: Steel, matte blued. Height from top-of-blade to

top-of-dovetail - .385" (9.8mm). Fits all Marlin lever-action centerfire rifles. Works with factory rear sight on rifles with dovetail barrel. Use Brockman Rear Peep Sight on rifles with ramp front sight.

#127-000-004AK .125" Front Sight 7B29P20 \$ 37.99 #127-000-005AK .080" Front Sight 7B29P20 37.99

1895 FRONT SIGHT - Steel ears guard the front sight blade. Full blade is easily picked up by the eve to get on target fast. Serrations on sight blade prevent glare. SPECS: Steel, matte blued. Sight blade - 130" (3.3mm) wide, Sight Base - 2.07" (5.3cm) long, .44" (11.2mm) wide. Fits Marlin 1895 with 1" c-to-c hole spacing.

#127-000-007AK Marlin 1895 Front Sight 7B80P15 .\$ 87.99



GALAZAN WINCHESTER M70/94 FRONT SIGHT HOOD

Front Blade Protection & Enhanced Sight Picture

Protects the front sight from damage caused by normal field use. Open front design allows plenty of light to reach the front blade and provide an enhanced sight picture. Spring steel construction for durability. Available for Model 94 carbine with sight ramp and pre-64 Model 70.

SPECS: Steel, blue, matte finish. 1" (2.5cm) long x ½" (12.7mm) wide. **Model 94 -** ½" high (12.7mm). **Model 70 -** 11/16" (16.7mm)

#344-000-007AK Model 94 Carbine w/Ramp Sight Hood, #344-000-008AK Pre-64 Model 70 Sight Hood,

FRONT SIGHT ELEVATION CORRECTION CHART

How To Use Table Below - Suppose a rifle, having a sighting radius of 24" between front sight and receiver sight, shoots 6" high at 100 yards, even with the rear sight adjusted as low as possible. Remove front sight and measure overall height, preferably with a micrometer. This might be .410", such as a Marble No. 41N. Reference to columns for 24" and 6" on table below will show a necessary correction of .040". This would mean a new, higher front sight (with an overall height of .410" plus .040" for a corrected height of .450") such as a Marble No. 45N, should be installed.

Sighting in should be done with a benchrest or prone with a sand bag or other rest for the rifle. Do not put rifle barrel or forearm directly on solid surface, but put the back of your hand or wrist on the rest and hold forearm of the rifle securely in your hand with approximately the same tightness of grip you would use when shooting at running game. If the forearm or barrel is rested directly on the sand bag or rest, the rifle will shoot higher than when held firmly while shooting at game as more "muzzle flip" will occur.

AMOUNT OF ADJUSTMENT NECESSARYTO CORRECT ERROR Distance Between Front & Rear Sights


		14"	15"	16"	17"	18"	19"	20"	21"	22"	23"	24"	25"	26"	27"	28"	29"	30"	31"	32"	33"	34"
Amount	1"	.0038	.0041	.0044	.0047	.0050	.0053	.0055	.0058	.0061	.0064	.0066	.0069	.0072	.0074	.0077	.0080	.0082	.0085	.0088	.0091	.0093
of Error	2"	.0078	.0083	.0089	.0094	.0100	.0105	.0111	.0116	.0122	.0127	.0133	.0138	.0144	.0149	.0155	.0160	.0156	.0171	.0177	.0182	.0188
At	3"	.0117	.0125	.0133	.0142	.0150	.0159	.0167	.0175	.0184	.0192	.0201	.0209	.0217	.0226	.0234	.0243	.0251	.0259	.0268	.0276	.0285
100 Yards	4"	.0155	.0167	.0178	.0189	.0200	.0211	.0222	.0234	.0244	.0255	.0266	.0278	.0289	.0300	.0311	.0322	.0333	.0344	.0355	.0366	.0377
Given in Inches	5"	.0194	.0208	.0222	.0236	.0250	.0264	.0278	.0292	.0306	.0319	.0333	.0347	.0361	.0375	.0389	.0403	.0417	.0431	.0445	.0458	.0472
inches	6"	.0233	.0250	.0267	.0283	.0300	.0317	.0333	.0350	.0367	.0384	.0400	.0417	.0434	.0450	.0467	.0484	.0500	.05175	.0534	.0551	.0567

SATISFACTION GUARANTEED **SINCE 1939**



CALCULATING SIGHT HEIGHTS

Determining proper sight height is not difficult. Just remember the front and rear sights must be the same height above the center of the barrel, And, when you make your measurements, you MUST use a caliper or micrometer, A few thousandths can have a substantial effect, and this is no place for a tape measure or eyeballing!





- sight. Barrel outside diameter divided by 2.
- **C** = Distance from centerline to top of barrel at front **D** = Front sight height. sight. Barrel outside diameter divided by 2.

DETERMINING FRONT SIGHT HEIGHT

When you have a rear sight and need to find the correct front sight height, the formula is (A + B) - C = D. With the rear sight in place:

- 1) Measure barrel diameter at the location of the rear sight and divide by 2 to get Dimension A.
- 2) If the rear sight is adjustable, set the blade in the MIDDLE of its travel. Then measure the total rear sight height from the top of the barrel, to the top of the sight blade to get Dimension B. For example, on aWGOS with a 1/4" blade, the mid-setting is .462" high, so Dimension B would be .462".
- 3) Measure the barrel diameter at the projected location of the front sight and divide by 2 to get Dimen-
- 4) Add Dimension A + Dimension B, then subtract Dimension C from the total to get Dimension D, the required height of the front sight above the top of the barrel.
- 5) Choose the tallest ramp and shortest sight blade combination that's closest to the results in Step 4. In the example below, the required front sight height is .587". AWilliams 3/8" (.282" high) ramp and a Marble #31MR sight (.312" high) will provide a

combined height of .594". Or combine a Williams .250" high blade with a Williams 7/16" (.3445") ramp for a total height of .5945".

DETERMINING REAR SIGHT HEIGHT

When you have a front sight and need to find the correct rear sight height, the formula is (C + D) - A = B. With the front sight in place:

- 1) Measure barrel diameter at the projected rear sight location and divide by 2 to get Dimension A.
- 2) Measure the barrel diameter at the location of the front sight and divide by 2 to get Dimension C.
- 3) Measure the front sight height from the top of the barrel to the top of the sight blade to get Dimension D.
- 4) Add Dimension C + Dimension D, then subtract Dimension A from the total to get Dimension D, the required height of the rear sight above the top of the barrel.
- 5) Choose a rear base and sight combination with a total height closest to D. If the rear sight is adjustable, the total height should match Dimension D when the sight is positioned in the MIDDLE of the adjustment area.

EXAMPLE WITH NUMBERS D = .587'B = .462"A = .475C = .350'.700" .950'

FRONT SIGHT CALCULATION:	REAR SIGHT CALCULATION:
(A + B) - C = D	(C + D) - A = B
(.475 + .462)350 = .587	(.350 + .587)475 = .462
.937350 = .587"	.937475 = .462"

KENSIGHT AK-47 ADJUSTABLE NIGHT SIGHTS

Genuine Trijicon Lamps For Fast Sight Acquistion In Low Light

Drop-in sights with genuine, Trijicon lamps feature polished quartz lenses, which make these sights the perfect upgrade for AK-47 rifles and variants used during low light periods. Sight bodies are



EDM machined from rugged, 4140 steel, then heat-treated to Rc 38-40 and vacuum tempered to retain the extra-tight tolerances. Rear sight fits AK-47, Norinco 56S, Mak-90, and Polytech AKS variants. Fine line serrations on the rear blade surface help cut glare in bright light conditions. Features click adjustments for windage and uses standard issue, tangent rear sight increments for elevation adjustments. Robust, Front post has M6 x.075" tpi thread to replace standard issue front sight post on all AK variants with a front sight base.

SPECS: 4140 steel, blue, matte finish. .076" (1.9mm) diameter Tritium lamps.

#100-002-630AK	Rear AK-47 Night Sight,
	5A111V41
	Front AK-47 Night Sight,
	5A41V99

YOU CAN ALSO GO ONLINE AND USE OUR SIGHT CALCULATORS




Automatically calculate SIGHT CORRECTION or front and rear SIGHT HEIGHT

Go online to www.brownells.com/sightcalculator

You can also call one of our many full time gun techs to help you!


BROWNELLS We like to make things easy!



HIVIZ SIGHT SYSTEM

Bright, Easy-To-See Sights For Ruger® 10/22®

Glowing, fiber optic dots give an accurate sight picture that really stands out. Features two, green rear dots with



windage and elevation. SPECŠ: Steel sight body, black, matte finish. Fiber optic rods, orange and green, 3/32" (2.3mm), 7/64" (2.77mm), 1/8" (3.17mm) diam-

eter, 3/4" (19mm) long. Fits 10/22 with factory dovetail sights. #638-000-008AK 10/22 HiViz Sight 8C25V26...... \$ 39.95

HIVIZ FIBER OPTIC RIFLE SIGHT

Eye Grabbing Dot For Fast Target Acquisition

Front sight: Six, interchangeable, fiber optic rods offer a choice to match nearly all shooting and light conditions. The glowing, orange and green light pipes


provide great contrast against dark target backgrounds. SPECS: Steel, black, matte finish. .315" (8mm), .380" (9.7mm), .420" (10.7mm), .500" (12.7mm) height. Standard 3/8" dovetail. Light pipes: 1/16" (1.5mm), 3/32" (2.4mm), 1/8" (3.1mm), diameter.

#638-115-000AK	.315" Fiber Optic S	Sight	8C22B36	\$ 33.40
#638-000-013AK	.380" Fiber Optic S	Sight	8C22V36	. 33.40
#638-000-014AK	.420" Fiber Optic S	Sight	8C22V36	. 33.40
#638-000-015AK	.500" Fiber Optic S	Sight	8C22V36	. 33.40

HIVIZ AK-47/74/AKM FIBER OPTIC FRONT SIGHT

Bright Fiber Optic For Easy Aiming

Replacement front sight post has a light-gathering fiber optic rod to produce a bright dot that's easy to acquire in a broad range of light conditions. Easily replaces the post on most AK-47, AK-74 and AKM rifle sights, no gunsmithing required. Unique, U-shaped rod gathers



SPECS: Black steel post with 2 green and 2 red fiber optic rods. Includes detent pin, sight wrench, fiber optic rod removal tool, carrying case, and instructions. **#638-000-190AK AK-47 FO Front Sight** *8C19B59* . . **\$ 24.99**



For more choices of HIVIZ FIBER OPTIC SIGHTS visit brownells.com

MARBLE #95 FOLDING SPORTING REAR SIGHT



Folding design helps prevent accidental damage to the rear leaf. Leaf easily flips down, out of the way, when your favorite

lever or single-shot rifle is stored or carried. Long shank, barrel-mounted sight is fully adjustable using the center plate and center plate lock screw—no need for a separate elevator. Flat top leaf with white diamond sight insert helps improve sight acquisition and alignment. Screw and drift adjustable for windage. Fits nominal 3/8" dovetail. May require minor fitting. SPECS: Steel, blue, polished finish, Leaf - .300" (7.8mm) high, .630" (15.8mm) wide. Fits nominal 3/8" (9.5mm) dovetail.

#579-000-082AK #95 Folding Rear Sight 9G22V85 . \$ 30.99

order on the web www.brownells.com

MARBLE DOVETAIL FRONT RAMP

Graceful & Attractive For Rifles & Muzzleloaders

Solid steel ramps for custom fitting fiber optic, ivory and brass bead sight blades. Available in two heights and four barrel contours to fit a wide selection of current and older production rifles. Ramp attaches to barrel with a single screw under the sight body and solder; flat base is drilled for two mounting screws. SPECS: Steel, blue, polished finish. .340" (8.6mm) wide. 2" (5cm) long. Height is from the top of barrel to the bottom of dovetail.

STOCK#	BL DIA.	HGT
#579-000-034AK	.625	.100"
#579-000-035AK	.6875	.100"
#579-000-036AK	.875	.100"
#579-000-041AK	Flat	.225"

STOCK#	BL DIA.	HGT
#579-000-038AK	.625	.225"
#579-000-039AK	.6875	.225"
#579-000-040AK	.875	.225"

- Advise # - Dovetail Front Ramp 9G07T77 \$ 12.99

MARBLE UNI-RAMP FRONT SIGHT



Solid Steel Body For Strength; Long Rod Picks Up Lots Of Light

Glowing, 3/4" long, fiber optic rod

gives excellent visibility. Quickly replaces screw-held front sights on rifles, shotguns and muzzleloaders. Two blade heights and two

SPECS: Steel, blue, polished finish. 2" (5cm) long. Height - .405" (10.3mm) or .470" (11.9mm). Barrel Contour - 5%", ¾4", ¾6" diameter. Optic rod 3/4" (19mm) long, orange.

STOCK#	HEIGHT	CONTOUR	PRICE
#579-000-016AK	.405"	5%"	9G12T91 \$ 19.99
#579-000-017AK	.470"	5%"	9G12T58 \$ 19.99
#579-000-020AK	.405"	7/8"	9G12T58 \$ 19.99
#579-000-021AK	.470"	7/8"	9G12T58 \$ 19.99

MARBLE CONTOUR FRONT SIGHT

The Standard In The Industry

Precision-made sights for rifles, both with and without ramp bases. The blade is gracefullly contoured, sloping toward the front. Made of steel and nicely blued to look good on any gun.

Ramp Front, Gold RAMP MOUNTED FRONT SIGHT: "MR" fea-







Barrel Front, Ivory

Glow Sight

tures a straight-sided base for guns having a ramp base on the barrel. All "MR" sights have a .340" (8.6mm) wide base. The BAR-REL MOUNTED FRONT SIGHT has rounded base sides for guns with the front sight dovetail cut directly into the barrel. "W" sights have a 17/32" (13.5mm) wide base. Ramped and Barrel front sights are available with three beads, Pope's Island Gold, flat faced gold available in $\frac{1}{16}$ " (1.6mm) or $\frac{3}{2}$ " (2.4mm) diameter. **Ivory**, flat faced white polymer in $\frac{1}{16}$ " (1.6mm) or $\frac{3}{2}$ " (2.4mm) diameter. **GLOW SIGHTS**: Two colors - Orange or Green .060" dia. optic rod. **RAMP MOUNTED** - .340 wide base. **BARREL MOUNTED** - $\frac{1}{2}$ " wide base. SPECS: Steel, blue, polished finish, .620" (15mm) long.

	RAMP MOUNTED FRONT SIGHTS						SIGHTS
HGT	MRBL #	1/16" GOLD	1/16" IVORY	3/32" GOLD	3/32" IVORY	GREEN	ORANGE
.260	26-MR	#579-502-621AK	#579-502-622AK	#579-602-621AK	#579-602-622AK	NA	NA
.290	29-MR	#579-502-921AK	#579-502-922AK	#579-602-921AK	#579-602-922AK	NA	NA
.312	31-MR	#579-503-121AK	#579-503-122AK	#579-603-121AK	#579-603-122AK	#579-603-126AK	#579-603-125AK
.343	34-MR	#579-503-421AK	#579-503-422AK	#579-603-421AK	#579-603-422AK	#579-603-426AK	#579-603-425AK
.375	37-MR	#579-503-721AK	#579-503-722AK	#579-603-721AK	#579-603-722AK	#579-603-726AK	#579-603-725AK
.410	41-MR	#579-504-121AK	#579-504-122AK	#579-604-121AK	#579-604-122AK	#579-604-126AK	#579-604-125AK
.450	45-MR	#579-504-521AK	#579-504-522AK	#579-604-521AK	#579-604-522AK	#579-604-526AK	#579-604-525AK
.500	50-MR	#579-505-021AK	#579-505-023AK	#579-605-021AK	#579-605-022AK	#579-605-026AK	#579-605-025AK
538	53-MR	#579-505-321AK	#579-505-322AK	#579-605-321AK	#579-605-322AK	NΔ	NΔ

	BARREL MOUNTED FRONT SIGHTS					GLOW S	SIGHTS
HGT	MRBL#	1/16" GOLD	1/16" IVORY	3/32" GOLD	3/32" IVORY	GREEN	ORANGE
.312	31-W	NA	#579-103-132AK	#579-203-131AK	#579-203-132AK	#579-203-136AK	#579-203-135AK
.343	34-W	#579-103-431AK	#579-103-432AK	#579-203-431AK	#579-203-432AK	#579-203-436AK	#579-203-435AK
.375	37-W	#579-103-731AK	#579-103-732AK	#579-203-731AK	#579-203-732AK	#579-203-736AK	#579-203-735AK
.410	41-W	#579-104-131AK	#579-104-132AK	#579-204-131AK	#579-204-132AK	#579-204-136AK	#579-204-135AK
.450	45-W	#579-104-531AK	#579-104-532AK	#579-204-531AK	#579-204-532AK	#579-204-536AK	#579-204-535AK
.500	50-W	#579-105-031AK	#579-105-032AK	#579-205-031AK	#579-205-032AK	#579-205-036AK	#579-205-035AK
.538	53-W	#579-105-331AK	#579-105-332AK	#579-205-331AK	#579-205-332AK	NA	NA
.570	57-W	#579-105-731AK	#579-105-732AK	#579-205-731AK	#579-205-732AK	NA	NA

	MARBLE Chart To Determine Overall Sight/Ramp Heights													
Sight No.	Ramp	Total Height	Sight No.	Ramp	Total Height	Sight No.	Ramp	Total Height	Sight No.	Ramp	Total Height	Sight No.	Ramp	Total Height
26MR	3/16"	.3545	26MR	3/8"	.5420	41MR	5/16"	.6295	37MR	7/16"	.7195	34MR	9/16"	.8125
29MR	3/16"	.3845	45MR	³ ⁄16"	.5445	53MR	3/16"	.6325	26MR	9⁄16"	.7295	53MR	3/8"	.8200
31MR	3/16"	.4065	34MR	⁵ ⁄16"	.5625	29MR	7⁄16"	.6345	45MR	3/8"	.7320	50MR	⁷ ∕16"	.8445
34MR	3/16"	.4375	29MR	3/8"	.5720	31MR	7⁄16"	.6565	41MR	7⁄16"	.7545	37MR	9⁄16"	.8445
37MR	³ ⁄16"	.4695	31MR	3/8"	.5940	37MR	3/8"	.6570	53MR	5/16"	.7575	41MR	⁹ ⁄16"	.8795
26MR	5/16"	.4795	50MR	3/16"	.5945	45MR	5⁄16"	.6695	29MR	9/16"	.7595	53MR	⁷ ∕16"	.8825
41MR	3/16"	.5045	37MR	5/16"	.5945	34MR	⁷ ⁄16"	.6875	31MR	9/16"	.7815	45MR	9/16"	.9195
29MR	5/16"	.5095	26MR	⁷ ⁄16"	.6045	41MR	3/8"	.6920	50MR	3/8"	.7320	50MR	9⁄16"	.9695
31MR	5⁄16"	.5315	34MR	3/8"	.6250	50MR	5⁄16"	.7195	45MR	7⁄16"	.7945			

MARBLE'S SIGHT SELECTION CHART

WINCHESTER RIFLES 1892 Rep. 25-20, 32-20, 38-40, 44-40 1892 Carb. 25-20, 32-20, 38-40, 44-40 1892 Carb. with ramp 1894 Rep. 32-40, 38-55, 30-30, 32 Spec.		SPORTING REAR	SPORTING REAR L		FRONT	
1892 Rep25-20, .32-20, .38-40, .44-40 1892 Carb25-20, .32-20, .38-40, .44-40 1892 Carb. with ramp 1894 Rep32-40, .38-55	FLATTOP	SEMI-BUCK	FULL BUCK	FLAT	MOD. NO.	
1892 Carb. with ramp 1894 Rep32-40, .38-55	66	67	68	69	31W	
1894 Rep32-40, .38-55	63	64	65	69	-	
	63	64	65	69	-	
1894 Rep25-3530-3032 Spec.	66	67	68	69	31W	
	66	67	68	69	45W	
1894 with ramp .25-3530-30, .32 Spec.	66	67	68	69	-	
1894 Carb32-40, .38-55	63	64	65	69	-	
1894 Carb25-35, .30-30, .32 Spec.	63	64	65	69	894	
1894 Carb. with ramp	63	64	65	69	-	
Mod. 61 Pump Action .22 Cal.	63	64	65	69	34W	
Mod. 62 Rep. Rifle .22 Cal.	63	64	65	69	34W	
Mod. 63 .22 L. R. Auto	63	64	65	69	34W	
Mod. 64 .25-35, .30-30, .32 Spec.	66	67	68	69	-	
Mod. 65 .25-20, 32	66	67	68	69	-	
Mod. 67 Single Shot .22 Cal.	63	64	65	69	34W	
Mod. 68 .22 Cal.	63	64	65	69	45W	
Mod. 69 .22 Cal.	63	64	65	69	45W	
Mod. 70 All Cal.	66	67	68	69	-	
Mod. 71 .348 Cal.	66	67	68	69	-	
Mod. 77 .22 Cal. S. L. Rifle	63	64	65	69	41M	
Mod. 88 .308 Cal. L. A. Rifle	66	67	68	69	-	
Mod. 100	63H	64H	65	69H	26MR	
MARLIN RIFLES						
Mod. 39, A Rep. Rifles	63	64	65	69	37M	
Mod. 39 A with Ramp	63	64	65	69	-	
Mod. 56 22 Cal. L. A.	63	64	65	69	-	
Mod. 36, 336 rifle and carbines	66	67	68	69H	45W	
Mod. 336, SC .35 Cal.	66	67	68	69H	37M	
REMINGTON RIFLES						
Mod. 12 Rep. Rifle .22 Cal	63	64	65	69	31W	
Mod. 121 Fieldmaster .22 Cal.	63	64	65	69	37M	
Mod. 121 Fieldmaster (1936 Series) .22 Cal.	63M	64M	=	-	37M	
Mod. 141 Gamemaster .30, .32, .35	66H	64	65	69	31M	
Mod. 241 Speedmaster .22 Auto-Ldg.	63M	64	65	69	37W	
Mod. 33, 34, 41, .22 Cal. Single Shot	63	64	65	69	31W	
Mod. 341 Speedmaster .22 Cal.	63	67H	-	68H	31W	
Mod. 510, 513T	63	64	65	69	37M	
Mod. 511, 512, 550, 552	63	64	65	69	37M	
Mod. 514	63M	64	65	69	37M	
Mod. 521T .22 Cal	63	64	65	69	45W	
Mod. 572 .22 Cal.	63M	64M	-	69	37M	
Mod. 700	63	64	=	69	41MR	
Mod. 721, 722 All Cal.	63H	64H		69H	34W	
Mod. 760 All Cal.	66	67	68	69H	-	
Mod. 740 .22 Cal.	63H	64H	-	69H	37M	
Mod. 740 ADL	63H	64H	-	69H	-	
Mod. 742	63H	64H	65	69	41	
Mod. 760 .22 Cal.	66H	67H	65	69	41	
Mod. 725	66	67 Pama	=	69	31M	
On late Model 700, 721, 722, 725, 740 Sight Base is required to use Marble Open	Rear Sights (r	not stocked)				
SAVAGE RIFLES Mod. 340, .30-30 Cal. for Gun with Slot in Ramp	63H	64H		69H		
Mod. 340, .30-30 Cal. for Gun with Slot in Ramp Mod. 342 .22 Hornet	63H	64H	-	69H	-	
Mod. 1899 E. F. G.	66	67	68	69	-	
	66		68	69	-	
Mod. 99R .250 and .300 Cal. Types A, B, C, D & H. Serial No. below 297,000 in Cal22 HP25-35, .30-30, .303300	-	67	-	69H	45W	
For Featherweight		<u> </u>	=	0311	4577	
Mod. 99T .30-30 & .303 Cal.	63	64	65	69H	_	
99F, G & EG .22 Cal. HP; 99RS .250	63	64	65	69H	34W	
99F, G & K .30-30 & .303; Carbines .250, .30-30, .303	66	67	68	69H	37M	
99T .22 HP, .250, .300, 99A, E. F. G. EG.K & R .250, 99G, K, RS .300	66	67	68	69H	45W	
Mod. 110MC-MCL	66H	67H	-	69H		
Mod. 99DL .300 Sav.	66	67	68	69H	26MR	
	66	67	68	69H	29MR	
Mod. 99E .243, .300 Sav. and .308						
	63H	67H	68	69H	37W	
Mod. 99 . 243, .300 Sav. and .308 STEVENS RIFLES Mod. 87	63H	64H	65	69H	37W	
STEVENS RIFLES						
STEVENS RIFLES Mod. 87					37M	
STEVENS RIFLES Mod. 87 Mod. 87K BROWNING			-	-		
STEVENS RIFLES Mod. 87 Mod. 87K BROWNING 22 Automatic late models	- 63	- 64	- 65	69	-	
STEVENS RIFLES Mod. 87 Mod. 87K BROWNING	63	- 64 -	- 65 -	- 69 -	- - -	
STEVENS RIFLES Mod. 87 Mod. 87K Mod. 87K STEVENS RIFLES Mod. 97K BOD STEVENS RIFLES 22 Automatic late models 22 Automatic Mod30, .06	- 63 -	- 64 -	- 65 -	- 69 -	- -	
STEVENS RIFLES Mod. 87 Mod. 87K BROWNING 22 Automatic late models 22 Automatic Mod. 30, 06 STURM-RUGER RIFLES	63	64	- 65 -	-	- -	
STEVENS RIFLES Mod. 87 Mod. 87K Mod. 87K STEVENS RIFLES Mod. 97K BOD STEVENS RIFLES 22 Automatic late models 22 Automatic Mod30, .06	63	64	- 65 - - -	69H 69	45MR 41MR	
STEVENS RIFLES Mod. 87 Mod. 87K Mod. 87K BROWNING 22 Automatic late models 22 Automatic Mod. 30, .06 STURM-RUGER RIFLES Mod. 44 Mag. Mod. 10/22 - No sight available.	63	64	- 65 - - -	- 69H	45MR	
STEVENS RIFLES Mod. 87 Mod. 87 Mod. 87K BROWNING 22 Automatic late models 22 Automatic Mod. 30, .06 STURM-RUGER RIFLES Mod. 44 Mag.	63	64	- 65 - - -	- 69H	45MR	

MARBLE SPORTING REAR SIGHT

Traditional Sights Fit Many Brands



Sporting Rear Sight Base with three styles of Uprights. Perfect as replacement sights for customizing sight picture, or adding adjustment to fixed sight guns. Fits standard 3/8" dovetails; available in Flat Top, Semi-Buckhorn or Full Buckhorn Uprights. SPECS: Dovetail Model - Total heights: #63 and 64, .275" (7.1mm) - .505" (12.4mm); #63H, 64H, 66H and 67H, .350" (9.0mm) - .630 (16.0mm): #65, 66, 67 and 68, .300" (7.6mm) -.510" (12.9mm).

FLATTOP SIGHTS

STOCK #	MODEL #	STYLE	SHANK	
#579-063-001AK	63	Dovetail	Short	
#579-063-003AK	63H	Dovetail	Short	
#579-066-001AK	66	Dovetail	Long	
#579-066-003AK	66H	Dovetail	Long	
- Advise # - Flat Top Rear 9G13B64				

SEMI-BUCKHORN SIGHTS

STOCK #	MODEL #	STYLE	SHANK
#579-064-001AK	64	Dovetail	Short
#579-064-003AK	64H	Dovetail	Short
#579-067-001AK	67	Dovetail	Long
#579-067-003AK	67H	Dovetail	Long

- Advise # - Semi-Buckhorn Rear 9G14B50.... \$ 21.99

FULL-BUCKHORN SIGHTS

STOCK #	MODEL #	STYLE	SHANK		
#579-065-001AK	65	Dovetail	Short		
#579-068-001AK	68	Dovetail	Long		
- Advise # - Full-Buckhorn Rear 9G13B93 \$ 21.99					

MARBLE FOLDING LEAF REAR SIGHT

Perfect "Back-Ups" For Scoped Guns

Folds down when not in use. Strong spring secures sight in "up" or "down" position. The reversible notch piece gives choice of "U" or "V" notch. Styles and heights available to fit most standard rear sight dovetails. The chart shows the overall sight height for those sights below.

69 & 69W - Height, .370" (9.4mm) to .480" (12.2mm) **69H & 69WH -** Height, .470" (11.9mm) to .600" (15.2mm) 69EH & 69WEH - Height, .520" (13.2mm) to .640" (16.3mm)

No. 69EH and No. 69H are .096" (2.4mm) higher than standard folding leaf; EH model adjusts for elevation from .538" to .657". Blade & Screw replacement parts available to main-



tain your existing, folding-leaf sights.	
#579-069-000AK No. 69 Flat Top 9G13B64	\$ 21.99
#579-069-001AK No. 69H Flat Top 9G13B44	21.99
#579-000-071AK No. 69EH Flat Top 9G15V31	
#579-000-073AK Blade & Screw 9G01V19	2.99

FLATTOP FOLDING LEAF SIGHT WITH WINDAGE

NO.69W - "W" indicates Windage and can be used wherever No. 69 sights are indicated in Marble sight chart.





NO.69WH - "H" indicates "high" and can be used wherever No. 69H is indicated. "H" is .096" (2.4mm) higher. No.69WEH - "EH" indicates "extra high"

and is elevation adjustable .538" to .657".	
#579-069-002AK No. 69W Flat Top 9G14B40\$	22.99
#579-069-003AK No. 69WH Flat Top 9G14B40	. 21.99
#579-000-072AK No. 69WEH Flat Top 9G14V59	. 22.99

MARBLE BULLSEYE REAR SIGHT



For Fast Target Acquisition & Improved Accuracy

Barrel-mounted, dovetail Bullseve sight gets you on target fast with perfect alignment for improved accuracy. Steel, doublering peep design ensures consistent sight alignment and helps improve shooting form. The moment the rear sight is misaligned, the front sight drifts out of the center ring, telling the shooter to re-align. Replaces standard 3/8" dovetail rear sights on many rifles. For use with bead-type or traditional blade front sights. Adjustable models are available with a short or long base and six-position step elevator that's adjustable in .030" increments for precise elevation settings. Fixed model features the same Bullseve peep design but without the extended base and is not elevation adjustable. All models are drift adjustable for windage. May require minor fitting.

SPECS: Steel, blue, polished finish. Fits nominal 3/8" (9.5mm) dovetail. Outside Ring O.D. - 9/16" (1.4cm). Inside Ring I.D. - .15" (3.8mm). Adjustable - .338"-.535" (8.6mm - 13.5mm) elevation adjustment in six, .030" (.76mm) increments. OAL from rear of dovetail - Long: 2½" (6.3cm). Short - 1½" (3.8cm). Fixed - .438 (11.1mm) fixed height from bottom of dovetail to center of inside ring. 7/16" (1.1mm) long. #579-000-163AK Short Adj. Bullseye Sight,

	9G13V64\$	17.99
579-000-164AK	Long Adj. Bullseye Sight,	
	9G13V82	17.99
579.000.165AK	Fixed Bullsove Sight 9C13V03	1799

MEPROLIGHT® REMINGTON RIFLE SIGHT



All Steel Replacement Sights With Excellent Low-Light Visibility

Easy-to-install, adjustable replacement sights equipped with Meprolight's standard, tritium

insert with visibility guaranteed for five years. All sights fit in the factory sight bodies. No alteration to the gun. Fits Remington model 4, 6, 7400, 7600, 870, 1100 and 11-87 equipped with adjustable rifle sights.


SPECS: Steel sight body, blued, Tritium inserts, Includes front and rear sight.

387-310-460AK	Remington Rifle Sights,		
	7H99A99	\$ 119.99	

MIDWEST INDUSTRIES SIG 556 FOLDING FRONT SIGHT

Allows Use Of AR-15 Rear Sights On Your Sig; Fits Factory Sight Dovetail

Flip-up front sight deploys with the flick of a finger to provide instant back-up to keep you in the fight if your Sig 556's primary optics or laser sight fails. Fits the factory dovetail on the gas block, and is the correct



SPECS: 6061 T6 aluminum, hardcoat anodized, matte black. #100-004-065AK Sig

K	Sig 556 Folding Front Sight,	
	2A80V65	\$ 89.99

N.E.C.G. UNIVERSAL SCREW-ON RAMP

Adjustable, With **Easy-To-Change Blades**

Pivoting, interchangeable front blades provide up to .030" of elevation adjustment.
Optional hood mounts from the rear to resist recoil. Installs easily with a single, 6-48 screw; accepts the Universal Front Sight Beads and Ramp Hoods (listed below). SPECS: Steel, blue, matte finish. Height measured from top of barrel to top of base. Includes 6-48 attachment screw and Allen

STOCK	# HEIGHT
n) #661-000-00	7AK .525"(13.3mm)
m) #661-000-00	8AK .595"(15.2mm)
	p,
1	m) #661-000-00 (mm) #661-000-00 (Screw-On Ram)

UNIVERSAL BANDED RAMP - Combines the classic look of the Masterpiece Banded Ramp with the easy elevation adjustability of the Universal Screw-On Ramps. Accepts the interchangeable front sights and hoods, available below. Ramp is 7/16"

high, with a straight, untapered inside diameter to fit barrels with .670" O.D.

SPECS: Mild steel, in the white, Fits barrels with .670" (17mm) O.D. Ramp overall length: 3.3" (8.4cm). Band length 1.2" (3cm). Ramp width: .40" (1cm). Height to dovetail: .43" (11mm). Band wall thickness: .039" (1mm).

#661-000-059AK Univ. Banded Ramp 1F84Y51 \$ 99.00

INTERCHANGEABLE FRONT SIGHT -

Highly-visible front sight beads fit the Universal Ramps. Available in six different styles: Gold Patridge (Ptrdg.),


White Bead, and Red Fiber Optic Bead. Includes spring detent. SPECS: Steel, blue. Heights listed are from top of base to top of bead. Sights will adjust for approximately .060" of additional height. Low - . 177" (4.5mm), Med. - . 197" (5mm), High - . 216" (5.4mm). Bead Width: Standard, .099" (2.5mm). Fiber Optic (F/O) is available in red only

STK # LOW	STK # MED.	STK # HIGH	COLOR
#661-108-102AK	#661-108-202AK	#661-108-302AK	Gold(Ptrdg.)
#661-108-103AK	#661-108-203AK	#661-108-303AK	White
#661-108-104AK	#661-108-204AK	#661-108-304AK	F/O

- Advise # - Universal Front Bead 1F22Y21 \$ 26.00

FRONT SIGHT HOODS - For Universal Front Sight Ramps. Use Medium Hood for Medium and Large Hood for High. Window Hood allows more light, must be used with Fiber Optic Beads

#661-000-002AK Medium Universal Hood.



	1F21V31	
#661-000-003AK	Large Universal Hood 1F21V31 25.00	
#661-000-004AK	Window Universal Hood 1F25V31 30 00	

N.E.C.G. EXPRESS SIGHT Fast Sight Picture,

Elegant Looks

Classically styled, all-steel sight with one fixed, plus single or double flip-up leaves give fast pickup and clear sight picture for hunting in thick cover. Install directly on a rib or on the specially contoured N.E.C.G. base.

SPECS: Machined steel, in-the-white. Height from top of base radius to bottom of dovetail is .250" (6.3mm). Total sight height to top of middle leaf is .755". **1-Leaf Sight:** .98" (25mm) long, **2-Leaf Sight:** 1.4" (3.5cm) long, .7" (17mm) wide. **1-Leaf Base:** 2.2" (5.7cm) long, **2-Leaf Base:** 2.6" (7.5cm) long, .65" (16.5mm) wide.

#661-000-028AK	1-Leaf Express	Sight	1F69Y99	\$ 8	30.00
#661-000-029AK	2-Leaf Express	Sight	1F82Y31	9	90.00
#661-000-030AK	1-Leaf Express	Base	1F49Y99.	5	4.00
#661-000-031AK	2-Leaf Express	Base	1F49Y99.	!	57.00

N.E.C.G CLASSIC EXPRESS SIGHT

Magnum ClampWon't Loosen Under Recoil

Flip-up, windage adjustable, expressstyle sights clamp securely into the pre-contoured base so they won't shoot loose, even under heavy recoil. Blank leaves require trimming to correct height. Drill and tap, or silver solder to barrel. P1 single leaf. P2 two leaves. P3 three leaves.

SPECS: Steel, blued, polished finish. 31/16" (8cm) long. 1/4" (6.3mm) wide. 2.6 oz. (774g) weight. Fits barrel diameters: L .730" to .830", XL .830" to .930".

STOCK#	STYLE	PRICE
#661-001-730AK	P1-L	1F119Y99 \$ 135.00
#661-001-830AK	P1-XL	1F129Y99 \$ 135.00
#661-002-730AK	P2-L	1F125Y61 \$ 144.00
#661-002-830AK	P2-XL	1F125Y61 \$ 144.00
#661-103-830AK	P3-XL	1F139Y99 \$ 154.00

N.E.C.G. "MASTERPIECE" ADJUSTABLE REAR SIGHT

Precision Windage & Elevation Adjustment

Notched, "V"-style blade is fully adjustable for windage and elevation. Machined from solid steel, polished and blued to compliment the finest sporting rifle.

SPECS: Steel, polished, blued. 23/16" (5cm) long, .546" (13.8mm) wide, 1.6 oz. (44g) wt. .322" (8.1mm) from top of barrel to top of base. Solder-on or drill and tap for 8-36 screw.

STOCK # MODEL		FITS BARREL DIA.	PRICE	
#661-105-675AK	MR-S	.600" To .675"	1F83Y31 \$ 99.00	
#661-105-830AK	MR-L	.731"To .830"	1F83Y31 \$ 99.00	
#661-105-930AK	MR-X	.831"To .930"	1F83Y31 \$ 99.00	

N.E.C.G. CZ 550 FRONT SIGHT

Highly Visible Front Sights In Classic & Modern Designs







Patridge

steel front sights give your CZ 550 a custom look, plus the advantages of fast sight acquisition in changing hunting conditions. Precision machined to fit the dovetail on CZ rifles equipped with factory ramped front sights, and available in five heights to regulate properly with a variety of calibers. **White Bead (WB)** features a bright, white, polymer rod supported front and aft with two carefully machined bands for added strength. Traditional Gold Patridge (GP) design features a polished brass insert on the face for the truly classic look found on many custom rifles. Red Fiber Optic

dusk. Sight bases may require some fitting. SPECS: Base - Steel, blued finish. .655" (16.6mm) long x .195" (5mm) wide. **WB** - White polymer rod with .094" (2.4mm) dia. bead. **GP** - .100" (2.54mm) wide x .290" (7.4mm) high brass insert. **RFO -** .550" (14mm) long x .099"(2.51mm) dia. red fiber optic rod. Heights shown in table are measured from bottom of dovetail to

(RFO) includes an easy to see, .099" diameter fiber optic rod for

superior light transmission during all periods from dawn 'til

STOCK #	MODEL	HEIGHT	PRICE
#661-000-047AK	WB	.237" (6mm)	1F23Y31 \$ 26.00
#661-000-048AK	WB	.256" (6.5mm)	1F23Y31 \$ 26.00
#661-000-049AK	WB	.296" (7.5mm)	1F23Y31 \$ 26.00
#661-000-051AK	WB	.374" (9.5mm)	1F23Y31 \$ 26.00
#661-000-052AK	GP	.374" (9.5mm)	1F36Y24 \$ 41.00
#661-000-053AK	RFO	.256" (6.5mm)	1F33Y49 \$ 39.00
#661-000-054AK	RFO	.296" (7.5mm)	1F33Y49 \$ 39.00
#661-000-055AK	RFO	.335" (8.5mm)	1F33Y49 \$ 39.00
#661-000-056AK	RFO	374" (9 5mm)	1F33V49 \$ 39 00

order on the web www.brownells.com

N.E.C.G. "MASTERPIECE" **BANDED FRONT RAMP**



Window-Style

Classic, Hooded Front Sight Bands

Machined from solid, mild steel; classic sight that's easy to fit and finish. A wide selection of interchangeable blades match any hunting situation.

Accepts "Masterpiece" front sights only. Hood shown is optional. Hoods are available in Small, Medium, and Large diameter. Window-

style hood features light-admitting side cutouts for use with fiber optic front sights.

SPECS: Mild steel, in-the-white. Band - approx. 3.3" (8.4cm) long. Height shown in chart is from top of barrel to bottom of dovetail. Hoods - approximately 11/8" (3.1cm) long, .Small - .555" (14mm); Med. - .630" (16mm); Large - .708" (18mm) I.D.

STOCK #	MODEL	I.D. (mm)	HEIGHT	PRICE
#661-120-551AK	1	.551" (14)	.500"	1F62A51 \$ 75.00
#661-120-571AK	1A	.571" (14.5)	.421"	1F62A51 \$ 75.00
#661-120-590AK	2	.590" (15)	.421"	1F62A51 \$ 75.00
#661-120-618AK	3	.610" (15.5)	.421"	1F62A51 \$ 75.00
#661-120-650AK	4	.650" (16.5)	.421"	1F62A51 \$ 75.00
#661-120-670AK	4A	.670" (17)	.386"	1F62A51 \$ 75.00
#661-120-689AK	5	.689" (17.5)	.362"	1F62A51 \$ 75.00
#661-120-708AK	5A	.708" (17.9)	.386"	1F62A51 \$ 75.00
#661-120-728AK	5B	.728" (18.5)	.362"	1F62A51 \$ 75.00
#661-120-748AK	6	.748" (19)	.362"	1F62A51 \$ 75.00
#661-120-768AK	6A	.768" (19.5)	.362"	1F62A51 \$ 75.00
#661-120-787AK	6B	.787" (20)	.362"	1F62A51 \$ 75.00
#661-120-827AK	6C	.827" (21)	.362"	1F62A51 \$ 75.00
#661-120-080AK #661-120-100AK #661-120-120AK #661-000-045AK	Mediu Large	ım Sight Ho Sight Hood	od 1F22A 1 1F22A3	431 25.00 1 25.00
	1F29Y			34.00

"MASTERPIECE" FRONT SIGHTS - Spring-loaded plunger and

detent, located in "Masterpiece" Banded Front Ramp, hold the sight blade into the longitudinal dovetail: set



screw firmly locks the sight blade in place. Styles available: S-1 and **S-2** - $\frac{5}{64}$ " (1.9mm) and $\frac{3}{32}$ " (2.3mm) diameter silver bead. **S-3** - Sourdough/patridge front bead, S-4 - fixed silver 3/32" diameter bead and fold-down 11/64" (4.3mm) diameter Ivory bead. S-5 - 3/32" x 11/16" long red fiber optic light pipe.

SPECS: Steel, blued. Base - 7/8" (22mm) long, S-4 is 3/4" (19mm) long; 32" (5.5mm) wide. Blade - 916" (14.3mm) long. Height - shown in chart is from bottom of dovetail to top of blade, S-5 Light Pipe - 3/32 (2.3mm) Dia. x 11/16" (17mm) long.

		-	
STOCK #	MODEL	HEIGHT (mm)	PRICE
#661-121-197AK	S-1	.197" (5.0)	1F17A10 \$ 19.00
#661-121-237AK	S-1	.237" (6.0)	1F17A10 \$ 19.00
#661-121-256AK	S-1	.256" (6.5)	1F18A21 \$ 19.00
#661-121-315AK	S-1	.315" (8.0)	1F17A21 \$ 19.00
#661-122-237AK	S-2	.237" (6.0)	1F18A31 \$ 20.00
#661-122-256AK	S-2	.256" (6.5)	1F18A31 \$ 20.00
#661-122-276AK	S-2	.276" (7.0)	1F18A31 \$ 20.00
#661-123-256AK	S-3	.256" (6.5)	1F24A31 \$ 28.00
#661-123-276AK	S-3	.276" (7.0)	1F24A31 \$ 28.00
#661-124-256AK	S-4	.256" (6.5)	1F52A31 \$ 59.00
#661-000-040AK	S-5	.256" (6.5)	1F33Y61 \$ 39.00
#661-000-041AK	S-5	.276" (7.0)	1F33Y61 \$ 39.00
#661-000-042AK	S-5	.315" (8.0)	1F33Y61 \$ 39.00
#661-000-043AK	S-5	.354" (9.0)	1F33Y61 \$ 39.00

N.E.C.G. RUGER® RIFLE FRONT SIGHTS



High-Visibility White Bead Or Fiber Optic Rod Speeds Target Acquisition

No-gunsmithing replacement front sights for Ruger No. 1® and M77® rifles feature sturdy, fully-machined bodies with a high-visibility white bead

or bright fiber optic rod for fast sight acquisition. Makes your front sight stand out even when aiming against dark foliage or muted backgrounds. Beautifully blued sight body blends with your rifle's original bluing.

SPECS: Steel body, blued. Fits factory sight ramp on Ruger No. 1 and M77 rifles. Heights given below are measured from bottom of base to top of sight. White Bead - White polymer bead, .300" (7.6mm) high, .940" (2.4mm) wide. Fiber Optic - Red fiber optic bead, .330" (8.38mm) high, .100" (2.5mm) wide

#661-000-064AK .300" White Bead Front Sight,

#661-000-066AK .330" Red Fiber Optic Front Sight, . \$ 26.00

SAMSON SIG 556/522 QUICK FLIP FOLDING FRONT SIGHT

Familiar AR Sight Picture, Rugged Construction & Reliable Mechanism

Machined aluminum replacement for factory front sight gives your Sig the familiar AR-15/M16 sight picture and lets you use readily-available AR-type clamp-



on Picatinny rear sights. Serves as a reliable backup sight that deploys and retracts with the press of the large, easy-to-find release button. Spring mechanism locks in both deployed and folded positions, and is concealed to resist fouling from dust and dirt. AR-style post is the correct height to regulate with Samson and other many other commercial Picatinny rail-mountable rear sights for the AR-15/M16 (will not work with SIG 556/522 factory rear sights). Post adjusts for elevation using the standard four-prong AR front sight tool. A2 model features a wide field of view and thick protective ears that guard the post from impact. HK model has globe-style ears to give you a centered target-style shooting picture.

SPECS: 6061 T6 aluminum, hardcoat anodized, matte black. 1" (2.5cm) long when deployed, 21/8" (5.4cm) long when folded, 11/4" (3.18cm) wide. Post height regulates correctly with Samson Quick Flip Folding Rear Sights and ARMS #40A/#40L rear sights (both available separately), plus most A2-height rail-mounted AR-15/M16 rear sights

#100-005-375AK A2 Front Sight 1B81V38 \$ 94.99 #100-005-374AK HK Front Sight 1B81V38 94.99



LIPSKI **COMPETITION REAR** SIGHT BASE

Easy Rear Aperture Sight Mounting For Target Rifles

Attach receiver-style target sights to your favorite rifle without drilling and tapping. AR-15 model clamps to flattops; WR fits Weaver-style bases. WR-MJT accepts Lyman MJT and Williams Target Foolproof Sights. Once sight is mounted to base, the entire unit may be removed and re-installed without loss of zero. Pre-drilled side mounting plate accepts Redfield Palma, Warner, Zelenak and other sights using 10-32 mount screws. Mounting plate is adjustable for vertical and horizontal position.

SPECS: Steel, matte black. Adapter base 2.25" (5.7cm) long, .90" (23mm) high. Threaded 10-32. Weighs 3.1oz. (68 g). #527-100-015AK AR-15 Sight Base 7B65P99..... \$ 80.95 #527-100-100AK WR Sight Base 7B65P99 80.95 #527-000-004AK WR-MJT Sight Base 7B65P99 80.95

MERIT #3 & #4TARGET SIGHT DISC



Adjustable Aperture **Eyepiece For Popular Target Sights**

Precision sight receiver discs with 10, click-adjustable iris settings (.022" to .125" dia.) let shooters

match peep sight aperture to light conditions. Internal spring eliminates face wobble. #3LS fits most Redfield, Lyman and Williams receiver sights. Separate model fits Browning 1885 factory sight. Master models add a 1½" (3.8cm) dia. flexible neoprene light shield and a steel cup that completely shades the opening. 💳

SPECS: Steel. 3/4" (19mm) dia. x 1/4" (6.3mm) thick disc. #3LS - 7/32" (5.6mm) - 40 thread on 5/16" (7.9mm) lg. shank. **Browning 1885 -** 10-32 thread shank fits Browning factory tang sights.

#571-003-001AK Merit #3LS 1G37B87	56.99
#571-003-002AK Merit #3LS Master 1G44B00	. 66.00
#571-003-004AK Browning 1885 1G37B33	. 56.00
#571-003-014AK Browning 1885 Master 1G44B00	. 66.00

#4 HUNTING SIGHT DISCS - Compact, adjustable receiver sight discs give choice of iris openings from .025" to .155" diameter. External "click" spring.

SPECS: Steel. $\frac{1}{2}$ " (12.7mm) diameter x $\frac{1}{4}$ " (6.3mm) thick disc, $\frac{7}{32}$ " (5.6mm) - 40 thread. #4LS - 11/32" (8.7mm) long shank. #4 10-32 - 5/16" (8.7mm) long shank, fits Marble tang sight. #4 \$\$ - 5/16" (8.7mm)

IUTIY STIATIK, TILS L	yrriari #2 tariy siyrit.
#571-000-002AK	#4 10-32 Sight Disc 1G32B50 \$ 48.99
#571-000-003AK	#4 SS Sight Disc 1G32B00 48.00
#571-004-002AK	Merit 4LS Sight Disc 1G32B72 48.99
	_

LIPSKI

COMPETITION BARREL BAND

Easy Mount, High Quality, Adjustable Target Base

No gunsmithing required to attach this heightadjustable, machined steel base to AR-15 and other heavy-barrel, match rifles. Clamp on muzzle and adjust riser block to correct height for rear sight. Accepts Redfield and similar target globe assemblies. 🔙

SPECS: Steel, matte black, Base - 1" (2.5cm) long, Fits .812" (20mm), .750" (19mm), .732" (18.6mm) (Colt factory Flattop competition) and .922" (23.4mm) barrels. 1.25" (3.2cm) high from center of barrel to top of base. Riser height adjusts 1" (2.5cm).

#527-101-812AK	.812" Comp. Barrel Band,	
	7B97P28	119.95
#527-101-750AK	.750" Comp. Barrel Band,	
	7B97P28	119.95
#527-101-732AK	.732" Comp. Barrel Band,	
	7B97P28	119.95
#527-000-003AK	.922" Comp. Barrel Band,	
	7B97P28	119.95



LIPSKI/SOUTH SHORE **BARREL BAND &** SIGHT BASE

Easy Aperture Sight Mounting For Target Rifles

No machining required, no holes to drill. Clamps quickly onto target contour barrels. Separate, heat treated, screw-on base is machined to accept Anschutz, Redfield and other, similar, target globe front sight assemblies.

SPECS: Steel, blue, matte finish. **Band -** 1" (2.5cm) long, fits barrels .750" (19mm), .812" (20mm), .835" (21.2mm) or .922" (23.4mm) diameter. **Bases -** 1" long, .562" c-to-c hole spacing, .175" (4.4mm), .225" (5.7mm), .275" (6.9mm) high.

#52/-100-/50AK .750" Barrel Band 7B32P6	55 \$ 40.95
#527-100-812AK .812" Barrel Band 7B32P6	35 40.95
#527-000-001AK .835" Barrel Band 7B32P6	35 40.95
#527-000-002AK .922" Barrel Band 7B32P6	35 40.95
#841-101-175AK .175" Sight Base 1D09Z99	12.99
#841-101-225AK .225" Sight Base 1D09Z75	12.00
#841-101-275AK .275" Sight Base 1D09Z75	12.00

BROWNELLS SIGHT APERTURES



A Complete Selection Of Williams Apertures

Have the right combination of aperture and disc always on hand. Perfect to change between hunting and target shooting or as replacements for missing ones. Fit Williams

and Lyman, 7/32"-40 sights.

STANDARD SHANK SIGHT APERTURES - Standard lengthshank fits Williams Foolproof, Target Foolproof, and 5D only. SPECS: 7/82"-40 thread. 3/6" or 1/2" STD Aperture Paks include three, 3%" or 1%" O.D. apertures: one each with .050", .093" and .125" aperture holes. 1/8" x .050" Target Aperture Pak includes three, 1/8" O.D. apertures with .050" aperture holes.

#080-766-380AK	3/8" Std. Aperture Pak 8K24C93 \$	59.99
#080-766-500AK	1/2" Std. Aperture Pak 8K30C28	36.99
#080-766-705AK	%" x .050" Tgt. Apts. 8K36C91	46.99

INDIVIDUAL STANDARD APERTURES - One Per Package

SPECS: 7/32"-40 thread. 3/8" Long Shank (L/S) or 3/8" Twilight, Long Shank (TW L/S) Aperture Paks include three, 3/8" O.D., long shank apertures: one each with .050", .093" and .125" holes. #080-784-380AK %" L/S Aperture Pak 8K33X34

3/8" TW L/S Aperture Pak,
<i>8K31X34</i>

TWILIGHT APERTURES - A light gathering brass ring surrounds the peep to enhance visibility in low light. Fits Foolproof, Target Foolproof, and 5D sights only.

SPECS: 1/2 -40 thread. Standard length shank. 3/8 Twilight (TW) Aperture Pak includes three 3/8" O.D. apertures: one each with .050", .093" and .125" aperture holes. Individual apertures also sold separately.

#080-767-380AK %" TW Aperture Pak 8K35C67.....\$ 47.99

INDIVIDUAL TWILIGHT APERTURES - One Per Package #080-767-050AK %" x .050" TW Aperture 8K12C33 ...\$ 17.99 #080-767-093AK %" x .093" TW Aperture 8K12C33 ... 17.99 #080-767-125AK %" x .125" TW Aperture 8K12C33 ... 17.99 #080-767-051AK ½" x .050" TW Aperture 8K12C33 ... 17.99 #080-767-126AK ½" x .125" TW Aperture 8K12C33 ... 17.99

ALLEY M1A/M14 **APERTURE** FRONT SIGHT

Globe Style Sight For M14/M1A & Garand Reduces Eve Fatique



Cleaner sight and target definition plus greatly reduced eyestrain for higher match scores. Installs easily; no permanent alterations to rifle. Legal in NRA "Match Rifle" category only. SPECS: Sight - Blued Steel, 1" (2.5cm) long, .625" (15.8mm) diameter, .8 oz. (25g) wt. Includes 1 aperture. Insert Set - Blued Steel, 2 post, 4 apertures included. Inserts also fit Redfield 65/66 series. #034-200-000AK Aperture Insert Set 4C11H79 16.99

FRIEND US ON FACEBOOK!



SATISFACTION GUARANTEED **SINCE 1939**

KENSIGHT M1 CARBINE REAR APERTURE SIGHT

High Quality Reproduction Of The Factory Original

Modern, high-quality reproduction of the original rear sight makes restoring your M1 carbine easier and the final job look authentic.



Patterned after the factory rear sight using modern CAD/CAM design techniques and wire EDM cut from 4140 bar stock for tight tolerances. Features audible clicks for precise windage adjustment and preset range increments for elevation adjustment. SPECS: Steel, blued, matte finish, Fits M1 Carbine.

#100-004-084AK Rear Aperature Sight,

LYMAN TARGET FRONT SIGHT



All steel front sight with eight interchangeable sight inserts that are locked into place by threaded cap. Sight includes insert set

SPECS: Sight tube-9/16" (14.3mm) dia.. Dovetail base is 3/8" (9.5mm) wide for standard dovetail. Use 17AML with 57SML Receiver sight, 17 ATC is for use with factory vernier tang sight on T/C muzzleloaders. 17AEU fits European 9mm (nominal .360" x .070") dovetail. **HEIGHT is from bottom of dovetail to**

STOCK #	MODEL	HEIGHT
#539-017-360AK	17AHB	.404"
#539-017-444AK	17AEU	.465"
#539-017-445AK	17AMI	.494"

center or aper	ture.				
STOCK #	MODEL	HEIGHT	STOCK #	MODEL	HEIGHT
#539-017-360AK	17AHB	.404"	#539-017-446AK	17AML	.494"
#539-017-444AK	17AEU	.465"	#539-017-532AK	17AUG	.584"
#539-017-445AK	17AMI	.494"	#539-017-852AK	17ATC	.854"
- Advise # -	17A F	ront Sig	ght 9C31H27		\$ 37.95

INSERTS FOR 17A SIGHTS - Spare insert set for the 17A. Set includes: two post inserts (.100" and .050" wide), one "pin head" insert, five aperture inserts (1 plastic .120" hole insert and four steel inserts with .070", .093", .110" and .120" holes). #539-017-001AK 17A Insert Set 9C14H42 \$ 17.50

LYMAN MJTTARGET SIGHT

90 MJT UNIVERSAL RECEIVER SIGHT

- Features windage and elevation knobs with click detents in minute and 1/4 minute graduations.

SPECS: Machined aluminum body, steel knobs. Matte black finish. Adjusts from 1.06" (2.6cm) to 1.56" (3.9cm) above bore line. Includes 7/8" (22mm) target disc w/.040" (1mm) aperture. Wt. 4 oz. (113g). Fits Williams Foolproof Bases, For .22RF target rifles.

#539-090-000AK MJT Receiver Sight,

9C83H10.....\$99.99

20 MJT GLOBE FRONT SIGHT - Machined steel, globe front with interchangeable inserts. SPECS: Steel, blued. 11/4" (3.1cm) long, .875" (22.2mm) diameter. 3/8" (nominal) dovetail. 1.8 oz. (51a) wt. .700" (17mm) from bottom of dovetail to

center of aperture. Includes 2 posts, 5 aperture inserts. #539-620-000AK MJT Globe Sight 9C41H15..... \$ 49.95

93 MJT AR-15 & MATCH RIFLES TARGET FRONT SIGHT - Ma-

chined steel globe front with interchangeable inserts. Knurled bezel locks aperture in place. Fits standard dovetail bases. Accepts Anschutz inserts. Quick-detach locking thumb-

screw retains sight on base. SPECS: Steel, blue, matte finish. .550" (13.9mm) from bottom of dovetail to center of aperture.

11/4" (3.1cm) long, .750" (19mm) diameter. Includes - five disc inserts with .126" (3.2mm), .154" (3.9mm), .161 (4.1mm), .169" (4.3mm), .177" (4.5mm) apertures; Two post inserts with .067" (1.7mm) and .102" (2.6mm) wide posts.

#539-620-100AK 93 Match Sight 9C53H51 \$ 64.95

LYMAN RECEIVER SIGHT

3 Styles Fit Hundreds Of Gun Models

Low-profile sights hug the receiver and

offer audible-click, ¼ minute adjustments for elevation and windage. Elevation slide is scribed in 3 minute increments. Quick release allows slide to be removed with a press of a button. Elevation stop screw permits

instantaneous return to zero. Model 57 is for round receivers; Model 66 is for flat receivers, 66 WB includes semi-target knobs. The 57 SML is a special model for tang installation on muzzleloaders such as T/C Hawken and similar rifles and includes semi-target knobs. The 57 SMET includes target knobs. SPECS: Aluminum, black, anodized. Comes with two apertures, b" (12.7mm) x .093" (2.3mm) and 5%" (15.8mm) x .040" (1.1mm)

½" (12.7mm) x .093" (2.3mm) and	d %" (15.8mm) x .040	" (1.1 mm).
FITS	STOCK #	MODEL
BROWNING Sako	#539-057-002AK	57 SME
BSA Majestic	#539-057-003AK	57 WJS
COLT Sako	#539-057-002AK	57 SME
ENFIELD		
U.S. 1917, .30/06		
British 1914 303B (altered receiver)	#539-057-002AK	57 SME
MARLIN	#333-037-002AK	37 SIVIE
39A	#E30 000 003 AV	66 MC
··	#539-066-003AK	66 LA
336 MOCEPERO 403	#539-066-002AK	
MOSSBERG 402	#539-066-003AK	66 MC
MUZZLELOADERS		
Lyman Great Plains, Trade, Deer Stalker	#539-000-001AK	57 GPR
T/C Hawken and others	#539-057-004AK	57 SML
IN-LINE MUZZLELOADERS	#333-037-004AK	37 SIVIL
White Systems In-line	#539-057-007AK	57 SMET
REMINGTON	#339-037-007AK	57 SIVIET
141	#539-066-001AK	66A
• • •		
700, 721, 722, 660	#539-057-003AK	57 WJS
XP-100	#539-057-003AK	57 WJS
SAVAGE 10, 110	#539-057-003AK	57 WJS
WINCHESTER		
64, 92, 94	#539-066-001AK	66 A
70	#539-057-003AK	57 WJS
1886 Win. & Browning	#539-000-004AK	66 WB
JAP Arisaka, 6.5mm, 7.7mm	#539-057-002AK	57 SME
MAUSER		
' 98; '91, '93, '94, '95, '96		
1904, 1909, 1936, G33/40	#539-057-002AK	57 SME
	#539-057-007AK	57 SMET
SPRINGFIELD 1903	#539-057-002AK	57 SME
	#539-057-007AK	57 SMET

- Advise # - Receiver Sight 9C83Y10..... \$ 99.99 TARGET KNOBS FOR LYMAN 57 - Knurled thumb knobs replace the original screws on the 57 series.

SPECS: Blued steel. Windage and Elevation Knob sold per each Fit Lyman 57 series only.

#539-399-262AK Target Elevation Knob 9C02H59 .. \$ 3.99 #539-399-261AK Target Windage Knob 9C02H59 3.99

FULTON ARMORY M1/M14/M1A REAR SIGHT ELEVATION KNOB

Replaces Worn-Out Part; Calibrated In Yards

Drop-in replacement for USGI-spec rear sight elevation knob. Calibrated in yards, with one minute of elevation at 100 yards per click, just like the original. Can also be used to replace the elevation knob on an M14/M1A to change rear sight calibration from meters to yards.

SPECS: Steel, Parkerized, matte black. Calibrated in yards. Fits M1 Garand and M14/M1A rifles.

#100-005-278AK Rear Elevation Knob 3K40V29 . . . \$ 49.99

N.E.C.G. CZ 550 GHOST RING PEEP SIGHT

Precision Crafted For Reliable Function; Fully Adjustable

Beautifully machined, all steel peep sight features the larger opening of a .096 I.D. ghost ring aperture for close range en-

counters with dangerous game. Extra-thick steel clamps with slotted, knurled knobs lock solidly to the rear square bridge on CZ 550 rifles. Integral indexing lug engages notch on left side of receiver for complete immobilization of sight and proper returnto-zero. Ghost ring provides a wide field-of-view and eliminates small peep obstruction caused by snow and other debris. Fine threaded sight post is locked in place with two, Allen head setscrews to prevent loosening under the heaviest recoil; each half of post turn yields approximately \(\frac{1}{2} \)" elevation correction at 100 yards. Left and right clamps adjust independently for precise windage control. Installation requires no modification to rifle. SPECS: Steel, blue, matte finish. $\frac{7}{6}$ " (2.2cm) long, $1\frac{1}{2}$ " (3.8cm) wide, $\frac{3}{4}$ " (1.9cm) high, .096" (2.4mm) diameter aperture. 1.7 oz. (48g) wt. Includes aperture adjustment tool and Allen wrenches.

#661-000-046AK CZ-550 Ghost Ring Sight,

1F79Y99 \$ 90.00

N.E.C.G PEEP-SIGHT

Provides Excellent Sight Picture, Clamps To Weaver-Style Bases

Solid-steel sight is fully adjustable for windage and elevation; provides a primary sight

when hunting dangerous game and a scope is not practical, or an emergency backup. Furnished with .093" and .125" diameter apertures; allows you to shoot very accurately, even under poor light conditions. Fits Weaver-style or Picatinny base, may be easily removed and returned to zero every time. Includes two elevation slides.

SPECS: Steel, blue finish, 11/8" (2.9cm) long, 11/2" (3.8cm) wide, 11 (2.5cm) high. Aperture - 7/32-40 thread, accepts Williams and Merit siaht discs.

#661-000-035AK Weaver Peep Sight 1F79Y99 \$ 90.00

N.E.C.G. RUGER® RECEIVER SIGHT

Clamps Quickly To Ruger® Integral Bases

Finely machined steel receiver sight clamps to factory ring notches on Ruger rifles; serves as a primary hunting sight in situations where a scope may not be practi-

cal. Pack as an emergency sight to save your hunt in case of scope failure. Install and remove without loss of zero. Height matches most M-77°, 77/22° and No. 1 factory front sights. Includes .093" and .125" apertures that draw your eye to the sight for fast sight alignment. Adjustable for windage and elevation.

SPECS: Steel, blue finish, 11/4" (3,2cm) long, 3/4" (19mm) high, 11/4 (3.2cm) wide.

#661-040-100AK Receiver Sight, for Ruger, 1F79Y99 \$ 90.00

N.E.C.G RIMFIRE RECEIVER SIGHT



Precision Target Acquisition; Mounts On Grooved Rimfire Receivers

Machined, steel peep sight gives you a precise sight picture for pin-point accuracy from your match or hunting rifle. Sight attaches to grooved, 3/81 dovetail, rimfire receivers. Fully ad-

justable for windage and elevation; comes with .093" and .125" apertures, plus a handy wrench for easy installation. SPECS: Steel, black, matte finish. 1" (2.5cm) long, ¾" (19mm) wide, 1/2" (12.7mm) high. .093" (2.3mm) and .125" (3.1mm) apertures. Fits grooved, 3/8" (9.5mm) rimfire receivers.

#661-000-044AK Rimfire Receiver Sight 1F79Y99. \$ 90.00

SMITH ENTERPRISE M14 TRITIUM CLOSE COMBAT SIGHT

Dependable Backup Sight For Close Range Combat In Low Light

Genuine Trijicon, self luminous vial makes this the perfect backup sight for close range combat in conditions with limited visibility. Wire EDM machined, steel ears protect the tritium vial. Dovetailed base securely clamps



to Mil-Spec M14 flash suppressors or the Smith Enterprise Gas Cylinder Lock with sight dovetail (found elsewhere in catalog). SPECS: 4140 chrome moly steel, black phosphate finish. .650" (1.6cm) long x .625" (1.5cm) wide. .4 oz. (11g) wt.

#851-000-065AK Tritium Close Combat Sight, 1E74C03 \$ 91.98

SMITH ENTERPRISE M1/M14/M1A FRONT & REAR SIGHTS

M14/M1A Front Sight

For Easy Restorations Or Competition

Replacement sights make it easy to upgrade your original military sights for improved accuracy. Provides a clear, easy-to-acquire sight

picture in all light conditions. Match front sights feature a narrow. .062" wide front blade for a crisp, clean sight picture at all normal competition ranges. Standard models have a .079" wide front blade to match original factory specifications. Garand **Tritium** front sight has a self-illuminating, green Tritium insert in the .091" wide blade for fast sight pick up in low-light conditions. Match Rear aperture sight includes 1/2" MOA windage adjustments and range elevation marks for easy sight-in. Fits M1 Garand and M14/M1A.

SPECS: Steel, Parkerized finish. Match Front - .062" (1.6mm) wide blade. Includes setscew. Standard Front - .079" (2mm) wide blade. Includes setscrew. Garand Tritium Front - .091" (2.3mm) wide blade. Includes clamping screw. Match Rear - .060" (1.5mm) I.D. aperature. Fits OEM dimensionally correct receivers.

#851-100-101AK Match M1 Garand Front Sight. ... \$ 49.99 #851-000-085AK M1 Garand Tritium Front Sight, #851-114-106AK Match M14/M1A Front Sight, #851-000-076AK M1 Garand/M14/M1A Match Rear Sight 1E242A51......**269.95**



TECH SIGHTS RUGER 10/22 GI-STYLE APERTURE SIGHTS

Provides Familiar M16 Service Rifle Sight Picture

Replacement sights give your 10/22 a longer sight radius for improved accuracy potential, plus the same sight picture as



AR-15/M16 military-issue sights. No gunsmithing, no drilling/ tapping, and no permanent alterations to the rifle. Rear sight mounts using the factory-provided holes for a scope base. Allsteel front sight assembly has a standard detent-locking M16 post surrounded by protective ears that guard it from damage and misalignment. Also accepts any aftermarket post that replaces the standard A2. TSR100 set's rear sight is adjustable for windage and features close-range and long-range flip-up apertures similar to the M16A2 sight. For even greater precision, the TSR200 set's rear sight has a single aperture with a rotating dial for fine adjustments in elevation; click adjustable for windage. SPECS: Front Sight-steel, blued, matte finish, .53" (13.4mm) wide, .90" (23mm) high. Rear Sight - aluminum, black finish. 2.9" (7.4cm) long. .94" (24mm) tall. Sold as front/rear sight sets.

#100-006-910AK TSR100 10/22 Sight Set 2C56A97 . \$ 59.99 #100-006-911AK TSR200 10/22 Sight Set 2C66A62 ... 69.99

order on the web

www.brownells.com

BROWNELLS PAGE 283



SHAVER LEVEL FRONT SIGHT

Eliminates Canting Of The Gun For Improved Accuracy

Quick-to-view level lets you position

the gun absolutely "square." Precision, spirit level mounted in removable steel housing is supplied, installed, on Shaver's own globe sight.

SPECS: Steel, blued. 111/32" (3.4cm) overall length, 13/16" (2.1cm) maximum width. .375" x .095" dovetail. Height from bottom of dovetail to center of aperture: **S-8 -** .525" (13.34mm); **S-16 -** .625" (15.87mm). Includes 6 post and aperture inserts.

781-101-008AK	S-8 Level Sight 1	H68P00	\$ 85.00
781-101-016AK	S-16 Level Sight	1H68P00	85.00

SHAVER GLOBE SIGHT INSERTS

Finer Crosshairs. Posts Or Silhouettes For **Greater Accuracy**





apertures do away with thick, bulky inserts; won't hide that 500 meter ram or tiny "black" you need to hit.

SPECS: 1095 spring steel, blued. .01" (.25mm) thick. Post & Aperture Card includes 3 apertures, 4 crosshairs, 3 posts. Lyman 17A also fits Browning BPCR. .470" (12mm) dia., Redfield/Alley - .550" (14mm) dia. Fits Redfield 65/66 and Alley globe sights. Large Lyman/Anschutz - .675" (17.1mm) dia., Parker-Hale - .587" (14.9mm) dia., Redfield International/Mid Tompkins - .769" (19.5mm) dia., Redfield Olympic - .700" (17.8mm) dia. All-Aperture Card features 10 apertures for Redfield Olympic, from .072" (1.8mm) dia. to .145"

POST & APERTURE CARD

STOCK #	MODEL	PRICE
#781-100-017AK	Lyman 17A Sight	1H17P69 \$ 21.95
#781-100-010AK	Redfield/Alley	1H17P33 \$ 20.00
#781-100-011AK	Large Lyman/Anschutz	1H17P33 \$ 20.95
#781-100-012AK	Parker-Hale	1H17P69 \$ 21.95
#781-100-013AK	Redfield Int. /Tompkins	1H17P69 \$ 21.95
#781-100-014AK	Redfield Olympic	1H17P69 \$ 21.95
	ALL APERTURE CARD	
CTOCK #	MODEL	DDICE

ALL AFENTONE CAND		
STOCK #	MODEL	PRICE
#781-100-016AK	Redfield Olympic	1H17P69 \$ 21.95

TRUGLO RIFLE SIGHT SET



Fully Adjustable, Fiber Optic Increases Visibility

Combination red front and green rear provides eye-catching contrast for quick sight

alignment. Fiber optic rods gather available light and draw your eve to the sights to get you on target fast. Machined aluminum body adjusts for windage and elevation. Front and rear set replaces factory sight without alteration or gunsmithing. Remington fits late production rifles and shotguns with adjustable sights. Ruger® 10/22® fits factory barrels. Winchester 94 fits models with a front sight ramp.

SPECS: Aluminum,	black, matte finish. Front and rear set.
HOOD OOD OOF ALL TO	D'fl G' -1 + C - +

#902-000-005AK	Rem. Rifle Sight Set,
	2K20T99
#902-000-006AK	Ruger 10/22 Rifle Sight Set,
	2K26T4837.61
#902-000-007AK	Winchester 94 Rifle Sight Set,
	2K26T48



TRUGLO DOVETAIL FRONT SIGHT

Metal Body For Durability; Bright Fiber Optic Insert Increases Visibility

Light-gathering, fiber optic rod offers a bright, eye-grabbing bead for fast sighting. Fits nominal 3/8" dovetail.

SPECS: Aluminum, black, anodized finish. 3/4" (19mm) long. Red or green optic rod is 3/4" long, .060" (1.5mm) diameter. Height measured from top of ramp to top of sight.

STOCK#	HEIGHT	COLOR
#902-000-008AK	.450"	Red
#902-000-011AK	.450"	Green
#902-000-010AK	.530"	Red

- Advise # - Dovetail Front Sight 2K12T31 \$ 17.45

TRIJICON® RIFLE SIGHT

Self-Luminous Replacement **Sights For Popular Rifles**

The ultimate, self-luminous rifle sight. Improves sight pickup and visibility during low-light hours when game is most ac-

tive. All sights include rugged sapphire crystal, self-illuminating Tritium lamps for a bright, well-defined aiming point and extralong life. Lamps guaranteed by the manufacturer to remain selfluminous for 12 years.

SPECS: Steel body, blued. Tritium insert. Includes front and rear sight unless shown in chart. All sights are adjustable if rifle or shotgun barrel was originally equipped with factory adjustable sights.

510CK#	FIIS	PRIC	_
#892-415-125AK	AR-15 A1/A2 front only	2H54V21 \$	56.10
#892-415-025AK			
	with 10-36 windage screws	2H76V45 \$	79.90
#892-407-001AK	Remington 74, 76, 760, 7400, 7600, 870, 1100, 11-87 (w/rifle		
	sights) front and rear 3-dot	2H104V25 \$ 1	109.65
#892-407-002AK	Rem., same as above, front only	2H65V33 \$	68.99

WEST ONE PRODUCTS RUGER® 10/22® M1 CARBINE-STYLE SIGHT SET



Authentic-Looking Sights For M1 Carbine "Look-Alike" Conversions

Steel sight set replaces the factory sights on a standard 10/22° barrel to add a realistic detail to your M1 carbine look-alike conversion. Front sight slips over front barrel band, and rear sight fits the factory rear

receiver scope base screw holes. Gives the same sight picture as original M1 carbine sights, but is calibrated for the .22 LR trajectory. Completes the "look" of an M1 carbine using the West One M1 Carbine Stock and Sling, both available separately.

SPECS: Steel, manganese phosphate finish, black. Rear - 11/4" (3.2cm) long, 5/8" (1.6cm) wide, 3/4" (1.9cm) tall, 0.7 oz, (20a) weight. Front - 34" (1.9cm) long, 11/16" (1.7cm) wide, 11/2" (3.8cm) high, 5/64 (2mm) sight blade. 1.2 oz. (34g) wt. Fits 10/22® standard 181/2" barrel. All mounting hardware included.

#100-006-289AK 10/22° M1 Carbine Sights,

WILDWEST GUNS LEVER RIFLE SIGHTS

Improves Sight Picture

Rear ghost ring improves sight picture and speeds target acquisition. Adjusts for windage and elevation. WPM 94 fits side-eject Winchester 94 only; requires drilling/tapping if receiver is not equipped with factory

mounting holes. WPM 95 fits Marlin factory scope base holes. SPECS: Steel, matte blued. Includes screws. WPM 94 fits Winchester 94. WPM 95 fits Marlin 1895, 1894, 336, and 30. #981-100-094AK WPM 94 Sight 1H119U99 \$ 129.99 #981-100-095AK WPM 95 Sight 1H99U99 109.99

WILLIAMS AK/SKS ADJUSTABLE REAR SIGHT

Drop-In Replacements For Military Front/Rear Sights

No gunsmithing required for increased accuracy and improved sight picture. Fully adjustable for elevation and windage. Easy to install. Replacement sight is held in place with a single, hardened, steel roll pin. Available with open blade or removable, aper-

ture rear sight for hunting or target shooting. SPECS: Aluminum, blued, matte finish. Open; 1/4" (6.3mm) wide "U" **Blade.** Aperture; 3/8" disc dia. with .150" dia. aperture. Includes roll pin and instructions. Fits all AK or SKS rifles and carbines.

#962-445-590AK Open SKS Sight 2F18D63...... \$ 21.99 #962-445-600AK Aperture SKS Sight 2F17D94 20.99 #962-474-760AK Aperture AK Sight 2F17D94 20.99

SKS FIRESIGHT SET - Bright, red fiber-optic front and adjustable aperture rear sight makes a fast, accurate sighting combination. Front blade fits in the SKS front sight housing; rear aperture re-

places the rear sight leaf with no gunsmithing required. Fully adjustable for windage and elevation.

SPECS: Aluminum, blue, matte finish. Fiber optic, red, sight dot. Aperture; 3/8" disc diameter with .150" diameter aperture.

#962-000-018AK SKS Firesight Set 2F27B57 \$ 31.99 SKS FRONT FIRE SIGHT - Fits in the SKS front sight aperture

with no gunsmithing required. Bright, red fiber-optic dot makes a great sighting combination when used with the Williams SKS Adjustable Rear Sight.

SPECS: Steel, blue, matte finish. Fiber optic, red, sight dot. #962-602-140AK SKS Front Sight Bead.

WILLIAMS MAUSER 96 APERTURE SIGHT



No Gunsmithing Replacement For Military Rear Sights

Drop-in for a vast improvement in sight picture over the military issue. Adjusts for wind-

age and elevation; works with original front sight. No permanent changes to rifle.

SPEČS: Aluminum, anodized, black, satin finish. Fits M96 and other Swedish military, small ring Mausers, 3/8"disc dia., 150" dia, aperture. Includes instructions.

#962-660-196AK Aperture M96 Sight 2F17P94 20.99

WILLIAMS GROOVED RECEIVER FOOLPROOF

Fits All Grooved Receiver .22's

groove that measures .300" to .600" wide. No drilling, tapping or modifications required. Internal micrometer adjustments with positive clicks, Lockscrews secure adjustments against accidental change. Mounts low but may require a higher than standard front sight.



SPECS: Aluminum , black, anodized body. Bright steel "standard style" windage and elevation screws. Blue steel aperture. FP-GR 13/4" (4.4cm) wide. 121/32" (4.2cm) high. Weighs 11/4 oz. (35 g). .0093" (2.4mm) aperture opening. FP-GR-TK: 25/32" (5.5cm) wide. 15/8" body. Blue steel "Target Knobs" adjust windage and elevation. .093" (2.4mm) aperture opening.

#962-200-810AK Foolproof FP-GR 2F53A75 \$ 62.99 #962-201-606AK Foolproof FP-GR-TK 2F62A03..... 71.99

WILLIAMS TARGET FOOLPROOF

Micrometer Click Adjustments

FOR .22 LR TARGET RIFLES Deluxe Model Show - True, target receiver sights with positive-click, micrometer adjustments on both windage and elevation, knurled target knobs and elevation lock. All come with 7/8" x .050" aperture sight disc.



SPECS: Aluminum, black, anod-

ized, HIGH, for target rifles with globe fronts, Aperture 1,250"-1,750" above bore axis. LOW for sporter rifles with standard front sights (may require a higher bead). Aperture .750" to 1.250" above bore

962-201-001AK	Target FP	High	2F56C51	\$ 65	5.99
962-201-002AK	Target FP	Low	2F56C51.	65	5.99

DELUXETARGET FOOLPROOF - Adds markings and arrows for "UP" and "R". Uses steel, quick-release elevation nut for elevation/windage overarm.

SPECS: Aluminum, black, anodized. Line of sight is 1.250"- 1.750" above bore axis.

#962-201-210AK D/T Foolproof Sight 2F68A93 \$ 79.99

TARGET FOOLPROOF BASES - Adapt sights above to .22 rifles.

SPECS: Rem. 51	0 also fits 51	11, 512,	. 513T, 5	521T. Rem.	540X a.	lsc
fits 541S, 580, 58	1, 582.					
#962-201-075AK	Target FP	Base,	Win. 78	5 2F15A11	\$ 17.	99
#962-201-510AK	Target FP	Base.	Remin	gton 510.		
	2F15A11				17.	99
#962-201-540AK	Target FP	Base.	Remin	gton 540X.		
	2F15A11				17.	99

WILLIAMS RIFLE SIGHT BEAD



Thin, streamlined, almost invisible blade with a machined bead gives a crisp, highly vis-

ible sight picture.

SPECS: Steel blade, blued, Brass bead, polished, Nominal .375' dovetail. Narrow are .250" (6.35mm) wide to fit Williams Streamlined and Shorty Ramps. Medium are .340" (8.6mm) wide to fit factory ramps including Marlin and Remington. Wide are .531' (13.5mm) for dovetailed barrels on .22 rifles and muzzleloaders. All heights include the .090" thick dovetail portion itself.

HEIGHT	WIDTH	⅓ ₁₆ " GOLD	3/32" GOLD
.260"	Narrow	#962-161-250AK	#962-165-250AK
.260"	Medium	#962-161-251AK	NA
.281"	Narrow	#962-161-290AK	#962-165-290AK
.281"	Medium	#962-161-291AK	NA
.312"	Narrow	#962-161-310AK	#962-165-310AK
.312"	Medium	#962-161-311AK	#962-165-311AK
.343"	Narrow	#962-161-340AK	#962-165-340AK
.343"	Medium	#962-161-341AK	#962-165-341AK
.343"	Wide	#962-161-342AK	NA
.375"	Narrow	#962-161-370AK	NA
.375"	Medium	#962-161-371AK	#962-165-371AK
.375"	Wide	#962-161-372AK	NA
.406"	Medium	#962-161-401AK	#962-165-401AK
.410"	Wide	#962-161-402AK	NA
.450"	Narrow	#962-161-450AK	NA
.450"	Medium	#962-161-451AK	#962-165-451AK
.450"	Wide	#962-161-452AK	NA
.500"	Wide	#962-161-502AK	NA
.538"	Medium	#962-161-531AK	NA
.570"	Medium	#962-161-571AK	NA

- Advise # - Williams Gold Bead, .260" thru .450" high,

SATISFACTION GUARANTEED **SINCE 1939**

BROWNELLS PAGE 284

HEIGHT/

WIDTH

406 M

450 M

500 M

538 M

570 M

375 W

410 W

437 W

500 W

538 W

570 W

Rear	Rea
Sight	Blad Heig
C	OMN
BRO	NINWC
BRC Barrel Diameter 4" Barrel Diameter at Height of Factory F	ahead o Muzzle Ramp an
FP-98 WGOS-L WGOS-L	3/16 1/4
BROW! Barrel Diameter 4" Barrel Diameter at Height of Factory F	VING 3 ahead o Muzzle
FP-98 WGOS-L	3/16 1/4
WGOS-L	
Barrel Diameter at Barrel Diameter at Height of Factory F	BROW Muzzle Dovetai lamp an
WGRS-BAR WGOS-BAR- Special	3/16 3/16
WGOS-BAR-L	
Barrel Diameter 4" Barrel Diameter 22 Height of Factory F	MARLI ahead o -1/2" ah Ramp an
FP-39 or 5D-39 WGOS-M	3/16
Barrel Diameter 4" Barrel Diameter 22 Height of Factory F	ahead o " ahead Tamp an
FP-36 or 5D-94/36 WGOS-L	3/16
REMII Barrel Diameter 3" Barrel Diameter 18 Height of Factory F	NGTOI ahead o " ahead Ramp ab
FP-760N, 5D-760N 5D-510 (for round	-
receiver) WGOS-S WGOS-S	1/4' 5/16 3/8'
WGOS-S	-
Barrel Diameter 4- Barrel Diameter 23 Height of Factory F	REMINO 1/4" ahea " ahead
	_
5D-510 WGOS-2 or M WGOS-S or M	3/16 1/4
	DE
Barrel Diameter 4- Barrel Diameter 22 Height of Factory F	ahead ront Sig
WGOS-S or M	3/16
F Barrel Diameter 4" Barrel Diameter at Height of Factory F	ahead o Muzzle Ramp an
FP-740 AP 5D-572	- :
WGRS-54 WGOS-M WGOS-M	1/4' 5/16
Barrel Diameter 3- Barrel Diameter 21 Height of Factory F	RF
	ront Sig
FP-740 AP WGOS-M WGOS-M	3/16 3/16

					WILLIAMS SIGHT
Rear Sight	Rear Blade Height	Williams Ramp Height	Williams Bead Height	Tot. Frnt Height abv. Bbl.	Rear Rear Williams Williams Tot. Frnt Sight Blade Ramp Bead Height Height Height Height abv. Bbl.
CC	OMME	RCIAL F	IFLES		REMINGTON 721, 722 Barrel Diameter 5-1/4" ahead of Receiver .750
		0-'06 (FN			Barrel Diameter 22" ahead of Receiver .605 Height of Factory Ramp and Bead above Barrel .535
Barrel Diameter 4" : Barrel Diameter at I	ahead of Re		.98		
Height of Factory R		ad above Ba			FP-70, 5D-70 - 3/8" .312 .594 WGOS-M 1/4" 5/16" .312 .531
FP-98			.280	.594	WGOS-M 5/16" 3/8" .312 .594 WGOS-M 3/8" 7/16" .312 .656
WGOS-L WGOS-L	3/16" 1/4"	3/8" 7/16"	.312 .312	.594 .656	
	NING 308 A ahead of Re Muzzle	AND 270 (I	FN Mause .98 .50	r) 0	REMINGTON 760, 740, 742 Barrel Diameter 4-12" ahead of Receiver .800 Barrel Diameter 20-34" ahead of Receiver .800 Height of Factory Front Sight above Barrel (old style) .425 Height of Factory Front Sight above Barrel (new style) .840
	anip and be				FP-760 or 5D-570/740 - 5/16" .281 .500
FP-98 WGOS-L	3/16"	7/16" 7/16"	.345 .281	.689 .625	WGOS-M 3/16" 5/16" .281 .500
WGOS-L	1/4"	7/16"	.345	.689	WGOS-M 5/16" 7/16" .281 .625 WRGS-760 - 7/16" .281 .625
E Barrel Diameter at I Barrel Diameter at I Height of Factory R	Muzzle Dovetail	IG AUTO R	.60	5	REMINGTON 788 Barrel Diameter 4-1/2" ahead of Receiver .893 Barrel Diameter 4-1/2" at Muzzle .587
WGRS-BAR	-	7/16"	.345	.6895	Height of Factory Ramp and Bead above Barrel .826
WGOS-BAR- Special	3/16"	7/16"	.345	.6895	FP-788 - 5/16" .312 .531
WGOS-BAR-L	3/16"	3/8"	.281	.563	
Barrel Diameter 4": Barrel Diameter 22- Height of Factory R	ahead of Re -1/2" ahead o	of Receiver	.78 .67	5	RUGER 10-22 Barrel Diameter 2" ahead of Receiver .860 Barrel Diameter at Muzzle .580 Height of Factory Ramp and Bead above Barrel .412
FP-39 or 5D-39	-	1/8"	.312	.344	FP-RU450 Beac
WGOS-M	3/16"	9/32"	.260	.448	5D-RU450 Beac WGRS-RU450 Beac
	MAI	RLIN 336			WGOS-L 3/16"583 Beac
Barrel Diameter 4": Barrel Diameter 22' Height of Factory R	ahead of Re ahead of Re amp and Be	ceiver eceiver ad above Ba	.86 .64 rrel .48	0	RUGER 44 MAGNUM Barrel Diameter 4-1/4" ahead of Receiver .816 Barrel Diameter 17-1/2" ahead of Receiver .625 Height of Factory Ramp and Bead above Barrel .475
5D-94/36 WGOS-L	3/16"	5/16" 9/32	.312 .312	.531 .500	
					FP-RU, 5DRU - 5/16" .312 .531 WGOS-M 3/16" 9/32" .312 .500
Barrel Diameter 3": Barrel Diameter 18' Height of Factory R	ahead of Re ' ahead of R	eceiver	76, 10, 11, .62 .62	5 5	WGOS-M 3/8" 7/16" .345 .689 WGRS-44 - 3/8" .281 .563
FP-760N, 5D-760N 5D-510 (for round	-	3/8"	.281	.563	Barrel Diameter 4-1/2" ahead of Receiver .505 Barrel Diameter at Muzzle .505
receiver) WGOS-S	1/4"	3/8" 9/32"	.281 .281	.563 .469	WGOS-L - 9/32" .312 500 5D-22/410 - 9/32" .260 .450
WGOS-S WGOS-S	5/16" 3/8"	5/16" 3/8"	.312 .312	.531	
	EMINGTO 1/4" ahead of " ahead of R	N 510, 51 Receiver eceiver	1, 512 .74	5	SAVAGE 99DL, 358 Barrel Diameter 4-1/2* ahead of Receiver
5D-510 WGOS-2 or M	3/16"	3/16" 9/32"	.281 .281	.375 .469	FP-99S - 3/8" .260 .542 WGOS-M 3/16" 5/16" .281 .500 WGOS-M 1/4" 3/8" .281 .563
WGOS-S or M	1/4"	5/16"	.312	.531	
Barrel Diameter 4-1 Barrel Diameter 22' Height of Factory Fi	/4" ahead of " ahead of R	eceiver	.73 .60 .25	7	SAVAGE 99E (old style) Barrel Diameter 3-3/4" ahead of Receiver .870 Barrel Diameter 22" ahead of Receiver .585 Height of Factory Ramp and Bead above Barrel .500
WGOS-S or M	3/16"	9/32"	.281	.469	FP.99S - 9/32" .312 .500 WGOS-L 3/16" 3/8" .260 .542
R Barrel Diameter 4" : Barrel Diameter at I Height of Factory R	ahead of Re Muzzle		.74 .62	5	SAVAGE 99F, .308 Barrel Diameter 4-1/2" ahead of Receiver .665 Barrel Diameter 20-1/4" ahead of Receiver .575
FP-740 AP 5D-572 WGRS-54	-	9/32"	.281	.570 .469 .570	Height of Factory Ramp and Bead above Barrel
WGOS-M	1/4"	9/32"	.312	.500	WGOS-S 1/4" 3/8" .281 .563
WGOS-M	5/16"	3/8"	.312	.594	SAVAGE 99R, 99EG, .300 SAVAGE
Barrel Diameter 3-1 Barrel Diameter 21- Height of Factory F	1/2" ahead of -1/2" ahead o	of Receiver	.75 .61: .32	9	Barrel Diameter 3-3/4" ahead of Receiver
FP-740 AP WGOS-M	3/16"	3/16" 9/32"	.312 .281	.406 .469	FP-99S - 9/32" .260 .448 WGOS-L 3/16" 5/16" .312 .531
WGOS-M	3/16" VINGTON ahead of Re ahead of Re	3/16" 580, 581, ceiver eceiver	.375	.469 5	SAVAGE 110 Barrel Diameter 3-1/4" ahead of Receiver .775 Barrel Diameter 19-12" ahead of Receiver .575 Height of Factory Ramp and Bead above Barrel .600
WGRS-54	-	9/32"	.312	.500	FP-110 - 7/16" .260 .605 WGOS-M .1/4" 3/8' .281 .563
WGOS-S WGOS-S Barrel Diameter 5-1 Barrel Diameter 20'	/4" ahead of		.312 .312 725 .79	.406 .469	WGOS-M 5/16* 7/16* .281 .625 SAVAGE 340 Barrel Diameter 3-1/4* ahead of Receiver .820 Barrel Diameter 19* ahead of Receiver .600
Height of Factory R					Height of Factory Ramp and Bead above Barrel .475

### AND CONTROLL OF THE PROPERTY OF THE PROPER	Rear Sight	Rear Blade Height	Williams Ramp Height	Williams Bead Height	Tot He abv
Height of Factory Ramp and Bead above Barrel	Barrel Diameter 4-1	WEATHE /4" ahead o	RBY MAR	KV .73	0
or Left Handi MS (1940)	Barrel Diameter at Height of Factory R	Muzzle		.55 rrel -	5
### Barrel Diameter 5" ahead of Receiver ### 256 ### Barrel Diameter 2-1/2" ahead of Receiver ### 250 ### Barrel Diameter 4" ahead of Receiver ### 250 ### Barrel Diameter 4" ahead of Receiver ### 250 ### Barrel Diameter 4" ahead of Receiver ### 250 ### Barrel Diameter 4" ahead of Receiver ### 250 ### Barrel Diameter 4" ahead of Receiver ### 250 ### Barrel Diameter 4" ahead of Receiver ### 250 ### Barrel Diameter 5" ahead of Receiver ### 250 ### Barrel Diameter 5" ahead of Receiver ### 250 ### Barrel Diameter 5" ahead of Receiver ### 250 ### Barrel Diameter 5" ahead of Receiver ### 250 ### Barrel Diameter 2-1/2" ahead of Receiver ### 250 ### Barrel Diameter 2-1/2" ahead of Receiver ### 250 ### Barrel Diameter 2-1/4" ahead of Receiver ### 250 ### Barrel Diameter 2-1/4" ahead of Receiver ### 250 ### Barrel Diameter 5-	or Left Hand) MS WGOS-S		7/16" 5/16" 7/16"	.312	.!
WINCHESTER 63	Barrel Diameter 5": Barrel Diameter 22:	ahead of Re	ceiver of Receiver	.72 .58	4
Barrel Diameter 4" ahead of Receiver					0 .4
FP-94	Barrel Diameter 21-	ahead of Re 1/2" ahead	ceiver of Receiver	.71	5
### WINCHESTER 64, 30-30 Barrel Diameter 5" ahead of Receiver	FP-94	-	3/16"	.312	-
Starte Diameter 5" ahead of Receiver 782 782 782 783 782 782 783 782 783 783 783 783 783 783 783 784 785			•		4
SD-94/36	Barrel Diameter 5" Barrel Diameter 22	ahead of Re -1/2" ahead	ceiver of Receiver	.78 .56	5
Barrel Diameter 2-34" ahead of Receiver .588 arrel Diameter 5-14" ahead of Receiver .588 height of Factory Front Sight above Barrel .232 .332 .332 .332 .332 .332 .332 .33	5D-94/36	- 3/16"			.5
WINCHESTER 70 WESTERNER, STANDARE Barrel Diameter 5-14" shead of Receiver	Barrel Diameter 23	4" ahead o	f Receiver of Receiver	.78	8
Barrel Diameter 5-14" ahead of Receiver 7-90 Arrel Diameter 22" ahead of Receiver 3-18 Arrel Diameter 22" ahead of Receiver 4-18 Arrel Diameter 3-18 Arrel Diameter 3-18 Arrel Diameter 3-18 Arrel Diameter 4-14" ahead of Receiver 7-95 Arrel Diameter 4-14" ahead of Receiver 8-18 Arrel Diameter 3-18 Arrel Diameter 4-18 Arrel Diameter 5-18 Arrel Di					-
Section Sect	WGOS-M	•	5/16"	.281	
WINCHESTER 94, 30-30, 32 WINCHESTER 100, 243, 308 WINCHESTER 100, 3243, 345 WINCHESTER 100, 3243,	Barrel Diameter 4-1 Barrel Diameter 20	/4" ahead o " ahead of R	f Receiver eciever	.79 .56	5 5
Barrel Diameter 4-14" ahead of Receiver .800	FP-70, 5D-70 WGOS-M	1/4"			.5 .5
WGOS-M 3/16" 5/16" 3.12 3/16" WGOS-M 3/8" 3/16" 3/12" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/12" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/12" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/12" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/12" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/16" 3/12" 3/16" 3/16" 3/16" 3/16" 3/12" 3/16" 3/12" 3/16" 3/12" 3/16" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/12" 3/12" 3/16" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/16" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12" 3/12" 3/16" 3/12	Barrel Diameter 4-1 Barrel Diameter 20' Height of Factory R	/4" ahead o ahead of R	f Receiver eceiver	.80	5
Barrel Diameter 4" ahead of Receiver 7.45	WGOS-M WGOS-M	3/16" 3/8"	5/16" 7/16"	.312 .345	.6
FP-94 or 5D-94-36 3/16" 9/32" 2.81 WINCHESTER 100, 243, 308 Barrel Diameter 4-14" ahead of Receiver 560 Height of Factory Ramp and Bead above Barrel 4-40 Height of Factory Ramp and Bead above Barrel 4-40 Height of Factory Ramp and Bead above Barrel 4-40 FP-88 3/16" 5/16" 2.81 WILLITARY RIFLES WILLITARY RIFLES 30 CARBINE Barrel Diameter 2-1/2" ahead of Receiver 4-50 Barrel Diameter 18" ahead of Receiver 5.75 Barrel Diameter 18" ahead of Receiver 4-50 Barrel Diameter	Barrel Diameter 4" Barrel Diameter 18	ahead of Re -1/2" ahead	ceiver of Receiver	.74	0
WINCHESTER 100, . 243, .308	FP-94 or 5D-94-36		5/16"	.260	
WGRS-100 3/8" 7/16" 3.445	WI Barrel Diameter 4-1 Barrel Diameter 20' Height of Factory R	NCHESTE /4" ahead o " ahead of R amp and Be	FR 100, . 24 f Receiver eceiver ad above Ba	.78 .56 rrel .44	5 0 0
30 CARBINE 30	WGOS-M WGRS-100	3/8"	7/16" 3/8"	.345 .345	
Height of Military Front Sight above Barrel .450 WGRS-M1-CAR - 9/32" .312 .1 FP-30-M1 - 3/16" .260 Military Rear .9/32" .260 WGOS-S 1/4" 3/16" .312	Barrel Diameter 2-1 Barrel Diameter 18'	30 (/2" ahead o ' ahead of R	CARBINE f Receiver eceiver	.70	
FP-30-M1 - 3/16" .260 Military Rear - 9/32" .260 WGOS-S 1/4" 3/16" .312	Height of Military F	ront Sight a	bove Barrel	.45	Ó
	FP-30-M1 Military Rear WGOS-S		3/16" 9/32" 3/16"	.260 .260 .312	1.0

	Barrel Diameter 4-1/4" Barrel Diameter 22" ah Height of Military Fron
.656 .531 .656	5D-JEMS or FP-JAP WGOS-M WGOS-M WGOS-M
.469	Barrel Diameter 4-1/4" Barrel Diameter 22" at Height of Military Fron 5D-JEMS or FP-JAP WGOS-M WGOS-M WGOS-M
.406 .469	Barrel Diameter 4-1/4" Barrel Diameter 21" al Height of Military Fron FP-A-KRAG WGOS-L WGOS-L
.500 .500	WGOS-L Barrel Diameter 4-1/4" Barrel Diameter 22" at Height of Military Fron FP-98 or 5D-JEMS WGOS-L WGOS-L
.469 RD	Barrel Diameter 4-1/4" Barrel Diameter 22" at Height of Military Fror FP-98 or 5D JEMS WGOS-M WGOS-M
.594 .563	Barrel Diameter 4-1/4" Barrel Diameter 22" ah WGOS-M WGOS-M WGOS-M
.531 .531 .689 .594	Barrel Diameter 4-1/4* Barrel Diameter 22* at Height of Military Fror FP-SMLE or 5D-SMLE WGOS-S WGOS-S
.479 .469	Barrel Diameter 4-1/4" Barrel Diameter 22" ah Height of Military Fron FP-SMLE or 5D-SMLE WGOS-M WGOS-M
.479 .500 .689	Barrel Diameter 4-1/4* Barrel Diameter 20-1/2 OD of Flash Hide Height of Military Fron FP-SMLE or 5D-SMLE WGOS-S WGOS-S
.627	'03 Barrel Diameter 4- Barrel Diameter 22" al Height of Military Fron FP-'03 or 5D-JEMS WGOS
.500 .354 .448 `.406 .469	Special WGOS Special 751

Bead Height Height abv. Bbl.

1917 ENFIELD

Barrel Diameter 4-1/4" ahead of Receiver

5D-JEMS

.531 .533 .531

Barrel Diameter 22" ahead of Receiver Height of Military Front Sight above Barre

Rear Sight	Rear Blade Height	Williams Ramp Height	Williams Bead Height	Tot. Frnt Height abv. Bbl.	
		6.5 JAP			'
Barrel Diameter 4-1 Barrel Diameter 22 Height of Military F	I/4" ahead o " ahead of R	f Receiver eceiver	.73 .63	5 5	
	ront Sight a	bove Barrel	-		
5D-JEMS or FP-JAP		7/16"	.260	.604	
WGOS-M	1/4"	5/16"	.281	.500	
WGOS-M WGOS-M	5/16" 3/8"	3/8" 7/16"	.281 .281	.563 .625	
***************************************	-,-		.201	.020	' I
Barrel Diameter 4-1	1/4" ahead o	7 JAP f Receiver	.74	5	
Barrel Diameter 22 Height of Military F	ahead of R	eceiver	.62	0	
5D-JEMS or	Tonic orgini a	Dove Dairei			1 I
FP-JAP	-	7/16"	.260	.604	
WGOS-M WGOS-M	1/4" 5/16"	5/16" 3/8"	.312 .312	.531 .594	
WGOS-M	3/8"	7/16"	.312	.656	
	AMER	ICAN KRA	G		
Barrel Diameter 4-1 Barrel Diameter 21 Height of Military F	1/4" ahead o	f Receiver	.89 .67	0	
Height of Military F	ront Sight a	bove Barrel	.67	0	
FP-A-KRAG	-	7/16"	.312	.656	ı I
WGOS-L	1/4" 5/16"	3/8" 7/16"	.281 .281	.563 .625	
WGOS-L WGOS-L	3/8"	7/16"	.345	.689	
	GERMAN	1 98 MAU	SER	•	·
Barrel Diameter 4-1	1/4" ahead o	f Receiver	.90	0	
Barrel Diameter 22 Height of Military F	anead of R ront Sight a	eceiver bove Barrel	.60 .48		- 1
FP-98 or	1		1 .40	I	ı 1
5D-JEMS		3/8"	.281	.563	
WGOS-L WGOS-L	1/4" 3/8"	3/8" 7/16"	.281 .345	.563 .689	
	!	E MALICE	DC DC		' I
Barrel Diameter 4-1 Barrel Diameter 22	91, 94, 9 1/4" ahead o	5 MAUSE f Receiver	.76	0	
Barrel Diameter 22 Height of Military F	ahead of R	eceiver	.68	5	
FP-98 or	Tonic Signica	Tove barrer	.40	1	, I
5D.JEMS	-	3/8"	.281	.563	
WGOS-M WGOS-M	1/4" 5/16"	5/16" 3/8"	.312 .312	.531 .594	
WGOS-M	3/8"	7/16"	.312	.656	
	7.62 RU	SSIAN M	91		
Barrel Diameter 4-1 Barrel Diameter 22	1/4" ahead o	f Receiver	.75 .65	0	
WGOS-M	1/4"	5/16"	.281	.500	, I
WGOS-M WGOS-M WGOS-M	5/16"	3/8"	.281	.563	
WGOS-M	3/8"	7/16"	.281	.625	l I
	#1	SMLE			
Barrel Diameter 4-1 Barrel Diameter 22	I/4" ahead of " ahead of R	f Receiver	.71 .58	2	
Height of Military F	ront Sight a	bove Barrel	.74	0	1
FP-SMLF or					
5D-SMLE WGOS-S	1/4"	7/16" 5/16"	.312 .312	656 .531	1
WGOS-S	3/8"	7/16"	.312	.656] [
	#4	SMLE			- 1
Barrel Diameter 4-1 Barrel Diameter 22	1/4" ahead o	f Receiver	.77	5	
Barrel Diameter 22 Height of Military F	anead of R ront Sight a	bove Barrel	.63 .77	0	
FP-SMLE or					
5D-SMLE WGOS-M	1/4"	7/16" 5/16"	.312 .312	.656 .531	
WGOS-M WGOS-M	3/8"	7/16"	.312	.656	
	#5	SMLE			
Barrel Diameter 4-1 Barrel Diameter 20	1/4" ahead o	f Receiver	.71		
Barrel Diameter 20 OD of Flash H	-1/2" ahead ider Should	of Receiver be Cut to 75	.75 0	0	- 1
Height of Military F	ront Sight a	bove Barrel	.77	0	- 1
FP-SMLE or					ı 1
5D-SMLE WGOS-S	1/4"	9/32" 3/16"	.260 .345	.448 .439	
WGOS-S WGOS-S	5/16"	9/32"	.345	.500	.
	'03 SP	RINGFIELI			
03 Barrel Diameter Barrel Diameter 22	4-1/4" ahea	d of Receive	r .93	0	- 1
Barrel Diameter 22 Height of Military F	" ahead of R ront Sight a	eceiver bove Barrel	.66	0 7	
FP-'03 or	I	T	.,-		1 1
5D-JEMS	-	9/16"	.260	.729	
WGOS Special	3/16"	7/16"	.312	.656	
opetial	3/10	1 "10	1 .012	.000	

Barrel Diameter 4-1 Barrel Diameter 21' Height of Military F	.89 .67 .46	0					
FP-A-KRAG	-	7/16"	.312	.656			
WGOS-L	1/4"	3/8"	.281	.563			
WGOS-L	5/16"	7/16"	.281	.625			
WGOS-L	3/8"	7/16"	.345	.689			
GERMAN 98 MAUSER Barrel Diameter 4-1/4" ahead of Receiver .900							

Barrel Diameter 4-1 Barrel Diameter 22' Height of Military F	/4" ahead of ahead of Re	eceiver	.90 .60 .48	Ō	
FP-98 or 5D-JEMS WGOS-L WGOS-L	1/4" 3/8"	3/8" 3/8" 7/16"	.281 .281 .345	.563 .563 .689	

	91, 94, 9	5 MAUSE	RS		
Barrel Diameter 4-1	/4" ahead o	f Receiver	.76	0	
Barrel Diameter 22'	' ahead of R	eceiver	.68	5	
Height of Military F	ront Sight a	bove Barrel	.48	5	
FP-98 or					•
5D JEMS	-	3/8"	.281	.563	
WGOS-M	1/4"	5/16"	.312	.531	

Barrel Diameter 4-1 Barrel Diameter 22 Height of Military F	1/4" ahead of F	Receiver	.71 .58 .74	0
FP-SMLE or 5D-SMLE WGOS-S	1/4"	7/16" 5/16"	.312	656 .531

#4 SMLE Barrel Diameter 4-1/4" ahead of Receiver .775 Barrel Diameter 22" ahead of Receiver .630 Height of Military Front Sight above Barrel .770			
FF-SMLE or 5D-SMLE - 7/16" .312 .656 WGOS-M 1/4" 5/16" .312 .531 WGOS-M 3/8" 7/16" .312 .656			

Barrel Diameter 4-1	/4" ahead o	f Receiver	.71	17
Barrel Diameter 20-1/2" ahead of Receiver .750				50
OD of Flash Hider Should be Cut to 750				
Height of Military Front Sight above Barrel .770				
FP-SMLE or				
5D-SMLE	-	9/32"	.260	.448
WGOS-S	1/4"	3/16"	.345	.439
WGOS-S	5/16"	9/32"	.312	.500

Height of Military Front Sight above Barrel			.747	
FP-'03 or 5D-JEMS WGOS	-	9/16"	.260	.729
Special WGOS	3/16"	7/16"	.312	.656
Special 751	5/16"	9/16"	.281	.751

'03-A3 SPRINGFIELD 900 '03-A3 Barrel Diameter 4-1/4' ahead of Receiver .900 Barrel Diameter 22' ahead of Receiver .600 Height of Military Front Sight above Barrel .820				
FP-'03-A3 or				
'03-A3	-	9/16"	.312	.781
WGOS				
Special	5/16"	9/16"	.312	.781
WGOS				
Special	3/8"	9/16"	.345	.815
WGRS-'03-A3	-	9/16"	.345	.814

WILLIAMS RIFLE FIRE SIGHT

Glowing, Fiber Optic Dots For Fast Sight Pickup

Easy-to-install front sights for popular centerire and muzzleloading rifles gather ambient light for superb risibility. The more light, the brighter the round, red beads glow; von't "wash out" even in the strongest sunlight. Narrow sights fit Williams Streamlined and Shorty Ramps. Medium sights fit most factory ramps including Marlin and Remington. Wide ights are for .22 rimfire rifles and muzzleloaders. 💳

SPECS: Blued steel, Fiber optic insert, Beads: 1/16" (1.6mm) dia, Fit nominal 3/8" dovetail. Number indicates height, letter (N, M or W) ndicates base width. Height is measured from bottom of dovetail o top of sight. **N Series -** .250" (6.3mm) wide base. **M Series -** .340" (8.6mm) wide base. **W Series -** .531" (13.5mm) wide base.

FIRE SIGHT RIFLE BEADS - RED

FIRE SIGHT KIFLE BEADS - KED				
STOCK #	HEIGHT/ WIDTH	STOCK #		
962-564-320AK	260 N	#962-564-440AK		
962-564-330AK	290 N	#962-564-450AK		
962-564-340AK	312 N	#962-000-085AK		
962-564-350AK	343 N	#962-564-460AK		
962-564-360AK	375 N	#962-564-470AK		
962-564-370AK	406 N	#962-590-830AK		
962-564-380AK	450 N	#962-590-840AK		
962-564-390AK	260 M	#962-590-790AK		
962-564-400AK	290 M	#962-590-800AK		
962-564-410AK	312 M	#962-590-810AK		
962-564-420AK	343 M	#962-590-820AK		
962-564-430AK	375 M			

- Advise # - Rifle Fire Sight 2F13D77..... \$ 15.99

FIRE SIGHT ASSORTMENT - Have the nost popular sights on-hand for quick epairs and installations to get your cusomers back to shooting quickly! Handy cit contains red, fiber optic front sights n seven different heights and both narow and medium base widths, plus two ights with red fiber optic rods for mountng directly on the barrel. Also included



are two rear dovetail sights and two sets of six inch long, fiber ptic rods for replacement and repair. Aluminum, rear sights with eye-grabbing, green, fiber optic dots really stand out in low ight. They fit 3/8" dovetails and feature screw adjustment for levation. Kit saves you approximately 50% over buying single eads. A perfect, money-saving kit for your shop.

SPECS: Front Sights: Blued steel body. Red fiber optic rods. Seven 7).250" (6.3mm) and (7) .340" (8.6mm) wide sights to fit narrow and , "nedium front sight bases (14 total). Heights: .260", .290", .312 343", .375", .406", and .450". Two (2).531" (13.5mm) sights to fit lirectly in a dovetail on the barrel. Heights: .538" and .570". Rear Gights: Aluminum, black matte. Green fiber optic rod. 2½" (6.35cm) ong. **Replacement Rods:** 6" (15.2cm) long. Two (2) 0.060" (1.4mm) liameter orange rods, two (2) 0.040" (1mm) diameter vellow rods. 962-000-064AK Williams Fire Sight Assortment Kit,

2F115B85..... \$ 134.99

FIRE SIGHT HOOD - Protects front blade from hose damaging accidental bumps. Open top alows plenty of light to reach the fiber optic rod. its Williams Streamlined Dovetail Ramps.



SPECS: Steel, blue. .630" (16mm) diameter. 1 (2.5cm) long.

#962-000-016AK Fire Sight Hood 2F08B21..... \$ 9.99

WGOS REPLACEMENT REAR SLIDE/BLADE - Fits all standard Williams adjustable, rear guide open sights. Aluminum blade contains two, green, fiber optic dots; use with existing factory front or choose a replacement Fire Sight Rifle Bead listed above. SPECS: 1/4" and 5/16" height only.

#962-602-180AK 1/4" Fire Sight WGOS Slide/Blade, 2F17D90. #962-602-190AK 1/6" Fire Sight WGOS Slide/Blade, 2F17D90......**20.99**

order on the web

WILLIAMS **BLADES & BASES FOR** "WGOS" & "WDOS" SIGHTS



U-Notch

Assemble Complete Sights Or Replace Blades To **Change Sight Picture**

Precision-made sight bases and blades milled from high-tensile strength, rustproof alloy. Dovetailed windage and elevation adjustments have hardened gib locks. Make adjustments quickly by loosening one screw. No dovetailing of barrel necessary. Bases

and blades sold separately. Blades can also replace the aperture on WGRS sights.

SPECS: Bases and blades: aluminum, black anodized finish. Bases - All models except the **One Inch** have .5625" c-to-c hole spacing. Small - .347" radius, fits .660" to .730" dia. barrels Medium - .395" radius, fits .730" to .830" dia. barrels. Large - .440" radius, fits .830" to .930" dia. barrels. X-Large - .5625" c-to-c hole spacing .475" radius, fits .900" to 1" dia. barrels. One Inch - 1" c-to-c hole spacing, .500" radius, fits 1" dia. barrels. 26mm - .550" radius, fits 1" to 1.1" dia. barrels. **Blades** available in 3/16" (4.8mm), 1/4" (6.3mm), 5/16" (7.9mm), and 3/8" (9.5mm) heights. Range of adjustment for each listed in table below.

WGOS/WDOS BASES

STOCK#	FOR SIGHT	FITS BARREL DIAMETER
#962-600-000AK	WGOS	Small, .660"730" dia.
#962-607-000AK	WGOS	Medium, .730"830" dia.
#962-608-000AK	WGOS	Large, .830" - 930" dia.
#962-611-000AK	WGOS	X-Large, .900" - 1" dia., .5625" c-to-c hole spacing
#962-609-000AK	WGOS	One Inch, 1" dia., 1" c-to-c hole spacing
#962-626-000AK	WGOS	26mm, 1" - 1.1" dia.
#962-400-000AK	WDOS	%" nominal dovetails
- Advise # -	WGOS	Base 2F15D87 \$ 18.99
#962-400-000A	K WDOS	Base 2F10D0111.99
BLAD	E HEIGHT	& RANGE OF ADJUSTMENT

BLADE	SLADE TOTAL SIGHT HEIGHT			
HEIGHT	On WGOS Base*	On WDOS Base		
3/16"	.369" (9.4mm)431" (10.9mm)	.281" (7.1mm)345" (8.8mm)		
1/4"	.431" (10.9mm)493" (12.5mm)	.345" (8.8mm)406" (10.3mm)		
5/16"	.493" (12.5mm)555" (14.0mm)	.406" (10.3mm)468" (11.9mm)		
3/8"	.555" (14.0mm)617" (15.7mm)	.468" (11.9mm)531" (13.5mm)		
#962-350	-118AK Square Notch Bla	ade. 3/16"		

#962-350-118AK	Square Notch Blade, 3/16",	
	2F06D21\$	7.99
#962-350-218AK	U-Notch Blade , 3/16" 2F06D21	7.99
#962-350-225AK	U-Notch Blade, ¼" 2F07D49	8.99
#962-350-231AK	U-Notch Blade, 5/16" 2F06D21	7.99
#962-350-237AK	U-Notch Blade , %" 2F06D21	7.99

WILLIAMS "WDOS" DOVETAIL OPEN SIGHT

Windage & Elevation Adjustments

Fits easily into standard 3/8" dovetail. Locking screw tightens against the dovetail. Windage and elevation adjustments. Three

#962-400-215AK WDOS Sight, 5/16" Blade,



2F17D49.....



MODEL

FP-AG-TK

FP-98-TK

FP-17-TK

FP-94/36-TK

FP-98-TK

FP-94/36-TK

FP-94/36-TK

FP-336-TK

FP-39-TK

FP-39-TKTM

FP-94/36-TK

FP-98-TK

FP-70-TK



FITS

BENJAMIN, 340,342,

347 (need higher front

d'tail receiver

BROWNING, B-92

DAISY, 99 & 299

d'tail receiver ITHACA M-37

JAP TYPE 38 & 99

KRAG, American

Norwegian

MARLIN, A-1

30-30

36

336

39A

39A3

56, 57, 62

99 Auto Load

.44 Mag & 44

MAUSER 98

MOSSBERG 800

REMINGTON

3000

11-48

31

700

RUGER

11 Nylon

48, 58, 11-48

510-11-12-13

700 Left Hand

721, 722, 725

4, 7400, 6, 7600

870. 1100. 11-87

10/22 & 44 Mag

80.81

ENFIELD 1917 & Br 14

AIRGUN

BRNO w/out

RI R

RPS

HIGGINS,

30/30 Lever **HUSQVARNA** w/out

BSA

FOOLPROOF RECEIVER SIGHTS - Internal micrometer adjustments lock positively to prevent accidental movement of sight setting. No obstructions to impair and blot out shooter's field of vision. Weighs only 1½ oz. Standard hole spacing to fit guns factory drilled and tapped for receiver sight. Foolproof features adjustment screws for windage and elevation.

FOOLPROOF-TK

STOCK #

#962-000-046AK

#962-000-041AK

NΔ

#962-000-077AK

NΑ

NA

NA

#962-000-039AK

#962-000-041AK

NΔ

NΑ

NA

#962-000-039AK

#962-000-039AK

#962-000-062AK

#962-000-036AK

#962-000-070AK

NΑ

NA

#962-000-039AK

NΔ

#962-000-039AK

#962-000-041AK

NA

NA

NA

NA

NA

NΔ

NA

NA

NA

#962-000-037AK

NΔ

FP-RU †† #962-000-050AK FP-RU-TK

#962-000-039AK FP-94/36-TK

#962-000-039AK FP-94/36-TK

Foolproof-TK comes equipped with target knobs

FOOLPROOF

STOCK #

NA

#962-200-098AK

#962-200-036AK

#962-200-072AK

NA

#962-200-071AK

NA

NA

#962-200-036AK

#962-200-098AK

NA

NA

NA

#962-200-036AK

#962-200-036AK

#962-200-002AK

#962-200-039AK

#962-000-069AK

NΔ #962-200-036AK FP-94/36 †

#962-200-036AK

#962-200-098AK

NA

NA

NA

NA

NA

NA

NΑ

#962-000-080AK

NA

#962-200-830AK

#962-200-825AK FP-Krag †

#962-200-825AK FP-Krag ††

#962-200-088AK FP-88/100 ††

#962-200-036AK FP-94/36 †

#962-200-088AK FP-88/100 ††

#962-200-071AK FP-70AP ††

#962-200-071AK FP-70AP ††

#962-200-071AK FP-70AP ††

#962-200-071AK FP-70AP ††

SPECS: Alum., black, anodized. Steel screws. See chart below.

- Advise # -	Foolproof Sight 2	2F53Y75	\$ 62.99
- Advise # -	Foolproof-TK Sig	ht 2F62B03	71.99

MODEL

FP-98 ††

FP-94/36

FP-71 ††

FP-11/87

FP-70AP †

FP-17 ††

FP-94/36 †

FP-98 ††

FP-94/36 †

FP-94/36 †

FP-336 †

FP-39 †

FP-39-TM

FP-94/36 †

FP-98 ††

FP-7400*

FP-11/87



5D

STOCK #

NA

#962-150-790AK

NA

NA

NA

NA

NA

#962-150-770AK

#962-150-770AK

#962-150-094AK

NA

#962-150-123AK

#962-150-770AK

NA

NΑ

#962-150-081AK

NΔ

#962-150-094AK

#962-150-001AK

#962-150-039AK

NA

NΑ

#962-150-081AK

#962-150-094AK

NΑ

NA

#962-150-094AK

#962-150-770AK

#962-150-070AK

#962-150-070AK

NΔ

#962-150-123AK

#962-150-510AK

#962-150-123AK

#962-150-123AK

#962-150-510AK

#962-150-070AK

#962-150-770AK

#962-150-070AK

NΑ

#962-150-123AK

NA

FOOLPROOF TARGET KNOBS - All Foolproof sights (except TK models) use the Short Elevation Knob. The Long Elevation Knob is for use with Foolproof-TK target sights. † indicates Short Windage Knob, †† indicates Long Windage knob. The Elevation Gib Lock Knob fits both standard Foolproof and Foolproof-TK models.

#962-157-520AK Target Windage Knob, Long,

MODEL

5D-SH

5D-JEMS

5D-JEMS

5D-94/36

5D-12/37

5D-JEMS

5D-81

5D-94/36

5D-336

5D-39A

5D-39A

5D-81

5D-94/36

5D-94/36

5D-JEMS

5D-70

5D-70

5D-12/37

5D-510

5D-12/37

5D-12/37

5D-510

5D-70

5D-JEMS

5D-70

5D-12/37

2F05Y83	9
#962-157-530AK Target Windage Knob, Shrt 2F05Y83. 6.9	
#962-157-240AK Target Elev. Knob, Long 2F06Y58 7.9	9
#962-157-250AK Target Elev. Knob, Short 2F06Y58 7.9	9
#962-000-079AK Elevation Gib Lock Knob 2F05B99 8.9	9



5D RECEIVER SIGHT - Same dependable, accurate construction as the Foolproof models but without micrometer adjustments. Windage and elevation adjustments are easily made by loosening screws, moving the sight, and re-tightening the screws. Excellent for hunting rifle applications that don't require regular tweaking of the sight adjustment set-

tings. Stop screw provides an accurate guide, so the 5D sightwill return to absolute zero upon detaching and reattaching to the gun. Standard hole spacing for easy, secure mounting.

SPECS: Aluminum, black, anodized. Steel screws. Advise Stock #

on chart below.		OFFICATION.	4
- Advise#—	5.D Sight	2#31V05	\$ 35.99

FITS	FOOLPROOF STOCK #	MODEL	FOOLPROOF-TK STOCK #	MODEL	5D STOCK #	MODEL
Ruger Continued	0100K#	MODEL	010010#	MODEL	010000	MODEL
Mod. 77, 77/22,	NA		#962-000-051AK	FP-RU-77-TK	NA	
No. 1	NA NA		#962-000-031AK	FP-RSS-TK	NA NA	
Mini-14 Ranch	NA NA	FP-11/87	#962-000-045AK	FP-11/87-TK	NA NA	
SAKO FINNWOLF	#962-200-088AK	FP-88/100 ††	NA	FF-11/0/-1K	NA NA	
SAVAGE(see Stevens)	#302-200-000AN	FF-00/ IUU	INA		INA	
99	#962-200-099AK	FP-99S †	NA		NA	
99DL-w/tang safe	#962-200-099AK	FP-99S †	NA NA		NA NA	
110	#302-200-039AR NA	11-330	#962-000-042AK	FP-110-TK	NA NA	
SEARS	INA		#902-000-042AK	FF-110-1K	IVA	
Centerfire Lever	#962-200-036AK	FP-94/36 †	#962-000-039AK	FP-94/36-TK	#962-150-094AK	5D-94/36
SHERIDAN, Model C	#302-200-030AK	FF-94/30 (#302-000-039AN NA	FF-94/30-1K	#962-150-790AK	5D-94/30 5D-SH
SHOTGUNS	INA		INA		#302-130-/3UAN	วบ-จก
	NA		NIA		#000 4E0 400 AV	FD 10/07
Pump/Flat Rec's SMITH & WESSON,	INA		NA		#962-150-123AK	5D-12/37
Rifle, Model 1500	#962-200-071AK	FP-70AP ††	NA		NA	
SPRINGFIELD	#302-200-07 IAIN	TT-/UAF	INA		IVA	
'03	#962-200-003AK	FP-A3 ††	NA		#962-150-770AK	5D-JEMS
'03/A3	#962-200-003AK	FP-A3 ††	NA NA		#302-130-770AK NA	OD-OFINIC
STEVENS	"205-500-0034K	11 70 11	11/1		INT	
22/410 & 20 ga.	NA				#962-150-224AK	5D-22/410
300 series	#962-200-340AK	FP-340 †	NA		#302-130-224AIX	30-22/410
620	#902-200-340AK NA	FF-340	INA		#962-150-123AK	5D-12/37
THOMPSON/CENTER	INA				#302-130-123AN	3D-12/37
Contender	#962-200-860AK	FP-T/C ††	NA		NA	
Hawken/Renegade	#962-200-800AK #962-200-815AK				NA NA	
WINCHESTER	#302-200-013AN	rr-nawken ii	INA		IVA	
9422	#962-200-810AK	ED CD ++	NA		#962-150-094AK	5D-94/36
		FP-GR ††			#302-130-034AK NA	DD-94/30
05, 07 & 10	#962-200-072AK	FP-71 ††	NA			ED 40/07
12, 1200, 1400	NA		NA		#962-150-123AK	5D-12/37
12-25	NA		NA		#962-150-123AK	5D-12/37
54	NA		#962-000-037AK	FP-70-TK	#962-150-070AK	5D-70
55 & 65	#962-200-036AK	FP-94/36 †	#962-000-039AK	FP-94/36-TK	NA	
64 & 94	#962-200-036AK	FP-94/36 †	#962-000-039AK	FP-94/36-TK	#962-150-094AK	5D-94/36
70 Old Style	NA		#962-000-037AK	FP-70-TK	#962-150-070AK	5D-70
70 New Style	#962-200-071AK	FP-70AP ††	NA		NA	
71, Win/Brwg 1895						
repro.	#962-200-072AK	FP-71 ††	NA		NA	
74	NA		NA		#962-150-070AK	5D-70
86, Win/Brwg 1895						
repro.	#962-200-072AK	FP-71 ††	NA		NA	
88	#962-200-088AK		NA	ED 0 4 10 0 To 1	NA	ED 04:22
94	#962-200-036AK	FP-94/36 †	#962-000-039AK	FP-94/36-TK	#962-150-094AK	5D-94/36
94 Angle Eject	#962-200-194AK	FP-94SE †	#962-000-040AK	FP-94SE-TK	#962-150-195AK	5D-94SE
Big Bore	#962-200-094AK	FP-94/375 †	NA		NA NA	
100 Auto	#962-200-088AK	FP-88/100 ††	NA		NA	
150 & 190	NA		NA		#962-150-123AK	5D-12/37
* * * *	#962-200-036AK	FP-94/36 †	#962-000-039AK	FP-94/36-TK	NA	
241						
250-255, 270-275,	87.5				H000 4E0 400 510	ED 40%=
	NA #962-200-071AK	FP-70AP ††	NA NA		#962-150-123AK #962-150-070AK	5D-12/37 5D-70

Ruger continued at top of next column

*Mounts in rear scope mount holes.

† Short windage knob.

†† Long windage knob

ROWNELLS ... PAGE 286

SATISFACTION GUARANTEED SINCE 1939

#962-000-077AK FP-11/87-TK

WILLIAMS

STREAMLINED DOVETAIL RAMP

Long & Graceful

Polished and Blued Steel. Sweat-on models have one attaching screw. Screw-on

models have two attaching screws, one under sight and one on ramp. Hole spacing on Remington models matches factory drilled and tapped barrels.

SPECS: Fractional height listed in table is the overall ramp height measured from top of barrel to top of ramp. Decimal height listed is measured from top of barrel to bottom of dovetail. Width of ramp is .250° (6.3mm). Supplied without hood.

SCREW-ON	SWEAT-ON	REMINGTON	
STOCK #	STOCK #	STOCK #	HEIGHT
#962-020-097AK	NA	NA	3/16" (.0975)
#962-020-219AK	#962-025-219AK	NA	5/16" (.2195)
#962-020-282AK	#962-025-282AK	#962-021-282AK	3 ₈ " (.282)
#962-020-344AK	NA	NA	7/16" (.3445)
#962-020-469AK	NA	NA	%16" (.4695)
- Advise # -	Streamlined F	Ramp 2F21B49.	\$ 23.99
#962-026-000AK	Streamlined R	lamp Hood,	
	2F05B87		6.99

WILLIAMS SHORTY DOVETAIL RAMP



Compact & Attractive For Smaller Guns

Polished, blued steel. Hoodless. Sweat-on, screw-on, or use optional Dovetail Filler

Block to attach to existing dovetail.

SPECS: Height shown in parenthesis in chart is from top of barrel to bottom of dovetail. Width of ramp is .250* (6.3mm). Made only in heights shown.

STOCK #	HEIGHT	STOCK #	HEIGHT
#962-010-032AK	1/8" (.032)	#962-010-188AK	9/32" (.188)
#962-010-094AK	³ ⁄ ₁₆ " (.0945)	#962-010-282AK	3/8" (.282)
		np 2F16B28 etail Block 2F03B4	
sight. SPECS: Aluminur 3/8" (9.5cm) H25	m, black, anod 60" wide fits W	eight, use lower front lized. 5%" (15.9mm) L x Villiams Shorty Ramp, man and older Marlir	-
ramps. #962-027-250AK	.250 Riser B	Block 2F06B35	\$ 7.99

WILLIAMS ONE-PIECE FIRE SIGHT RAMP

Replaces Fragile, Plastic Ramps With Sturdy, One-Piece Metal

No need to worry about breaking a sight ramp when you're busting through heavy brush. Solid, one-piece, CNC machined aluminum ramp attaches with one 6-48 screw and gives you a bright, glowing, sight picture. Fire red, fiber optic rod glows brightly using only available, natural light for high visibility.

SPECS: CNC machined aluminum, black. Fire red fiber optic rod. #70105 - height = .410°, fits barrel dia. of .625°, #70220 - height = .485°, fits barrel dia. of .875°; #70678 - height = .634°, fits barrel dia. of .650°. Gunsmith installation recommended.

#962-000-065AK	#70105 Fire Sight Ramp,
	2F13B77
#962-000-066AK	#70220 Fire Sight Ramp,
	2F13B77
#962-000-067AK	#70678 Fire Sight Ramp,
	2F13B77

WILLIAMS MUZZLELOADER FIRE SIGHT

Fast, Accurate Sighting For All Light Conditions





Contrasting red front and green rear, fiber op-

tic dots offer quick sight alignment; won't wash out in bright light, improve contrast in low light. Fully adjustable, "U"-notch, rear sight gives precise alignment for long range shots. Replaces factory sights with only minor fitting. Machined from aircraft aluminum for years of service.

SPECS: Aluminum body, black, matte finish. Bead - .058* (1.2mm) diameter, .89* (22.6mm) long. TC - Thompson Center. Octagon model fits newer guns with .836*, c-to-c hole spacing. Knight Fire Sight fits all models without Williams factory rear sight. Knight Mk-85 fits models with factory installed Williams rear sight. May require minor fitting. Remington sets are available with a standard notch rear sight or a .15* (3.8mm) diameter ghost ring rear sight. Models to fit 2003 & Earlier muzzleloaders with ½* dovetail front sight ramps or 2003 & Later muzzleloaders with 1-piece ramped front sights.

FRONT/REAR SIGHT SETS

STOCK#	FITS	PRICE
#962-622-550AK	CVA Octagon Barrel	2F27Z53 \$ 31.99
#962-000-054AK	CVA Round Barrel	2F27B53 \$ 31.99
#962-000-055AK	CVA Optima/Optima Pro	2F27B53 \$ 31.99
#962-622-560AK	TC Octagon Barrel	2F27Z53 \$ 31.99
#962-622-570AK	TC New Englander	2F27Z53 \$ 31.99
#962-622-580AK	Knight Fire Sight	2F34Z43 \$ 39.99
#962-000-005AK	Knight MK-85	2F26B29 \$ 30.99
#962-565-300AK	Rem 2003 & Earlier, Notch	2F21D39 \$ 24.99
#962-000-056AK	Rem 2003 & Later, Notch	2F21B39 \$ 24.99
#962-000-083AK	Rem 2003 & Earlier, G. Ring	2F22B01 \$ 25.99
#962-000-084AK	Rem 2003 & Later, Ghost Ring	2F22B01 \$ 25.99
#962-622-600AK	Traditional Lightning Fire, Buckhunter, Timberridge &	
	Cabela's	2F27Z53 \$ 31.99

AT BROWNELLS

We not only provide our customers the right tools to do the job - but also the information to do it well.

We pride ourselves on providing our customers with the best and most reliable information about our products before they make a purchase. We believe that informed customers will be satisfied customers.

Our crew of highly-skilled, veteran Gun Techs – all working gunsmiths recruited from across the United States – act as consultants to our marketing team, and trusted advisors to our customers. Together, their three centuries of combined experience help customers with more than 60,000 gun-related questions annually.

Call our Techs at 800-741-0015

- WILLIAMS

RIFLE FIRE SIGHT REAR SIGHT & SETS

Upgrade Your Factory Sights With Easy-To-See, Fiber Optics

All sets feature a bright red, fiber optic, front sight and fully adjustable peep or U-notch, rear sight. U-notch, rear sight sets use the highly accurate, 3-dot pattern with two green, fiber optic dots at the rear for sharp contrast and quick sight acquisition in all light conditions. No drilling or tapping required for most rifle models. Dovetailed front and rear sights may require minor fitting.

REMINGTON FIRE SIGHTS - Fiber optic, U-notch, rear sight

attaches to the factory, rear sight ramp to improve visibility; adjusts for windage and elevation. Contrasting, red, front sight really stands



out for fast pickup and alignment. 2003 & Earlier fits Remington rifles and muzzleloaders with dovetailed, front sight ramps, plus all Remington shotguns. 2003 & Later fits Remington rifles and muzzleloaders manufactured from 2003 to present with 1-piece, ramped front sights.

SPECS: Aluminum, black anodized.

#962-565-300AK 2003 & Earlier Rem. Fire Sights, 2F21D39 \$24.99 \$4962-000-056AK 2003 & Later Rem. Fire Sights, 2F21B39 \$24.99

REMINGTON GHOST RING FIRE SIGHTS - Bright, high contrast fiber optic sights with large aperture, rear ghost ring provide fast, accurate sight alignment in all light conditions. The more light, the brighter the beads glow. Front sight has a single red insert, rear ghost ring has two green inserts to form an easy-to-align, 3-dot sight picture. 2003 & Earlier fits Remington rifles and muzzleloaders with %" dovetail front sight ramps, plus all Remington shotguns with %" dovetail front sight ramps. 2003 & Later fits Remington rifles and muzzleloaders manufactured from 2003

to present with 1-piece, ramped front sights. Both sets include front and rear sights.

SPECS: Black, matte finish. Fiber optic insert. Bead - 've" (1.6mm) dia. Ghost Ring - .15" (3.8mm) dia. aperature. 2003 & Earlier - Steel front '3" dovetail sight. Aluminum rear sight. 2003 & Later - Aluminum front ramp sight and rear sight; includes steel 6-48 tpi front mounting screw.

#962-000-083AK 2003 & Earlier Ghost Ring Fire Sights, 2F22B01 \$25.99 #962-000-084AK 2003 & Later Ghost Ring Fire Sights, 2F22B01 25.99

RUGER® 10/22® FIRE SIGHTS - High visibility, fast to pickup, sight systems for the Ruger® 10/22®. WGRS features low profile, guide receiver, peep sight and red, fiber optic, front sight. 3-Dot has Unotch rear blade with green dots, red front sight. Adjustable for windage and elevation.

SPECS: Aluminum, black anodized. Front - .530" high, 1/16" red fiber optic bead. Fits Ruger 10/22 only.

BROWNING LEVER ACTION FIRE SIGHTS - Bright, easy-to-see, U-notch, rear sight improves

see, U-notch, rear sight improves sight acquisition during periods of low light. Excellent for hunting or target shooting. Green rear and contrasting red delivers a fast, accurate, 3-dot, aiming system.

ŠPECS: Aluminum, black anodized. Fits Browning BLR.

#962-000-020AK BLR Fire Sights 2F26B15...... \$ 30.99

MARLIN & WINCHESTER LEVER ACTION FIRE SIGHTS - For

Marlin and Winchester lever action rifles. **Dovetail** replaces factory front and rear sights. Rear sight is screw adjustable for elevation and drift adjustable for windage; has two, green, fiber optic dots. Front, has red, fiber optic rod. **FP** sight sets have a Foolproof, microadjustable, peep sight and red, front Fire Sight. Peep mounts



to existing holes in top or side of receiver, depending on model. WGRS-336 includes a compact, low profile, peep sight and red, front Fire Sight. Fully adjustable peep mounts to the rear scope mount holes for easy installation.

SPECS: Aluminum, black anodized. **Dovetail** fits all Winchester and Marlin lever actions with ramped front sights. **FP-94/36** fits Win. 94 top eject and models 55, 63, 64, and 65, Marlin 36, 336, 1894, 1895 and 444. Will not fit Win. 94/22. Requires two holes in the left side of the receiver and will require drilling and tapping on the newer guns. **FP-94SE** fits Will. 94 angle eject, except Big Bore models. **FP-336** fits Marlin 36, 336, 1894, 1895 and 444. Attaches to the top of the receiver and bolts up to factory drilled and tapped holes. **WGRS-336** fits Marlin 336, 444, 44 and 1895.

#962-602-170AK Dovetail Fire Sights 2F28D31	\$ 33.99
#962-633-310AK FP- 94/36 Fire Sights 2F59H99	69.99
#962-000-057AK FP- 94SE Fire Sights 2F59B99 .	68.99
#962-000-059AK FP- 336 Fire Sights 2F59B99	69.99
#962-000-058AK WGRS-336 Fire Sights 2F35B81	

MARLIN RIMFIRE FIRE SIGHTS - Dovetail sights replace the fac-

tory open sight sets on your Marlin rimfire. U-shaped, green, fiber optic, rear sight contrasts well with the red, front bead. Adjustable for windage and elevation. SPECS: Aluminum, black anodized. Model 60 also fits

915Y, 925, 925M, 981T, and 983T.

#962-000-061AK Marlin 25N/25NM Fire Sights,
2F20B67.....\$23.99

#962-000-092AK Marlin 60 Fire Sights,

slide/blade combo fits all standard size, Williams, adjustable, rear guide, open sight bases. Converts traditional, rear iron sights into Fire Sights. Aluminum blade contains a single, Ushaped, green, fiber optic rod for 2-dot accuracy. Use with existing factory front sight or

with fiber optic, Williams Riffe Sight Bead found elsewhere in catalog. Available in three heights.

SPECS: Aluminum, black anodized. 3/16" (4.8mm), ¼" (6.4mm), and 5/16" (7.9mm) high.

#962-000-081ÅK %s" WGOS Slide/Blade, 2F17B90 \$20.99 #962-602-180AK ¼" WGOS Slide/Blade 2F17D90 20.99 #962-602-190AK 5/16" WGOS Slide/Blade, 2F17D90 20.99

 $\underline{\textbf{WGOS REPLACEMENT SLIDE/GHOST RING}} \text{-} \operatorname{Rear slide/ghost}$

ring sight fits all standard size Williams adjustable rear guide open sight bases. Features a large light gathering ghost ring with two green, fiber optic dots for sharp contrast and quick sight acquisition in all light conditions. Ring aperature naturally centers to draw the eye to the front sight for faster

target acquisition and improved accuracy. Fully adjustable for windage and elevation. Rugged, low-profile aluminum sight has an anodized finish for resistance against scratches. Use with existing factory front sight or with fiber optic, Williams Rifle Sight Bead found elsewhere in catalog

Sight Bead found elsewhere in catalog. SPECS: Aluminum, black anodized. ¼* (6.4mm) high. Aperature - 5/32" (3.9mm) I.D.

order on the web



WILLIAMS "WGRS" RECEIVER SIGHT



- Easily Installed Compact • Rustproof • Low Profile
- Lightweight Positive Windage & **Elevation Adjustments**

In most cases, these sights utilize dovetail or existing screw holes on top of receiver to give guns the advantage of peep sights. SPECS: Aluminum, black, anodized. Peep height is approximately the same as a 3/16" (4.8mm) Open Sight Blade.

		-
STOCK #	MODEL #	FITS
#962-100-037AK	WGRS-37	Ithaca 37, Rem. 870/1100/11-87
		shotguns (drilling/tapping req'd)
#962-100-044AK	WGRS-44	Ruger® 44; use .500 to .560 front sight
#962-100-022AK	WGRS-RU-22	Ruger 10/22*; use .500 to .570 front
#962-100-054AK	WGRS-54	Sav-Ans 54, 64, 141, 141M, 153,
		552BDL, 572BDL; Win 310, 320.
		ost dovetailed receiver .22's
#962-100-070AK	WGRS-70	Post-war Win 70 (ex .375), 670, 770
#962-100-100AK	WGRS-100	Win 88-lever, 100-auto,
		Sako Finnwolf, use .450" front sight
#962-100-700AK	WGRS-700	Remington 700, 721, 722
#962-100-742AK	WGRS-742	Rem 742ADL, 760ADL;
		For BDL's use FP-740AP Foolproof
#962-100-740AK	WGRS-7400	Rem 4, 7400, 6, 7600
#962-000-019AK	WGRS-336	Marlin 336
#962-100-750AK	WGRS-BAR	Browning sporting Hi-Power auto rifle and lever
#962-100-760AK	WGRS-FN	Any FN Mauser (and others) w/ 1/2"
		hole spacing
#962-100-001AK	WGRS-M1-Carb.	Dovetail on .30 M1 Carbine
#962-100-158AK	WGRS-HR	H&R Topper/Handi-Rifles & Ruger Mk II pistols (drilling/tapping required)
#962-100-085AK	WGRS-KN	Knight MK-85 Modern Muzzleloader
#962-100-003AK	WGRS-DISC	Knight DISC, Browning T-Bolt
#962-100-086AK	WGRS-Legend	Modern Muzzleloading Legend & Wolverine, fits factory holes
#962-100-751AK	WGRS-CVA	CVA Apollo, Traditions, Deerhunter and others w/octagon bbl or receiver
#962-000-027AK	WGRS-CVA Rnd	CVA with round barrel, Win. X-140
#962-100-143AK	WGRS-Mini 14/30	Mini-14® Ranch Rifle & Mini Thirty®
#962-100-770AK	WGRS-M/L	Muzzleloader with octagon barrels
#962-100-775AK	WGRS-TC	T/C Contender
#962-000-015AK	WGRS-TC	T/C Encore
#962-100-002AK	WGRS-Black	
	Diamond	T/C Black Diamond
#962-000-068AK	WGRS-Savage	Savage 110 Accu-trigger (round receiver) (for use w/538M bead)

- Advise # - Guide Receiver Sight 2F30B29 \$ 35.99

RUGER FRONT/REAR SIGHT SET - A WGRS rear sight and .570" high gold bead front makes a fast system for Ruger carbines. SPECS: Aluminum, black anodized, Front - 1/16" gold bead, .570"

#962-445-650AK WGRS-RU-22 Set 2F35D85 \$ 41.99

 $\underline{\text{GHOST RING APERTURE}} \text{-} \text{Use with WGRS-37 for}$ a fast sight picture on combat and slug-shooting

SPECS: Aluminum, black anodized. .195" (4.9mm) diameter aperture.

#962-100-901AK Ghost Ring Aperture 2F03V95 \$ 5.95





XS SIGHT SYSTEMS RIFLE APERTURE REAR SIGHT **POST FRONT SIGHT**

Fast Sighting With Ghost-Ring Apertures

APERTURE REAR SIGHTS - Easy-to-install, fully machined, allsteel sights with windage and elevation-adjustable bases are pre-machined to fit quickly using the rear scope base holes on many popular rifles. A fast, accurate sight for brush hunting applications. Adjustments are secured with dual setscrews.

SPECS: Steel, blue, matte finish. . 191" (4.8mm) diameter aperture. Marlin Lever, Ruger® 10/22® and Rem. 700 fit factory, rear hole pattern. Win. 92 fits Model 92 and clones and Win. 94 Angle Eject. Win. 92 requires drilling and tapping of receiver. Win. 94 Top Eject requires drilling and tapping of bolt. Use with .350" (8.8mm) post front sight. Mauser requires drilling and tapping, use .350" (8.8mm) front sight. Ruger Mini Thirty®/Ranch replaces factory aperture.

STOCK #	FITS	PRICE
#006-103-300AK	Marlin 30AS, 336, 1894	6K45D00 \$ 60.00
#006-103-095AK	Marlin 1895 in 45-70, .444	6K45D00 \$ 60.00
#006-103-098AK	Mauser 98	6K45D00 \$ 60.00
#006-103-700AK	Rem. 700	6K45D00 \$ 60.00
#006-103-014AK	Ruger MiniThirty®/Ranch	6K45D00 \$ 60.00
#006-103-092AK	Win. 92/94 Angle Eject	6K45D00 \$ 60.00

REPLACEMENT APERTURES - Choose the opening size that matches your shooting conditions. .218" is threaded internally 7/32" x 40 tpi to accept Williams apertures.

SPECS: Steel, blue, matte finish. .150" has .70" thick rings; .218" has .050" thick rings.

STOCK #	SIZE	PRICE
#006-112-150AK	.150" (3.8mm)	6K09H00 \$ 12.00
#006-112-213AK	.218" (5.4mm)	6K09H00 \$ 12.00

POST FRONT SIGHTS - Modified post front sight with vertical white line insert is fast and easy to see in all light conditions. Variety of heights to fit a wide selection of rifles.

SPECS: Steel, blue, matte finish. Fits nominal 3/8" x .375" dovetail. .100" (2.54mm) wide post has .040" (1mm) wide stripe, heights listed in chart. Heights measured from top of blade to bottom of dovetail. Includes Test Post Sight.

.100" WIDE POST

STOCK #	HEIGHT	PRICE
#006-113-250AK	.250" (6.35mm)	6K22H50 \$ 30.00
#006-113-300AK	.300" (7.62mm)	6K22H50 \$ 30.00
#006-113-350AK	.350" (8.89mm)	6K22H50 \$ 30.00
#006-113-400AK	.400" (10.16mm)	6K22H50 \$ 30.00
#006-113-450AK	.450" (11.43mm)	6K22H50 \$ 30.00
#006-113-500AK	.500" (12.7mm)	6K22H50 \$ 30.00
#006-113-550AK	.550" (13.97mm)	6K22H50 \$ 30.00
#006-113-600AK	.600" (15.24mm)	6K22H50 \$ 30.00

XS SIGHT SYSTEMS COWBOY FRONT EXPRESS SIGHT

Faster To Find Than Factory Sights; **Legal For SASS Competition**

Get your Cowboy lever rife on target faster and enjoy higher overall scores. White dot expressstyle front sight works with either your factory rear or and aftermarket ladder-adjustable rear "V". Provides extremely fast pick-up in all light

conditions, so you can knock down those steel cowboy targets even faster. Includes instructions plus two nylon try-sights to help establish required front sight height before actual sight installation.

SPECS: All-steel, matte finish, black. .500" (12.3mm) high, .148" (3.7mm) thick blade, nominal 3/8" (9.mm) wide dovetail. Fits Winchester legacy lever action rifles and Marlin Cowboy rifle, all cali-

#006-000-155AK .500" Express Frt Sight 6K20V00 . \$ 30.00

XS SIGHT SYSTEMS LEVER ACTION **APERTURE REAR & FRONT SIGHT SETS**



Combines The Accuracy Of Aperture Sights With The Speed Of Open Sights Easy-to-see post front and ghost-

ring rear get you on target fast for brush hunting and action shooting. All steel construction, front/rear sets provide the correct front

sight for each model, eliminating the guess work of choosing sights. Easy-to-install, fully machined to fit existing rear scope base and front sight holes/dovetails. Windage and elevation adjustable with dual set screws. Modified post front sight with vertical white line insert provides excellent target contrast, is quick to pick up in all light conditions. Includes .191" and .230" I.D. apertures. 💳

SPECS: Rear - Steel, blue, matte finish. Win. 92 and Win. 94 Top Eject require drilling and tapping of receiver. Front - Steel, blue, matte finish. Fits .250" or .340" wide front bases or nominal 36" dovetail, as noted. Post - .100" (2.7mm) wide with .030" (.76mm)

STOCK#	FITS
#006-000-139AK	Marlin 336 w/ .340" wide front base
#006-000-140AK	Marlin 336 w/ %" dovetail barrel
#006-000-141AK	Marlin 1895SS, 444SS w/ 3/8" dovetail barrel
#006-000-142AK	Marlin 1895 w/ .340" wide front base
#006-000-143AK	Marlin 39A ,w/ .250" & .340" wide front base
#006-000-144AK	Win. 92, 94 Angle Eject Big Bore w/dovetail barrel
#006-000-145AK	Win. 94 w/ 20-24" dovetail barrel
#006-000-147AK	Win. 94 Trapper w/ dovetail barrel
#006-000-148AK	Win. 94 Big Bore & Timber Carbine w/ front base
Advise #	Anostrus & Doct Sight Set

 Advise # — Aperture & Post Sight Set. 6K67V50......\$81.00

MARLIN INTEGRAL POST AND BASE SET - One-piece front

base, plus a fully adjustable ghost ring rear sight for Marlin lever guns. Hunters and competitive shooters alike will benefit from the faster sighting offered by the .191" and .230" inside diameter rear apertures and

.100" wide, white line front sight blade. **Ghost Ring** sets include a rear ghost ring sight that mounts directly to the receiver without drilling and trapping. Lever Rail Ghost Ring sets include a rear ghost ring sight that mounts in the milled sight recess on the XS Sight Systems Lever Rail (available separately below). SPECS: Steel, black, matte finish. 1895 Ghost Ring Set - Fits Marlin 1895 with .700" and 1.00" c-to-c front ramp screws. .528" high front sight measured from top of barrel to top of blade. 336/1894/30AS Ghost Ring Set - Fits Marlin 336, 1894, and 30AS with .700" c-to-c front ramp hole spacing. Lever Rail Ghost Ring Sets - For XS Lever Rail applications only. Models available for Marlin 1895 and 336.

#006-000-033AK	1895 Ghost Ring Set,
	<i>6K67V50</i>
#006-000-024AK	336/1894/30AS Ghost Ring Set,
	6K67D5081.00
#006-000-162AK	1895 Lever Rail Ghost Ring Set,
	6K67B50
#006-000-164AK	336 Lever Rail Ghost Ring Set,
	<i>6K67B50</i>

DRC WINGED 1895 GHOST-RING SIGHT SET - Give your 1895 Guide Gun an extremely durable sight

that withstands the toughest hunting and field use. Sturdy steel wings protect the rear sight body from damage. Windage and elevation adjustable, ghost-ring rear

furnished with .191" and .230" diameter apertures. One-piece front post and base has highly visible, .100" wide, white line, front post.

SPECS: Steel, black, matte finish. 1895 - Fits Marlin 1895 with .700" and 1.00" c-to-c front ramp screws. .528" high front sight measured from top of barrel to top of blade.

#006-000-037AK DRC 1895 Marlin Sight,

XS SIGHT SYSTEMS AK-47 24/7TRITIUM STRIPE FRONT SIGHT

For Low-Light, Tactical Situations

Machined, steel, front post features a tritium vial for low-light target acquisition and an eyecatching white outline for use during daylight hours. Replaces factory windage drum and front sight post. Each full turn of front post moves point of impact approximately 4" at 100 yards. Includes installation instructions, tools, and locking adhesive. SPECS: Steel, matte black finish. Fits AK-47 rifles.

#006-000-150AK AK-47 24/7 Front Sight 6K52V50.. \$ 70.00



XS SIGHT SYSTEMS RIFLE BACKUP SIGHT

Excellent Insurance **Against Scope Failure**

Ghost-ring aperture is a fast, alternative, open sight that will save your hunt if your scope fails. Perfect for use on in-line muzzleloaders when hunting no-scope areas. Attaches in just seconds, without gunsmithing, to any Weaver-style base. Ruger model fits Ruger and Talley bases, requires drilling rear base. Fully adjustable for windage and elevation. Includes front Test Post. SPECS: Steel, blue, matte finish. . 191" (4.8mm) diameter aperture

Weaver - .275" (7mm), High Weaver - .500" (12.7mm) from top of base to center of aperture. Ruger - .300" (7.6mm) high from top of hase to top of sight hody

n boay.	
Weaver Backup Sight	6K48D75 \$ 65.00
High Weaver Backup	Sight,
6K48D75	65.00
Ruger Backup Sight	6K48D75 65.00
	Weaver Backup Sight High Weaver Backup 6K48D75 Ruger Backup Sight

MARLIN 1894/1895/336/308MX LEVER RAIL - Lightweight scope rail mounts to Marlin centerfire lever gun without drilling and trap-

ping. Accepts Weaver-style or Picatinny accessories, including the Marlin 1894, 1895 or Marlin 336/308MX Lever Rail Ghost Ring set (above). Extra-long rail gives plenty

of versatility in mounting scope directly over the receiver or forward over the barrel for intermediate eye relief optics or red dot sights. Requires removal of factory rear sight. Gunsmith installation recommended.

SPECS: Aluminum, black, matte finish. 11" (27cm) long, .830' (21mm) wide. 3 oz. (85g) weight. Includes mounting hardware.

#006-000-170AK Marlin 1894 Lever Rail 6K45B00 . \$ 54.00 #006-000-151AK Marlin 1895 Lever Rail 6K45V00 ... 54.00 #006-000-165AK Marlin 336/308MX Lever Rail. 6K45B00.....

MARLIN 1894/1895/336/308MX LEVER RAIL SIGHT SYSTEM

Convenient kit combines the lightweight Lever Rail onepiece scope rail with backup iron sights for mounting on your Marlin lever rifle without drilling and trapping. Rear ghost ring is fully ad-



justable for windage and elevation, with interchangeable .191" and .230" diameter apertures for fine-tuning accuracy. Onepiece front sight has .100" wide white-line post.

SPECS: Lever Rail - Aluminum, black, matte finish. 11" (27cm) long, .830" (21mm) wide. 3 oz. (85g) weight. Includes mounting hard-ware. Sights - Steel. matte black finish. Front sight: .100" wide. .528' high measured from top of barrel to top of blade. 1895 fits Marlin 1895 with .700" (17.8mm) and 1" (2.5cm) c-to-c front ramp screws. 336 fits round barrel Model 336 only.

#006-000-167AK Marlin 1894 Lever Rail Sight System, 6K107B14......\$ 135.00 #006-000-166AK Marlin 1895 Lever Rail Sight System, 6K108B05......135.99 #006-000-168AK Marlin 336 Lever Rail Sight System,

SATISFACTION GUARANTEED BROWNELLS PAGE 288 **SINCE 1939**

XS SIGHT SYSTEMS LONG-STEM GHOST RING APERTURE

Tall Rear Sight Posts For Increased Elevation

Gain increased elevation for those longer shots or cure insufficient sight elevation without machining or permanent alterations. These long stem apertures are simple and easy to install in any XS Rear Sight base equipped with their proprietary, ghost ring aperture.



SPECS: All-steel, matte finish, black. .649" (16.5mm) total height, .350" (8.8mm) threaded shaft length, .218" (5.5mm) diameter aperture, threaded 7/32-40 to accept Williams apertures.

#006-000-153AK .649" Threaded Ghost Ring Aperture,

XS SIGHT SYSTEMS AK-47 TRITIUM EXPRESS SIGHT SET



Big Dot Front Sight Puts You On Target Fast: Fully Adjustable Rear Sight For Improved Accuracy

High visibility sight combination easily replaces the factory

sights on your AK-47 or variant for fast sight acquisition in high stress or low light conditions. Machined steel set includes an adjustable white stripe, V-notch rear sight and a genuine Trijicon brand titrium lamp with large white ring for the front. Front sight completely replaces the factory windage drum and front sight post. Large, single setscrew in the tangent rear sight provides fine adjustments for elevation; dual setscrews in the dovetailed rear V-notch block securely lock-in your windage settings. Includes installation tools, thread locking agent, and detailed instructions.

SPECS: Steel, black, matte finish, Front Sight - ,160" (4,1mm) diameter white ring with .075" (1.9mm) diameter tritium lamp. Rear Sight - .140" (3.6mm) high vertical white stripe. Fits AK-47 and clones.

#006-000-161AK AK-47 Tritium Express Set,

XS SIGHT SYSTEMS SEMI-AUTO RIFLE TRITIUM SIGHT SETS for HK & SPRINGFIELD

Fast Target Acquisition In Full & Low Light

Steel sight sets feature tritium front sight for quick pickup in full light, half light, and low light. HK 91, 93, 94, and MP5 sight sets have either Big Dot or Standard Dot front sights and windage and elevation adjustable rear sights. HK USC/UMP, G36/ SL8 models come with Standard Dot tritium front sights, paired with same-plane rear Ghost Rings. M1A/M14 sight set has a 24/7 tritium strip front sight and a .125 aperture rear sight for fast acquisition. Available for M1A Scout Rifles with 18" barrels and M1A/M14 rifles with 22" barrels.

SPECS: Steel, matte black. Tritium insert on front sights. M1A Scout model fits rifles with 18" barrels. M1A/M14 model fits rifles with 22" harrel Gunsmith installation recor

WILLIAZZ Dallich. O	unsimili installation recommended.
#006-000-134AK	Big Dot Tritium, HK91, 93, 94, MP5,
	6K80V00
#006-000-135AK	Std Dot Tritium, HK USC/UMP, G36/SL8,
	6K80V00
#006-000-137AK	Std Dot Tritium, HK 91,83, 94, MP5,
	<i>6K80V00</i>
#006-000-138AK	24/7 Tritium, M1A Scout, Bush Rifle,
	6K86V67 130.00
#006-000-152AK	24/7 Tritium, M1A/M14 Rifle,
	<i>6K97V50</i>

· MARBLE

IMPROVED PEEPTANG SIGHT

Interchangeable Posts For Quick Change From Short-To Long-Range Configuration

Gives the single-shot or lever gun shooter the period looks of a traditional tangmounted peep sight, plus new adjustability features that allow fast changes from short- to long-range settings. Great for the cowboy shooter who wants to use the same gun in cowboy competition and long-range

side matches, or as an alternative to vernier-type sights on single-shot rifles used in BPCR and other long-range competitions. Each sight comes with a post that is the correct height to regulate the same as the original factory iron sights. Click adjustable for windage and elevation; each click is approximately 1/4" of adjustment at 100 yards. For larger elevation changes, you can easily swap in a higher or lower post (available below); choose a lower post for close-in shooting and a taller post for longer ranges. All components are precision CNC machined from 4140 steel, with critical parts heat-treated for extra strength. To purchase, find your gun in the left column, then find the correct sight kit and mounting screw set for it in the right column. Use with Marble's front sights, available separately.

SPECS: Steel, blued, Drilling and tapping may be required for installation on older guns. Sight kit includes base, Low (L) or Standard (S) height post, 1/2" O.D. aperture disc with .055" peep, and Allen

wrench.			
FITS	POST	STK # SIGHT	STK # SCREWS
American Arms 1874 Sharps	S	#579-000-166AK	#579-000-126AK
Armi 1874 Sharps	L	#579-000-167AK	#579-000-131AK
Ballard No. 8 Union Hill	L	#579-000-168AK	#579-000-124AK
Browning 1885 w/tang	L	#579-000-167AK	#579-000-100AK
Browning 1885, 78 w/o tang	L	#579-000-167AK	#579-000-125AK
Browning 1886	S	#579-000-174AK	#579-000-112AK
Browning 1892, 53, 65 (Japan mfr)	L	#579-000-167AK	#579-000-106AK
Browning 1892 w/tang safety	S	#579-000-178AK	#579-000-123AK
Browning 1895 (Japan mfr)	S	#579-000-176AK	#579-000-106AK
Browning 71LT	S	#579-000-174AK	#579-000-106AK
Cimarron 1866	S	#579-000-166AK	#579-000-109AK
Cimarron 1873	S	#579-000-166AK	#579-000-133AK
Colt Lightning (small frame)	S	#579-000-173AK	#579-000-128AK
EMF 1874 Sharps (not carbine)	L	#579-000-167AK	#579-000-131AK
H&R Buffalo Classic	L	#579-000-167AK	#579-000-125AK
Henry .22LR Lever			
(H001 & H001T, not H001V)	_L_	#579-000-167AK	#579-000-105AK
Henry Golden Boy .22LR (H004) & .22 Mag (H004M)	L	#579-000-173AK	#579-000-105AK
Henry Big Boy .30-30, .357/.38, .44 Mag. & .45 Colt	s	#579_000_166AK	#579-000-116AK
Marlin 1889, 1892, 1893, 1894, 25, 27		#373-000-100AK	#3/3-000-110AK
29, 39, 39A (old/original models)	L	#579-000-168AK	#579-000-124AK
Marlin 1894 & 1897 (current models)	L	#579-000-170AK	#579-000-114AK
Marlin 39A, 39AS, 39M, 39TDS			
(current models)	L	#579-000-170AK	#579-000-114AK
Marlin 336, incl. 444SS,			
1895G, 1895SS	S		#579-000-114AK
Marlin/Glenfield 30A, 30AS, 30GT	L		#579-000-114AK
Remington Model 1, 2, 5	S		#579-000-130AK
Rem. No. 1 Rolling Block (current mfr)			#579-000-100AK
Rossi 1892, 65	L		#579-000-101AK
Rossi 59, 62	L		#579-000-104AK
Savage 30G Stevens Favorite	L	#579-000-168AK	#579-000-124AK
Shiloh Sharps 1874 &			
New Model 1874	<u>L</u>		#579-000-129AK
Springfield 1870	<u> </u>		#579-000-125AK
Taurus M62	<u> </u>		#579-000-100AK
Taylor 1874 Sharps	L		#579-000-102AK
Thompson/Center Scout	L	#5/9-000-167AK	#579-000-100AK

SMITH ENTERPRISE FLIP-UP REAR SIGHT

Two Sight Pictures In One

Machined from bar stock with integral spring base. Flip it down, it's a fast pointing Buckhorn sight; flip it up, it's an elevator for long range shooting. Use on blackpowder cartridge rifles at

ranges from 500 to 800 yards with .45-70 and other straightwalled cartridges.

SPECS: Steel, blued, matte finish, Fits nominal 3/8" dovetails, 21/4

(5.7cm) long. Provides 1.75* (4.4cm) total sight elevation. **#851-000-026AK Flip-Up Rear Sight** 1E130C58... **\$ 169.99**

FITO		OT!! " O!O!!T	OTIV II CORFINIO	
FITS	POST			
Uberti 1873 (not incl. Hunter)	S	#579-000-166AK	#579-000-100AK	
Uberti 1885	L	#579-000-167AK	#579-000-132AK	
Uberti 1886	S	#579-000-166AK	#579-000-100AK	
Uberti 1892	L	#579-000-167AK	#579-000-100AK	
Uberti Henry	L	#579-000-167AK	#579-000-127AK	
Uberti Rolling Block	L	#579-000-179AK	#579-000-100AK	
Varner Favorite	S	#579-000-166AK	#579-000-107AK	
Winchester 1866	L	#579-000-167AK	#579-000-102AK	
Winchester 1873	L	#579-000-167AK	#579-000-119AK	
Winchester 1876 & 1886 (original)	S	#579-000-174AK	#579-000-117AK	
Winchester 1885 (original)	L	#579-000-167AK	#579-000-103AK	
Win. 1885 Low- &				
High-Wall (Japan mfr)	L	#579-000-167AK	#579-000-100AK	
Winchester 1890, 62, 64, 65	L	#579-000-167AK	#579-000-117AK	
Win. 1892 (original) &				
1894 (all, exc22 cal)	L	#579-000-167AK	#579-000-102AK	
Winchester 1892 (w/tang safety)	S	#579-000-178AK	#579-000-123AK	
Winchester 1895 (original)	S	#579-000-176AK	#579-000-116AK	
Winchester 1895 (w/tang safety)	S	#579-000-176AK	#579-000-113AK	
Winchester 1906	L	#579-000-167AK	#579-000-117AK	
Winchester 53, 55	L	#579-000-167AK	#579-000-102AK	
Winchester 9422 (.22LR)	L	#579-000-170AK	#579-000-120AK	

SIGHT POSTS - The Improved Tang Sight's quick-release post system makes it easy to replace the post that came with your sight with a higher or lower one for targeting at different ranges. Choose a lower post for close-in targets or a taller post for longer ranges. Post height is also click adjustable for fine-tuning when sighting in; each click represents 1/4" of adjustment at 100 yards. A jam nut locks the elevation, so you can remove and reinstall a post without losing settings.

SPECS: Steel, blued. Heights measured from base of post to center of aperture. Low - 1.085" to 1.415" height adjustment range. 1/2" aperture disc with .055" peep. Standard - 1.341" to 1.876 height adjustment range. Medium - 1.875" to 2.965" height adjustment range. 34" aperture disc with .032" peep. **High -** 2.820" to 4.770° height adjustment range, 34" aperture disc with .032" peep.

neight adjustinent range. 24 aperture disc with 1.032 peep.	
#579-000-096AK Low Sight Post 9G31V45 \$ 48.99	
#579-000-097AK Standard Sight Post 9G32V6450.99	
#579-000-098AK Medium Sight Post 9G49V99 63.99	
#579-000-099AK High Sight Post 9G39V06 47.99	

IMPROVED TANG SIGHT APERTURES - Refine and customize your sight picture by installing a different aperture. Available in six different peep sizes to help you tailor your sight to the range and type of target you'll be shooting. The farther the distance to the target, the smaller the peep hole should be. SPECS: Steel, blued.

STOCK #	DISC SIZE	HOLE SIZE
#579-009-780AK	½" O.D.	.055"
#579-009-785AK	¾" O.D.	.032"
#579-009-786AK	¾" O.D.	.043"
#579-009-787AK	3/4" O.D.	.055"

- Advise # - Tang Sight Aperture 9G39V06....\$ 47.99

PEDERSOLI COWBOYTARGET RIFLE SIGHTS

Superb Long-Range Accuracy & The Right Period Styling

In the days before compact scopes, target shooters and hunters seeking tack-driving accuracy relied on precisely adjustable vernier tang-mounted rear sights and globe front sights. Pedersoli offers BPCR silhouette shooters, competitors, and Cowboy Action shooters taking part in Schuetzen side matches replica sights that function just like the originals. Get your Winchester 1885, Rolling Block, Sharps, Ballard, Trapdoor Springfield, or other vintage single-shot rifle performing and looking its best.

"CREEDMOOR" REARTANG SIGHTS -

Named after the famous range on Long Island that hosted many longrange rifle competitions in the 1870s and '80s, the Creedmoor ladder-type sight is fully adjustable for windage and elevation and works equally well on cartridge rifles and muzzleloaders Sight is precision machined from steel and attaches to tang with supplied setscrews and folds down when not in use.



The Universal model is available in middle-range 2" and longrange 3" heights. The windage adjustment mechanism is on the eyepiece, allowing the eyepiece to dropped close to the base for close-in shots. The **Soule** model provides maximum adjustability to fit any hunting or target shooting conditions. Elevation is adjustable in precise increments of 1 MOA, and one full turn of the windage knob moves the point of aim left or right by 2½ MOA in ½ minute increments. Large knurled knob at the sight base allows fast, accurate return to center or previous setting. Choice of Short (SR), Middle (MR), and Long (LR) Range models. SPECS: Steel, blued. Elongated rear mounting hole allows installation on most rifles. Drilling and tapping of tang may be required. Distance between mounting holes 2.20"-2.29" (5.6-5.8cm). Mounting screws and installation instructions included.

#100-002-377AK	Univ. MR 2" Tang 4A130B29 \$	162.87
#100-002-376AK	Univ. LR 3" Tang 4A132B42	165.51
#100-002-378AK	"Soule" SR 2" Tang 4A193B39	241.74
#100-002-379AK	"Soule" MR 3" Tang 4A199B72	249.65
#100-002-380AK	"Soule" LR 4" Tang 4A216B54	270.67

SPIRIT LEVELTUNNEL FRONT SIGHT W/INSERTS - Windage-

adjustable, tunnel front sight comes with 12 interchangeable inserts so you can choose the sight 1000 picture that's best for the distance and range of



your target. The spirit level helps you hold the rifle completely upright to eliminate inaccuracies caused by tilting to the left or right. Perfect companion for the Creedmoor Rear Sights. Inserts available separately. Universal set includes 15 additional inserts for even broader choice of sight-picture options. Level Bubbles - Replacement bubbles in sets of 6, with two each of red, blue, and yellow-green.

SPECS: Steel, blued. Sight - 1 " (2.8cm) OAL, 113/32" (3.6cm) maximum width at adjustment knobs. Fits 3/8" (9.5mm), 60° dovetail

	Tunnel Sight w/Inserts	
#100-002-385AK	12-pc Sight Insert Set	4A12B65 14.99
#100-002-386AK	15-pc Univ. Insert Set	4A12B65 14.99
#100-002-384AK	6-pc Glass Bubble Set	4A25B24 29.99

VARIABLE APERTURE HADLEY-STYLE EYEPIECE - Rotating, detent-locking disc in the eyepiece lets you select one of eight aperture sizes to match your sight setting to current lighting conditions for optimum accuracy. Change settings with a flick of your thumb. SPECS: Steel, blued. 1.25" (3.1cm) diameter. Fits both

Universal and Soule-type Creedmoor sights. #100-002-381AK "Hadley"-Style Eyepiece 4A72B55 \$89.99

FOLDING FRONT SIGHT - Serves as globe sight for long-range shooting when raised, or fold down and use the built-in blade for close work. Ball/detent mechanism locks sight up or down. SPECS: Steel, blued, and natural-finish brass. Fits 3/8"

(9.5mm) 60° dovetail



#100-002-383AK Folding Front Sight 4A55B48 \$ 69.35

order on the web



SMITH ENTERPRISE **WESSON & HARRINGTON** LONG RANGE SIGHT



Extremely Versatile Buckhorn Sight; Sight, Base & Screws, All-In-One

Precision-machined, buckhorn, rear sight and base include screws that fit the holes in your Wesson & Harrington rifle for drop-on, no gunsmithing installation. Slider has a detent that lets you feel each adjustment; setscrew locks into place. Ladder has side markings so you can easily repeat the right

yardage settings. Drift adjustable for windage; setscrew locks your setting.

SPECS: Machined steel, blued finish. Sight - Ladder has approximately 127/64" (3.6cm) height adjustment; Buckhorn aperture 5/16" (8mm) I.D. Base - 1964" (7.5mm) high from bottom of receiver to top of base, 23/4" (7cm) long, 5/8" (15.9mm) wide.

#851-000-045AK Wesson & Harrington Sight,

1E140C85.....\$ 166.67

SMITH ENTERPRISE M-95 LONG RANGE SIGHT



Authentic Cowboy Action Look; Great For Long Distance Shooting

Versatile, CNC-machined, steel sight lets you shoot both long and short distances. Flipped up, the ladder adjusts from 100-1100 yards; flipped down, the flat top, V sight provides fast target acquisition for short shots. Ball detents provide an audible and felt click for each graduation on the ladder. Fits rifles with

a 3/4" dovetail.

SPECS: Steel, black oxide finish. 21/8" (5.4cm) long. Ladder provides 1²³/₆₄" (3.4cm) height adjustment. Fits rifles with a ³/₈" (9.5mm)

#851-000-046AK M-95 Long Range Sight,

1E131C94...... \$ 169.99

TOLL FREE: 800-741-0015

- MARBLE TANG SIGHT -

Period Looks, Superb Accuracy

Adds a touch of authenticity to pump and lever action rifles, whether they're used for hunting or Cowboy Action Shooting. Provides better sight definition and faster target acquisition in the field or on the range. Locates the aperture closer to the eye for a clear sight picture; longer sight radius increases accuracy. All steel construction with micrometer adjustments for windage and elevation. Folds to the rear for storage. Mounting screw set must be purchased separately.

SPECS: Steel, blued. Older guns may require drilling and tapping. Includes (2) ½" diameter apertures: .055" (1.4mm) and .102" (2.6mm) size holes, and (1) %" diameter aperture with .032" (.81mm) hole. Savage 99 will not fit late rifles with top safety. Late rifles with safety at trigger will require drilling and tapping. Mounting screw sets sold separately.

TANG SIGHT & REPLACEMENT SCREWS

STOCK#	FITS	MOUNTING SCREW SET
#579-009-824AK	Browning 53, 65, 1892 (Japan)	#579-000-106AK
#579-009-800AK	Browning 1885 (with metal tang)	#579-000-132AK
#579-009-804AK	Glenfield 30, Marlin 39, 1892, 1894 (Cowboy), 1897, 1897 Annie Oakley	#579-000-114AK
#579-000-150AK	Henry Lever Action .22S/L/LR & .22 Mag.	#579-000-105AK
#579-009-833AK	Henry Golden Boy .22LR	#579-000-100AK
#579-000-084AK	Henry Big Boy .44	#579-000-102AK
#579-009-829AK	Marlin 1893 & 1894 (original models made prior to 1932 only)	#579-000-124AK
#579-009-805AK	Marlin 336/1895, 444S	#579-000-114AK
#579-009-827AK	Marlin 25, 27, 29, 39A, 1892, 1897 (original) Ballard #8 Union Hill, Savage 30G, Stevens Favorite	#579-000-124AK
#579-009-819AK	Remington Model 1, 2, 5	#579-000-100AK
#579-009-807AK	Rossi 65, 1892	#579-000-101AK
#579-000-015AK	Savage 99 (see price below)	#579-000-124AK
#579-009-811AK	Uberti and Cimarron 1866	#579-000-105AK
#579-000-003AK	Uberti and Cimarron 1873	#579-000-105AK
#579-000-149AK	Uberti 1885	#579-000-132AK
#579-009-808AK	Win. 53, 55, 64, 1892 (original), 1894 (except .22)	#579-000-102AK
#579-009-803AK	Win. 62, 1890, 1906	#579-000-117AK
#579-000-001AK	Win. 1885 Low Wall (Japan)	#579-000-100AK
#579-009-800AK	Win. 1885 Hi-Wall (Japan), TC Scout	#579-000-100AK
#579-009-801AK	Win. 1876, 1886 Original	#579-000-118AK
#579-009-806AK	Win. 1886 (Japan), Browning 1886	#579-000-112AK
#579-000-085AK	Win. 94 (tang safety), 94 Legacy, 94 Trails End™	#579-000-108AK
— Advise # — M #579-000-015AK S — Advise # — M	Marble Tang Sight 9G97P98 lavage 99 Tang Sight 9G109T57 Mounting Screw Set For Marble Tang Sight 9G04V46	

TANG SIGHT APERTURES - Fine-tune your Marble tang sight for specific shooting situations by installing the perfect-sized aperture. Available in three hole sizes make it easy to obtain the best accuracy and target acquisition for long and short range, hunting or target shooting applications.

SPECS: Steel, blued finish. 3/4" (1.9cm) diameter aperture disc available with .032" (.813mm), .043" (1.1mm), or .055" (1.4mm) hole size.

10-52 till ead lits Marble's lang Signts.	
#579-009-785AK Marble Tang Sight Aperture, .032'	9G06P59\$ 9.99
#579-009-786AK Marble Tang Sight Aperture, .043'	' 9G06P59
#579-009-787AK Marble Tang Sight Aperture, .055	' 9G06P59



BRADLEY™ SIGHT BEAD

The Original "Bead-On-A-Block"

Standard Bradley - Places the front sight bead on a block of steel for positive indexing, greater surface area and increased

strength. Available in red and white colored plastic or gold brass beads. Solid Brass Bradley - Uniform yellow brass (gold) or white brass (silver) beads with positive-stop skirts.

SPECS: Standard Base - steel, blue. Bead - plastic, red, or white. Brass Beads - gold or silver. Metric beads are all white color.

STANDARD BRADLEY BEADS

		BEAD		SHANK	
STOCK # EA.	STOCK # 3-PAK	SIZE	TPI	LENGTH	COLOR
#146-184-011AK	#146-184-031AK	1/8"	3-56	5/32"	Red
#146-184-012AK	#146-184-032AK	1/8"	3-56	5/32"	White
#146-184-013AK	NA	1/8"	3-56	5/32"	Gold
#146-186-011AK	#146-186-031AK	1/8"	6-48	5/64"	Red
#146-186-012AK	#146-186-032AK	1/8"	6-48	5/64"	White
#146-186-013AK	NA	1/8"	6-48	5/64"	Gold
#146-187-012AK	#146-187-032AK	1/8"	6-48	9/64"	White
#146-532-412AK	#146-532-432AK	5/32"	3-56	5/32	White
#146-532-712AK	#146-532-732AK	5/32"	6-48	7/64	White
#146-532-812AK	#146-532-832AK	5/32"	6-48	9/64"	White
#146-532-912AK	#146-532-932AK	5/32"	8-40	1/8"	White
- Advise # -	Std. Bradley B	ead, ead	ch 6D1	2A00	\$ 6.99
Advise # -	Std. Bradley B	ead, 3-p	ak 6D	06A95	. 20.99

METRIC BRADLEY BEAD

STOCK # EA.	STOCK # 3-PAK	BEAD SIZE	TPI	
#146-000-001AK	#146-000-005AK	1/8"	2.5mm	
#146-000-002AK	#146-000-006AK	1/8"	3mm	
NA	#146-000-007AK	5/32"	2.5mm	
#146-000-004AK	#146-000-008AK	5/32"	3mm	
- Advise # - Metric Bradley Bead, each 6D22C89 \$ 8.99				
- Advise # - Metri	c Bradley Bead, 3-	pak 6D00YT	P . 22.99	

BRASS SKIRTED BEADS

	BEAD			
STOCK # EA.	STOCK # 3-PAK	SIZE	TPI	COLOR
#146-003-013AK	#146-003-033AK	1/8"	6-48	Gold
NA	#146-005-033AK	1/8"	5-40	Gold
#146-010-113AK	#146-010-133AK	1/16"	3-56	Gold
#146-020-114AK	#146-020-134AK	1/16	3-56	Bright Silver
NA	#146-030-135AK	1/16	3-56	Dull Sliver
- Advise # -	Brass Skirt Bead,	each	6D02A9	5 \$ 2.99

- Advise # - Brass Skirt Beads, 3-pak 6D06A12..... 8.99

LYMAN NO. 2TANG SIGHT

The Original No. 2; Now Back In Production

The original folding tang sight that increases sight radius for greater potential accuracy with your favorite lever action rifle. Sight features rugged, all-steel construction, knurled locking screw, index marks on aperture post,

.093" quick sight and .040" large disc apertures. Includes rear stock screw and front tang screw.

SPECS: Steel, blue. M-94, c-to-c 2.200", fits Winchester Model 94. M-36, c-to-c .845", fits Marlin Models 336, 30 and 1895. Win. 1886, fits original Winchester and Browning copies without tang safety. Some rifles may require drilling and tapping. Can be adapted to other rifles with tands.

#539-050-002AK Win. 94 No. 2 Tang 9C77H10 \$	93.99
#539-050-036AK Marlin 36 No. 2 Tang 9C77H10	93.99
#539-050-086AK Win. 1886 No. 2 Tang 9C77H10	93.99

BROWNELLS SHOTGUN SIGHT CONVENIENCE KIT



Everything you need to achieve a Profes-

sional shotgun sight repair or installation. Each kit includes the right drill bit and bottoming tap, plus sight(s) to help you clean up existing threads or install a sight with a larger, stronger shank. The Brownells 6-48 Kit features two, #4 brass front beads. Each Bradley kit has an Ivory, Bradleytype front sight.

ŠPECS: Bradley	sights have 3/32" (2.38mm) long shanks.	
#078-021-048AK	6-48 Brownells Kit 8G06A78 \$ 10.	.99
#078-021-256AK	3-56 Bradley Sight Kit 8G08A62 11.	.99
#078-021-248AK	6-48 Bradley Sight Kit 8G07A14 10.	.99

CARLSON'S HIGH VISIBILITY SHOTGUN BEAD

Easy-To-See White Or Fluorescent Red

Provides an easy-to-pick-up front bead in all types of hunting conditions. On dark or cloudy days the white bead is fast and

easy to see. On bright, sunny days the fluorescent red bead re mains visible in even the brightest light.

SPECS: Plastic bead, steel base, blued. 3-56 or 6-48 thread. #155-400-003AK 3-56 White High Vis. Bead.

	5E04Y70
— 6 or More —	3-56 White High Vis. Bead,
	5E03Y76
#155-400-004AK	3-56 Red High Vis. Bead,
	5E04Y70
 6 or More – 	3-56 Red High Vis. Bead,
	<i>5E03Y76</i> 5.50
#155-400-001AK	6-48 White High Vis. Bead,
	5E04Y78
 6 or More – 	6-48 White High Vis. Bead,
	<i>5E03Y76</i> 4.9 9
	6-48 Red High Vis. Bead 5E04Y70 5.99
 6 or More – 	6-48 Red High Vis. Bead 5E03Y76 5.50
_	

IVORYSIGHTS SHOTGUN CUSTOM IVORY BEAD SIGHTS

Beautifully Grained Ivory Adds A Touch Of Class To Your Favorite Shotgun

Meticulously handmade, one at a time, under the discriminating eye of a master craftsman. Polished, brass shank is delicately turned on a jeweler's lathe, so even the fine cut threads are an accomplished work of art. Beautiful, dome-style front bead or midbead is brought to life through the slow, careful shaping of pre-ban, elephant ivory. Final polishing to a high luster finish seals, protects and brings out the gorgeous, carousel pattern only genuine, elephant ivory can produce. At last, each part is brought together, bonded with high-strength, dental epoxy and inspected for uniformity and fit. Truly classic sight beads for the shotguns you really cherish.

SPECS: Shank - Brass, polished finish. 1/8" (3.2mm) long. Bead Genuine, elephant ivory. Front Bead - Approx. 5/32" (4mm) diameter. Midbead - Approximately 1/8" diameter. 3-56 or 6-48 thread.

#100-002-028AK	3-56 Custom	Ivory Front Bead,	
	7A25Y00		34.95
#100-002-149AK	3-56 Custom	Ivory Midbead	
			34.95
#100-002-029AK	6-48 Custom	Ivory Front Bead,	
	7A27Y96		. 34.95
#100-002-150AK	6-48 Custom	Ivory Midbead,	
	7127T06		34 05



Stock numbers shown in red indicate the product is made in the U.S.A. This information is not available for all products at time of catalog production, but will be regularly updated on our website.

BROWNELLS PAGE 290

SATISFACTION GUARANTEED SINCE 1939

—HIVIZ SHOTGUN FIBER OPTIC SIGHT

Improves Target Visualization

Light gathering, polymer rod works in low light as well as bright to provide an easy-to-see, fast-pointing dot. Four colored rods let you change sights to fit shooting conditions. Locating fingers on each end center the sight on your rib; two strong magnets prevent movement.

SPECS: Base - Plastic, black. Rods - Polymer, red, green, yellow, orange. .170" (4.3mm) diameter sighting dot. M-300 - fits ribs 7/32 (5.5mm) to \$\frac{5}{16}\$" (8.2mm) wide. **M-400 -** Fits ribs \$\frac{5}{16}\$" (8.2mm) to \$\frac{7}{16}\$" (11.3mm) wide. **M-500 -** Fits ribs 7/16" to 9/16" (11.3mm-14.5mm) wide.

MPB - Fits all 16, 2	20 and 12 gauge,	non-ribbed barrels.
----------------------	------------------	---------------------

#638-300-000AK	M-300 Fiber Optic Sight,
	8C17B88
#638-400-000AK	M-400 Fiber Optic Sight,
	8C17B88
#638-500-000AK	M-500 Fiber Optic Sight,
	8C17B88
#638-100-000AK	MPB Fiber Optic Sight,
	8C17B88


COMP SIGHT - Light gathering, polymer rod provides an easy-to-see dot in low light and bright daylight. Steel base replaces front bead, screws on for a secure mount. Includes eight interchangeable light pipes, three orange, three green and two white

in three diameters: .105", .115" and .130" for competition, law enforcement and field use. Four sight mounting screws are supplied to fit nearly all shotgun ribs, plus a rotary carrying case for storing light pipes and spring release key.

SPECS: Steel base, matte black. 1" (2.5cm) long. Screw/fits: 3-56" for Ruger, Beretta/Benelli, Browning Target Citori, Krieghoff; M3X.5" for Browning Gold and Citori Field; 5-40" for Mossberg; 6-48" for Remington (with threaded bead) and SKB sporting models.

#638-000-001AK Comp Sight 8C28V71.....\$ 39.99

TOM BUSTER II SIGHT SET - Fits shotguns with vent ribs between 11/64" and 7/16" wide and a removable front sight. Rear has two green dots and adjusts for windage and elevation. Front has one green and one orange, interchangeable rod. Sights fit a variety of shotguns and kit



#638-000-038AK	10m Buster II Signt Set,	
	8C22V87	36.20

TRIVIZTURKEY SIGHT - Three, green, triangular elements provide a precise, sight picture with fast sight alignment. Rear sight is fully adjustable for windage. Also includes a round, front pipe. Remove the rear sight use just the front sight for bird hunting, and clay target shooting. Mounts to any shotgun with a vent rib; no drilling or tapping.

SPECS: Rear sight - Injection-molded, optical-grade, resin, black. 1" (2.5cm) high, $1\frac{1}{4}$ " (3.2cm) wide. Front sight - $2\frac{1}{2}$ " (6.4cm) long. Includes 4, green, LitePipes (3 triangular in varied heights and one round). Fits all vent ribbed shotguns with replaceable front beads.

#638-000-009AK Turkey Sight 8C22V87..... \$ 36.20

FLAME SIGHT - Replaces the front bead with a highly visible fiber optic rod on all shotguns with a ventilated rib. Screws are included to fit all front bead thread sizes. An easy way to upgrade to a bright front sight for hunting, target shooting, or tactical use.

SPECS: Base – steel black oxide finish. Approximately 7/8" (2.2cm) long. Fluorescent LitePipe available in green or red. Replaces front sight head on all yent ribbed shotguns

	Flame Sight, Green,
	8C10V00 \$ 16.65
#638-000-041AK	Flame Sight, Red 8C10V00 16.65

FLASHPOINT & TRICOMP SIGHTS -

Each versatile unit includes triangular and round, full-dot sighting tubes you can snap in and out, depending upon

your situation. Mount to virtually any ventilated-rib shotgun. TriComp unit has a steel base and includes 9, 11/4" tubes. Flashpoint unit has a steel base and includes 8, 2" tubes, varying in color, size and shape.

SPECS: TriComp: Base - Steel, black-oxide finish. Approximately 13/4" (45mm) long, Includes (9) tubes, (3) round, .090" (2,3mm) O.D. (3) round, .125" (3.2mm) O.D.; red, green, white. (3) triangular, .140 (3.6mm) high; red, green, white. Flashpoint: Base - Steel, blackoxide finish. Approximately 21/2" (64mm) Iona, Includes (8) tubes. (2) round, .1" (2.5mm) O.D.; red, green. (2) triangular, .14" (3.6mm) high; (2) triangular, .18" (4.6mm) high; (2) triangular, .20" (5mm) high;

rea, green.	
#638-000-032AK	FlashPoint Sights,
	8C17V26
#638-000-033AK	TriComp Sights,
	8C25V26 39.95

SPARK II SIGHT - Highly visible, fiber optic front sight features a unique, interchangeable mounting post system for easy installation on most major brands of shotguns with plain or ribbed barrels. Pre-tapped, steel sight

base accepts five, included mounting posts to accommodate shotguns drilled and tapped for 6-48, 5-40 or 3-56, plus the popular 3mm x .5 or 3mm x .6 metric sizes. Bright, red, fiber optic LitePipe provides superior light transmission from dawn 'til dusk, perfect for low light hunting conditions, as well as competition and self defense guns where fast sight acquisition is paramount. Requires drilling and tapping on shotguns with factory, press-fit

SPECS: Sight Base - Steel, blue finish. .204" (5.2mm) long x .137" (3.5mm) wide. Bead - Polymer, red. .362" (9.2mm) long x .106" (2.7mm) diameter. Sight Height - .167" (4.2mm) high from top of barrel to top of bead. 6-48 fits Remington, Weatherby, SKB and Ithaca. 3-56 fits Browning Citori target guns, Benelli, Beretta, Ruger, and Winchester. **5-40** fits Mossberg. **3mm x** .**5** fits Browning Gold and Citori field guns. 3mm x .6 fits Browning Citori Hunter. #638-000-016AK Spark II Sight,

8C06V67.....

FOUR IN ONE I & II SIGHT - High contrast, light gathering front and rear sights can be used with the front only for wing shooting or in combination with the rear for a precision rifle-type sight. Removable rear is windage and elevation adjustable to increase your accuracy when hunting deer or tur-



key. Front sights include one red and one green rod that easily interchange to maintain sight visibility in low or bright light. Two-dot rear sight includes one red, green, white, and black rod for a variety of color combinations. Wing shooting front sight is held securely to ventilated rib with included screws, and will not shake loose under recoil. Rear sight clamps firmly around ventilated rib with machine screws and is used in combination with an additional front sight that secures over the wing sight with included pin, both are easily removed. Rods remove and install easily using light finger pressure and the included plastic pick. Includes pocket sized, plastic case for convenient storage. Requires removal of existing front sight and drilling and tapping. SPECS: Base - Plastic, matte black finish. Case - Clear plastic. Front Wing Base - 2¾" (7cm) long x ¼" (6.3mm) wide. Front Rifle Base - 21/4" (5.7cm) long x 5/16" (7.6mm) wide. Rear base 23/4" (7cm) x ¾" (1.9mm) wide. Front Rod - Polymer, (1) red, (1) green, 13/8" (3.4cm) long x .1" (2.5mm) dia. Rear Rod - Polymer, (1) red, (1) green, (1) white, (1) black, .05" (1.3mm) dia. Four In One-I Fits Beretta and Browning Gold ribs ¼" (6.3mm) wide, and Remington ribs %2"(7.5mm) wide. Four In One-II Fits BPS and Benelli ribs 5/16" (7.9mm) wide, and Mossberg or Winchester ribs 3/8" (9.7mm)

#638-000-077AK	Four In One I.
	8C28V69
#638-000-078AK	Four In One II,
	8C29V99 39.99

HIVIZ BENELLI SHOTGUN

For Faster Targeting In Low-Light Conditions;

Interchangeable Red & Green Rods

Fiber optic sight maintains excel-

lent sight/target contrast in a broad

range of lighting conditions and lets

from red to green. Easily replaces the

front post on Benelli M1, M2, M3, M4,

Nova Tactical and Super Nova Tacti-

rod quickly. Elevation adjustable.

shotguns with ghost ring rear sight.

tunnel sight with highly visible red or

green rod provides exceptional sight

contrast in all light conditions. Front

sight dot is only visible when using

correct head alignment, forcing proper

shooting form and increasing accuracy.

Red or green fiber optic rods are easily

interchanged allowing you to change

you quickly change the fiber optic rod 🧨

FIBER OPTIC FRONT SIGHT

cal shotguns with ghost ring rear sight. Unique, U-shaped rod

gathers far more light than a standard straight rod—perfect for

low-light situations. Comes with two green and two red inter-

changeable rods that can be changed quickly using the included

tool, so you can customize the sight picture or replace a damaged

SPECS: Steel, matte black, with 2 green and 2 red fiber optic rods.

Includes rod removal tool, carrying case, and instructions. Fits

Benelli M1, M2, M3, M4, Nova Tactical, and Super Nova Tactical

MAGNI-COMP/MAGNI-HUNTER I & II SIGHTS - Innovative

sight color when light conditions change. Designed to fit venti-

lated ribs with removable front beads. Magni-Comp contains a

compact, stainless steel base that is secured firmly to the venti-

lated rib using included screw, making it ideal for heavy recoil

loads or ported barrels. Sight base uses a locking spring to keep

the light rod secure, yet allows easy interchangability of the red

or green rod in the field with provided key. Includes five different

size sight screws for a variety of ribs. Magni-Hunter I/II features

a polymer base that snaps onto the rib and is held firmly in

place with a high-strength magnet for quick installation without

screws. Includes two red and two green light rods that easily

interchange using thumb and finger pressure. Magni-Hunter

models include two bases with different internal mounting di-

mensions allowing improved fit on a wide range of rib widths.

Includes pocket sized, plastic case for convenient storage. Mag-

ni-Hunter I fits ribs .230" to .330" wide. Magni-Hunter II fits

SPECS: Magni-Comp - Base - 1704 stainless steel, matte black

finish, 11/4" (3.1cm) long. Rods - polymer, (1) red, (1) green, 11/16

(17.8mm) long x .07" (1.8mm) dia. Includes five screw sizes: 3-56"

fits Winchester, Beretta, Benelli, and Ruger shotguns; M3 x .5" fits

Browning BPS, Gold and Citori Field guns; M3 x .6" fits Browning

Citori Hunter; 5-40" fits Mossberg shotguns; 6-48" fits Ithaca, Rem-

ington, and SKB field models. Magni-Hunter I & II - Base/Tunnel -

Polymer, matte black. Carrying Case - Clear plastic. Rods - Polymer,

(2) red, (2) green, 1¹⁵/₁₆" (4.9cm) long x .07" dia. **Magni-Hunter**

I - 25/8" (6.6cm) long x 7/16" (1.1cm) wide. Fits ribs .230" (5.8mm) -

.330" (8.3mm) wide, including Beretta 686/687 with ultra narrow

ribs, AL390, AL391 Urika, A391 Xtrema; Browning Gold, BPS, Citori

28 ga/.410; Benelli SBE, M1 Field, Nova, and all field models of

Remington, Franchi, Charles Daly, Verona, and Ruger Red Label.

Magni-Hunter II - 25%" (6.6cm) long x 9/16" (1.5cm) wide. Fits ribs

.355" (9mm) - .440" (11.1mm) wide, including all Mossberg; Rem-

ington SP10: Winchester 1200/1300/1400 and Super X2: Browning

Citori Target Models (except extra wide rib models); Beretta S682

#638-000-072AK Magni-Comp 8C27V29..... \$ 43.20

#638-000-076AK Magni-Hunter II 8C22V08 35.65

For more choices of HIVIZ SIGHTS visit brownells.com

8C26B47.....\$29.99

#638-000-191AK Benelli Shotgun FO Front Sight,

FRONT No. 10D (6-48 thread)

LYMAN SHOTGUN SIGHT



(Use #47 Drill)

#539-101-010AK No. 10 Front Sight, each 9C05H73 \$ 6.95
#539-111-028AK No. 11 Rear Sight, each 9C05H73 6.95
#539-101-012AK No. 10D Front, Screw-in, w/wrench,
9C05H73

IVORY FRONT

(Use # 29 Drill)

No. 10

MARBLE TRITIUM SHOTGUN SIGHT

Gets You On Target Quickly In Low & Regular Light

CNC-machined, steel sight uses eye-catching tritium to provide a fast sight picture in low light and an easily-noticeable, white ring for regular light. White ring is recessed to protect it from being scratched and to ensure proper light reflection from any angle. Five different thread diameters fit most shotguns. SPECS: Steel, blued, matte finish. Approximately .32" (8.1mm) long, 3/16" (4.8mm) wide, .21" (5.4mm) high. 3/32" (2.4mm) shank length. See price line for thread diameter. 6-48 Oversize (OS) has a

alarneter of . 146	(3.7MM).	
#579-000-077AK	3-56 Tritium Shotgun Sight,	
	9G23V93\$	37.9
#579-000-078AK	6-48 Tritium Shotgun Sight,	
	9G23V93	37.9
#579-000-079AK	6-48 OS Tritium Shotgun Sight,	
	9G23V93	37.9
#579-000-080AK	5-40 Tritium Shotgun Sight,	
	9G23V93	37.9

MARBLE #223 MID-RIB SHOTGUN BEAD

Installs Easily, Ensures Perfect Sight Alignment

Tapered, ivory-color, mid-rib bead helps prevent canting the gun or aiming over the top of the front bead. Stake-on design installs easily at center of barrel or 12" to 16" from muzzle. Drill a #45 hole, follow with #226 Bead Sight Reamer, and pressfit in place.

9G04T11.....\$ **5.99**

SPECS: Ivory-colored, .080" (2mm) diameter. #579-223-000AK #223 Ivory Mid-Rib Sight.

#226 BEAD SIGHT REAMER - Tapers and de-burrs after drilling hole for Marble #223 Mid-Rib Shotgun Bead.

SPECS: Steel. 1" (25mm) long, 1/8" (3.2mm) diameter. #579-226-000AK #226 Bead Sight Reamer 9G03T69. \$ 6.99

MARBLE SHOTGUN SIGHT

3 Styles of Thread-In Sights

EXPERT TYPE - A beautiful sight for most ribs. Shoulders on sight make for easy installation. SPECS: Bead: 1/8" (3.2mm). Shank length: 3/32" (2.4mm).

Gold bead with 3-56 thread or Ivory (white plastic) bead with 3-56 or 6-48 thread **#708-310-332AK 3-56 Expert,** Ivory 9G05Z15.....\$ 7.99 #708-310-631AK 6-48 Expert, Gold 9G04Z59 6.99

#708-310-632AK 6-48 Expert, Ivory 9G05Z15............ 7.99 EXPERT FIBER OPTIC - A bright, eye catching, fiber optic sight for ribs. Shoulders on sight make for easy instal-

SPECS: Bead: .0700" (1.7mm) dia. Shank length: 3/32' (2.4mm). Thread size: 3-56 or 6-48. Color: Green or Orange.

OLOR	3-56 THREAD	6-48 THREAD
REEN	#708-305-331AK	#708-305-631AK
RANGE	#708-305-332AK	#708-305-632AK

- Advise # - Expert Fiber Optic Sight 9G05Z15.. \$ 8.99

order on the web www.brownells.com

comp/trap guns; and Weatherby Orion.

ribs .355" to .440" wide.

BROWNELLS PAGE 291

Orders/Tech: 800-741-0015

BROWNELLS SHOTGUN SIGHT KITS

TWO KITSTHAT COMPLEMENT EACH OTHER

ATOTAL OF 160 GOOD-LOOKING, PRECISION-MACHINED REPLACEMENT SHOTGUN BEADS

SHOTGUN SIGHT KIT "A"



SHOTGUN SIGHT KIT "A" CONTAINS:

No.	Head Dia.	Thread Shaft	Drill & Tap Sizes	Color
1	.067	3 - 56	No. 45 - 3-56	G
2	.130	3 - 56	No. 45 - 3-56	G
3	.175	3 - 56	No. 45 - 3-56	G
4	.175	6 - 48	No. 31 - 6-48	G
5	.067	3 - 56	No. 45 - 3-56	W
6	.130	3 - 56	No. 45 - 3-56	W
7	.175	3 - 56	No. 45 - 3-56	W
8	.175	6 - 48	No. 31 - 6-48	W

SHOTGUN SIGHT KIT "B" CONTAINS:

No.	Head Dia.	Thread Shaft	Drill & Tap Sizes	Color
21	.067	6 - 48	No. 31 - 6-48	G
22	.130	6 - 48	No. 31 - 6-48	G
23	.130	8 - 40	No. 28 - 8-40	G
24	.175	8 - 40	No. 28 - 8-40	G
25	.067	6 - 48	No. 31 - 6-48	W
26	.130	6 - 48	No. 31 - 6-48	W
27	.130	8 - 40	No. 28 - 8-40	W
28	.175	8 - 40	No. 28 - 8-40	W

SHOTGUN SIGHT KIT "B"



Brownells Shotgun Sight Kit "A" is a practical, economical assortment of top-quality, replacement shotgun sights. The workman-ship is superb, being done on the most modern and up-to-date machinery in the U.S.A. The sight globes are true spheres - not lop-sided as those found on many other sights at a higher price. The threads are cut onto the shank, and are clean, sharp and well-machined for the best possible fit. Shanks are threaded right up to the base of the bead so you can set the sight exactly onto the barrel.

Your choice of sights in the Kit is extremely wide. There are 2 shank sizes, 3 bead sizes and 2 bead colors, giving you a total of 8 different sights to choose from so you can fit nearly any gun that comes into the shop.

The two shank sizes are 3-56 and 6-48. Size 3-56 is one of the most widely used shanks in the industry and will fit most guns having threaded sight holes. The 6-48 shaft was chosen for the alternate size to be used when the original hole must be redrilled and tapped - or where there is no hole at all - because 6-48 is the firearm industry standard screw size, and every gunshop in the country will have the drill and tap on hand to make the new hole.

Bead sizes are .067, .130 and .175, (the most popular sizes), giving your customer the choice of small, medium or large beads. In addition, each bead size is available in Gold color - machined from finest brass; or White color - machined from high tensile aluminum alloy. Neither color will bleed at the heels, wear off with hard use, or chip and peel, as almost all enameled sights eventually do.

Brownells Shotgun Sight Kit "A" comes to you very attractively displayed in a clear plastic counter case. Each individual sight number is in its own plainly identified box on a black tray. There are 10 sights of each number, giving you a total of 80 sights in the Kit - 40 Gold and 40 White - a complete inventory of top-quality shotgun sights with an absolute minimum of capital invested.

 $Don't \ pass \ up \ the \ opportunity \ to \ cash-in \ on \ the \ shotgun \ sight \ replacement \ market. For \ an \ unbelievably \ low \ investment \ you \ can \ have$ a complete, correctly balanced and assorted inventory of 80 superb shotgun sights, each carrying Brownells guarantee of perfect workmanship and materials. Don't let yourself get caught short when you can have them on hand so easily. SPECS: Brass and Aluminum Beads in 3½" (8.9cm) x 7" (17.8cm) clear plastic box.

#080-532-000AK Shotgun Sight Kit "A", total of 80 sights in Counter Case 8K40T73 \$69.99 SINGLE PAK REFILL SIGHTS FOR KIT "A"

STOCK #	NO.	STOCK #	NO.	STOCK #	NO.	STOCK #	NO.
#080-532-129AK	1	#080-532-131AK	3	#080-532-133AK	5	#080-532-135AK	7
#080-532-130AK	2	#080-532-132AK	4	#080-532-134AK	6	#080-532-136AK	8
- Advise # - Si	ngle Pak	Shotgun Sight Refills	8K01T76	· 			. \$ 3.99

STOCK #

#080-532-005AK

10 PAK REFILL SIGHTS FOR KIT "A"

STOCK #	NO.	STOCK #	NO.
#080-532-001AK	1	#080-532-003AK	3
#080-532-002AK	2	#080-532-004AK	4

- Advise # - 10 Pak Shotgun Sight Refills 8K09T99

MEPROLIGHT®TRU-DOT


DAY/NIGHT SHOTGUN BEAD

Constantly Visible Sight Almost Like Magic!

N.E.C.G.
SHOTGUN SIGHT BEAD

NO.

5



Unique, universal shotgun sight bead stays visible in all light conditions: bright sun, heavy overcast, late afternoon shadows. deep woods hunting. Tritium gas light source sealed in the center of a blued steel bead. On bright days, the shooter sees a black bead with a light center. As the light fades, the center becomes a soft green glow. No switches, batteries, wires, or charging—the sight is always "on." Drop-in replacement bead for Remington 870, 1100, and 11-87. Other shotguns may require drilling and tapping. SPECS: .160" (4.06mm) H x .158" (4.01mm) W. .110" (2.8mm) long shank, 6-48 thread

#387-314-405AK TRU-DOT Bead 7H29U99 \$ 33.99

This meticulously crafted front bead is made from genuine Mammoth ivory to give a fine shotgun the look of traditional elephant ivory, without violating international trade restrictions. Practical, too, because it gives a clean, easy-to-see,

SPECS: Turned Mammoth ivory, natural finish. .157" (4mm) dia. bead. Undersized 6-48 thread; secure with epoxy adhesive.

#661-104-004AK 4mm Sight Bead,

glare-free, white dot in all light conditions.

STOCK #

#080-532-007AK

Brownells Shotgun Sight Kit "B" is truly the natural and logical companion to the original Kit "A" - giving you all the sights that Kit "A" doesn't contain, but that you need to have for a really versatile and complete replacement shotgun sight inventory. Plus, in Kit "B." we took the practical step of making the White beads out of stainless steel. Stainless is stronger won't crush or distort when the beads are installed, does not have to be removed when the gun goes into the hot bluing solution (and won't dissolve and ruin your bluing bath once it's in there)!! Plus, the stainless won't break off at the top of the shank, stays shiny forever, stands up to tougher use in the field, and generally a lot better sight.

But, the real advantage of Kit "B" is that by combining it with Kit "A", you can now have a selection of shank sizes unequaled among shotgun sights. So, if you get a gun in your shop with a badly misshapen, worn or stripped-out sight hole, you will have a bead of exactly the same size, but with a shank one size larger. Replacement is then just a simple matter of drilling out the hole to the next size larger, tapping, and inserting the new bead.

The most important thing is that the Kit saves you time, giving faster work turnaround in the shop, which makes you more money. It also eliminates "patching-up" the original hole (which often then requires repairing the blue, too) and redrilling and tapping for the original size shank. And, it gets your customer back in the field sooner which makes him happy, and makes you look good! Like the original Kit "A", the workmanship is superb, the sight globes are true spheres, the threads are cut onto the shank, so they are clean, sharp, and give the best possible fit. And, they are threaded right up to the base of the bead so you can set the sight exactly onto the barrel.

Thread sizes are 6-48 and 8-40 - two of the most common and popular thread sizes in the gun industry, so everyone has the necessary drills and taps. The bead sizes are .067, .130 and .175, again the most popular sizes, and the same as those used in Kit "A".

The Gold beads are machined from finest brass; the White beads from tough stainless steel. Because these are solid metal beads, they cannot bleed, chip, peel or have the color wear off.

As the companion to Kit "A", Kit "B" also comes in a clear plastic counter case. Each individual sight number is in its own clearly identified box on a black tray. There are 10 sights of each number, giving you a total of 80 new sights. By itself, a complete inventory of 3 very popular sizes in 2 colors, with 6-48 and 8-40 shanks; but as a companion to Kit "A", an unbeatable assortment of the most versatile and useful shotgun sight beads available anywhere. And, right at your fingertips, ready to install for your customers. Order your Brownells Shotgun Sight Kit "B" today.

SPECŠ: Brass and Stainless Steel Beads in $3\frac{1}{2}$ " (8.9cm) x 7" (17.9cm) clear plastic box.

STOCK #

#080-532-123AK

#080-532-124AK

SINGLE PAK REFILL SIGHTS FOR KIT "B"

		SINGLI	FANN	LLIFE SIGHTS
STOCK #	NO.	STOCK #	NO.	_
0-532-137AK	21	#080-532-139AK	23	#0
0-532-138AK	22	#080-532-140AK	24	#0

- Advise # - Single Pak Shotgun Sight Refills 8K01T76.....

STOCK # 080-532-141AK 25 080-532-142AK 26

#080-532-143AK 27 #080-532-144AK 28

STOCK #

10 PAK REFILL SIGHTS FOR KIT "B"

NO. STOCK # NO. #080-532-125AK 23 25

#080-532-126AK

STOCK # #080-532-127AK 27 #080-532-128AK 28

A special three-flute tap for the oversized Poly-Choke Ex-

#080-598-146AK .146"-48 Tap,

These sizes are correct to the best of our knowledge, however, sizes may vary with year, country of manufacture, etc. Browning, 3mm-5 (Metal bead), 3-56 (Ivory bead); Franchi, M3.0x0.50; Ithaca, 6-48; Marlin, 3-56; Mossberg, 5-40; Remington, 6-48; Ruger®, 3-56; Smith & Wesson, M2.5x0.45; Weatherby, 3-56; Winchester, 3-56.

SHOTGUN SIGHTTHREADS

.146" - 48 TAP

tra Long Shank (5/16") and Bev-L-Blok sights. Use .125" (1/8") drill with this tap.

8K28T10 \$ 33.99

NO.

22

STOCK #

#080-532-122AK

#080-532-121AK 21

BROWNELLS PAGE 292

SATISFACTION GUARANTEED **SINCE 1939**

Brownells Shotgun sight bead kit "C" with shoulders

Shouldered Beads Install To The Right Height Every Time; Popular Sizes In Brass & Stainless Steel

SHOTGUN SIGHT KIT "C" CONTAINS:

No.	Head Dia.	Thread Shaft	Drill & Tap Sizes	Color
10	.130	3 - 56	No. 45 - 3-56	G
11	.130	6 - 48	No. 31 - 6-48	G
12	.175	3 - 56	No. 45 - 3-56	G
13	.175	6 - 48	No. 31 - 6-48	G
14	.067	3 - 56	No. 45 - 3-56	W
15	.130	3 - 56	No. 45 - 3-56	W
16	.175	6 - 48	No. 31 - 6-48	W
17	.175	3 - 56	No. 45 - 3-56	W



Brownells Shotgun Sight Kit"C" is a must have for any gunsmithor sporting goods store looking to save valuable time and really please their customers. We have taken everything that's great about our Shotgun Sight Kits"A" and "B"-like their unparalleled selection of high-quality and size-popular sight beads-and added aspecial feature to make the beads in Kit"C" fast, easy, and convenient to install... every time. It is the fact of the fact of

Every sight bead in Shotgun Sight Kit "C" has the advantage of skirted shoulders. What this means to you, the professional gunsmith or the sporting goods store owner, is you'll never have to get out your mike or calipers again to ensure you've installed the sight to its proper height. No more guesswork either! Because when the skirted shoulder reaches the barrel, it provides a positive stop that lets you know the sight is at its optimum height. Every sight from Shotgun Sight Kit "C" installs with fool-proof ease - saving you both valuable shop time and, even more important, the nightmare of upsetting a valuable customer. Not only will customers be pleased with the installation you do they'll also love the huge selection of sizes and styles from which to

Not only will customers be pleased with the installation you do, they'll also love the huge selection of sizes and styles from which to choose. We selected the most popular sizes from our Shotgun Sight Kits "A" and "B", because we know that's what your customers will come in and ask you for. Plus, we know how important it is to offer different styles to please as many shooters as possible. That's why Kit "C" offers each size bead in both Gold and White. It provides the perfect selection; Gold brass for a classy, traditional look many shotgun owners are partial to and White stainless steel for a sight bead so strong it even stands up to hot bluing. Thread sizes include 3-56 and 6-48 with bead diameters of .067", .130", and .175" to give your customers the choice of small, medium and large beads.

Also, for easy storage and quick identification, we've followed the same, convenient layout of Kits "A" and "B" to make it as simple as possible to find the sight you need. Kit "C's" plastic counter case is divided into eight compartments to keep the beads organized and right at your fingertips. Plus, if you put this great-looking kit on your counter for your customers to see, it's a great way to create more business by reminding people to replace broken or damaged sight beads. Brownells Shotgun Sight Kit "C" is everything you've been looking for; a huge selection, superb quality, and now the convenience of skirted shoulders. Order this time-saving, customerpleasing kit today and enjoy the speed, precision, and ease with which each of these sights installs.

SINGLE PAK SHOULDER BEAD FOR KIT "C"

STOCK #	NO.	STOCK #	NO.	STOCK #	NO.	STOCK #	N
#080-001-001AK	10	#080-001-003AK	12	#080-001-005AK	14	#080-001-007AK	1
#080-001-002AK	11	#080-001-004AK	13	#080-001-006AK	15	#080-001-008AK	1
- Advise # - Sing	gle Pak S	Shouldered Bead, each	a 8K02P22	·			\$

10-PAK SHOULDER BEADS FOR KIT "C"

STOCK #	NO.	STOCK #	NO.	STOCK #	NO.	STOCK #	NO.
#080-000-117AK	10	#080-000-119AK	12	#080-000-121AK	14	#080-000-123AK	16
#080-000-118AK	11	#080-000-120AK	13	#080-000-122AK	15	#080-000-124AK	17
- Advise # - 10-Pak Shoulder Bead Refills 8K15C99 \$24.99							

- MOUNTING SOLUTIONS PLUS SIGHTLINK FIBER OPTIC SHOTGUN SIGHT

Multiple Color & Length Options For Optimal Contrast

Machined steel, front sight base with fiber optic rod delivers optimal sight contrast in most light conditions. Base replaces factory bead sights with 6-48 tpi thread size. Models available with red or green light rod, plus an extra rod of the same color that can be cut for custom length applications to obtain maximum light gathering. Optional <code>Red/Green Rods</code> include (1) red and (1) green, 4" long light rod to reburbish or customize your

Sightlink sight or other aftermarket fiber optic sights. SPECS: Base - Steel, matte black. .25" (6.3mm) long x .14" (3.5mm) diameter, 6-48 tpi thread. Rods - Polymer, red or green. .08" (2mm) diameter.

STOCK#	MODEL	DESCRIPTION	PRICE
#100-003-356AK	Sightlink Red Front	Single front sight base w/extra red rod, 2" (5.1cm)	1K06Y88 \$ 8.95
#100-003-357AK	Sightlink Green Front	Single front sight base w/extra green rod, 2" (5.1cm)	1K06Y88 \$ 8.95
#100-003-362AK	Red/Green Rods	(1) red & (1) green rod, 4" (10.2cm) long	1K12Y25 \$ 16.54

SIMS VIBRATION LABORATORY DEAD CENTER DUAL-COLOR SHOTGUN SIGHT

Dual-Color Fiber Optics Provide Exceptional Contrast & Clarity; Easy To Install

Red fiber optic rod surrounded by a contrasting green outer fiber optic sleeve creates a unique, dual-color dot with exceptional contrast and clarity in all light conditions. Available in choice of

two mounting systems that attach the sight to the shotgun rib without screws, drilling or tapping. Both systems index against the original front bead to prevent shifting under recoil. Simple, stick-on **Adhesive** mounting system installs easily on any ventilated rib .296" wide or wider. **Magnetic** system uses powerful magnets and interchangeable, low-profile mounting adapters to fit a wide range of rib widths to hold the sight in place. **SPECS:** Rods/Sleeves - Polymer fiber optic. Base - Plastic, black. 2" (5.1cm) long x 5%6" (7.6mm) wide. **Adhesive** - Center Rod: .06" (1.5mm) dia. Outer Sleeve: .12" (3mm) dia. **Magnetic** - Center Rod: .05" (1.3mm) dia. Outer Sleeve: .08" (2mm) dia. Includes adapters to fit .24", .25", .29", .313", .315", and .39" wide ventilated ribs.

#100-005-456AK	Adhesive Dual-Color Sight,
	7K09X94
#100-004-196AK	Magnetic Dual-Color Sight

	7K09X94	\$ 11.99
(Magnetic Dual-Color Sight,	
	7K26C99	29.99



Advanced tunnel sight with highly visible green or red fiber optic rod provides improved sight contrast in all light conditions. Front sight dot is only visible when properly aligned.

forcing correct shooting form and increased accuracy. Features a polymer base that installs over the ventilated rib and is held firmly in place with a high-strength dual sided tape for quick installation without screws. Does not require rear sight. Fits all shotguns equipped with ¼", 7mm, or ½6" wide ventilated ribs and removable front beads, including most Remington, Browning, and Ithaca shotguns.

SPECS: Base - Polymer, black. 3¼" (8.2cm) long. Rods - Polymer, (1) red or (1) green, 1½/16" (3.3cm) long x .06" (1.5mm) dia. Sight fits all shotguns with ¼" (6.3mm), ½2" (7mm), or ½16" (7.9mm) wide ventilated ribs.

2K15X15	\$ 19.99	
2K15X15	19.99	



TRUGLO GLO-DOT SHOTGUN SIGHT

High Visibility Glowing Dot No Batteries Required

Lightweight, fiber-optic rod presents a bright, glow-

ing bead for better visibility in both bright and low light hunting conditions. Mounts to the top of all ventilated rib shotguns using dual-sided tape (included). Does not require front bead removal. May also be installed by drilling and tapping rib, screws not included.

SPECS: Base - Plastic, matte black. 3" (7.6cm) long. Rods - Polymer, red or green. 24" (5.7cm) long x. 060" (1.5mm) dia. Fits all ventilated rib shotuns

#902-100-090AK	Red Glo-Dot Sight, 2K13X50	\$ 18.05
#902-100-091AK	Green Glo-Dot Sight,	
	2K13X50	 17.99

GLO-DOT II - Bright, high-visibility red or green fiber optic rod snaps in place behind factory front bead on plain barrel 12 or 20 gauge shotgun; no gunsmithing required. Notch in base uses factory bead to locate Glo-Dot II sight correctly along bore axis.



SPECS: Base - Plastic, matte black. 2½" (6.35cm) long. Rods - Polymer, red or green. 2¼" (5.7cm) long x .078" (2mm) dia. Fits 12 and 20 gauge, un-ribbed barrels .728" (18.5mm) O.D. or larger.

#902-093-728AK	Red Glo-Dot II Sight,	
	2K13X73	\$ 19.51
#902-092-728AK	Green Glo-Dot II Sight,	
	2K13X73	 19.51

GLO-DOT XTREME - Magnetically attached, highly visible fiber optic sight provides exceptional sight acquisition in all light conditions. Features four different bases with different internal mounting dimensions that fit a variety of ventilated ribs. Polymer base snaps onto



the rib and is held firmly in place with a high-strength magnet for quick installation without screws. Includes one red, green, yellow, and amber fiber optic rod. Rods are easily interchanged using thumb and finger pressure. Notch in base uses factory bead to locate sight correctly along bore axis. Two sets of magnets allow mounting sights on two shotguns with different width ventilated ribs. Includes pocket sized, steel case for convenient storage. Universal fit for all shotguns equipped with ¼"(6.4mm), ¾6"(7.9mm), ¾"(9.5mm), or ½"(12.7mm) wide ventilated ribs. Includes one base of each size.

SPECS: Bases - Plastic, black. (1) .260" (6.5mm), (1) .330" (8.4mm), (1) .420" (10.7mm), (1) .520" (13.2mm) internal dimension. 2" (5.1cm) long. Rods - Polymer, (1) red, (1) green, (1) yellow, (1) amber. 1"3%" (2cm) long x .060" (1.5mm) dia. Includes (2) sets of magnets & steel carry case. Universal fit for all shotguns equipped with %" (6.4mm), %#" (7.9mm), 3%" (9.5mm), or ½" (12.7mm) wide ventilated ribs.

#902-000-124AK Glo-Dot Xtreme 2K23X57 \$ 29.99

TRUGLO BRITE-SITE SHOTGUN SIGHT



Tritium & Fiber Optic Sight Provides Superior Contrast, Day Or Night

Advanced Tritium Fiber Optic technology combines glow-in-the-dark tritium with a bright, fiber optic rod to

keep you on target during all lighting conditions. Highly visible, \$%e" diameter green dot ensures quick sight acquisition. Heavy duty, precision-machined aluminum base with protective wraparound cage prevents damage and snagging. Mounts to barrel with included 6-48 tpi screws that hold tight under the heaviest recoil. Hardcoat anodized for durability. Not designed for ventilated rib barrels; gunsmith installation recommended. \$\sumeting{\sumeting{E}} SPECS: Aluminum base, black. Base -2½" (6.3cm) long x%e" (1.6cm) wide. T.F.O. rod - green, 2½" (5.4cm) long x 3½e" (4.8mm) dia.

#902-000-112AK 131SG T.F.O. Brite-Site 2K70X36. \$ 79.99

BROWNELLS ... ONLY THE BEST ...

TRUGLO SHOTGUN STARBRITE DELUXE SIGHT



Durable, Machined Aluminum & Bright Fiber Optic Bead

Highly visible, bright red or green, aiming point lets you concentrate on following the target and making the shot. Improves sight acquisition in all light conditions for fast, almost automatic alignment. Machined aluminum body provides years of rugged

service. SPECS: Body: aluminum, black, anodized finish. Bead: .250"


(6.35mm) long, .05" (1.3mm) dia. Shank length: 3/32" (2.4mm). Thread sizes 3-56 tpi, 5-40 tpi, 6-48 tpi. STK # 3-56 STK # 5-40 STK # 6-48 COLOR

0	0	0	
#902-000-048AK	#902-000-050AK	#902-000-052AK	Red
#902-000-049AK	#902-000-051AK	#902-000-053AK	Green
	tarbrite Deluxe	0 0 /	0.10
21	K06145		\$ 9.16

CAVALRY ARMS REMINGTON 870 SST-870 FRONT SIGHT

Allows Using AR-15/M16 Style Rear Sights


Extra high, AR-style front sight post provides the proper height to regulate with any AR-15/ M16 style rear sight mounted to the Picatinny rail on the Calvalry Arms, Rem. 870 stock conversion. High visibility, red front post for fast acquisition in all lighting conditions. Clamps around the barrel and magazine extension tube to provide a rock-solid anchor that holds tight during




SPECS: Steel, parkerized. Polymer spacing block and post. Height from top of barrel to top of sight post - 21/16" (5.3cm). Regulates with AR-style rear sights used on Cav Arms AR-15 stock conversion. Fits Rem 870 with non-rib barrel and factory magazine extension. Will fit non-factory magazine extensions with minor modification.

#100-003-722AK Remington 870 Clamp-On Front Sight,

MEPROLIGHT® SHOTGUN NIGHT SIGHT





maintenance free.

SPECS: Blued steel with green Tritium inserts. M1 Benelli has post front and ghost ring rear. Fits M1 and M3 Ghost Ring. M2 Benelli has post front and ghost ring rear. Fits M2, Nova, and Super Nova with ghost ring rear sight. Tactical Benelli fits M1 Tactical M and Practical. **Remington** fits guns originally equipped with rifle sights. Mossberg has front post only. Fits 500 and 590 with factory ghost ring rear sight only.

#387-400-510AK	M1 Benelli Night Sight,	
	7H89A99\$	99.99
#387-000-052AK	M2 Benelli Night Sight,	
	7H89Y99	99.99
#387-400-511AK	Tact. Benelli Night Sight,	
	7H89A99	99.99
#387-310-460AK	Rem. 870, 1100, 11-87 Night Sight,	
	7H99A99	119.99
#387-400-500AK	Mossberg Night Sight,	
	7H40A99	47.99



SHOTGUN HEAVY DUTY **GHOST RING SIGHT**

Fast, Rugged Tactical Sight

Rugged steel ghost ring sight naturally centers, and draws the eye to the front sight for fast target acquisition. Adjusts for windage and elevation with hardened detents. Sturdy ears protect aperture. Contour Plain fits round-top receivers. Weaver clamps to any Picatinny or Weaver-style base.

SPECS: Steel, black, matte finish. . 193" (4.9mm) diameter aperture 2.2" (5.6cm) long. .94" (24mm) wide, .94" high. 3 oz. (85 g) weight. Contour requires drilling and tapping, fits Benelli, Ithaca, Mossberg, Remington and Winchester.

#625-105-000AK Contr Ghost Ring Sght 3K78T13 . \$ 117.99 #625-000-002AK Weaver Base G/R Sight 3K101Y59 . 136.99

SAGE INTL. SHOTGUN COMBAT SIGHT

Faster Sight Pickup In Low Light

Rugged, combat sights give enchanced point of aim in low light or even complete darkness. Tritium dot front post glows for fast pickup through the adjustable, rear ghost



ring aperture. Steel side guards protect the sights. Designed for plain barrels, or remove part of rib to install on ribbed barrels. SPECS: Steel, matte blue finish. Includes (1) front sight, (1) rear sight, and instructions. Measure barrel and choose the correct front sight band from barrel diameter chart. Band installation requires interference fit, band will not expand more than .015". Installation requires drilling and tapping of receiver and barrel.

STOCK#	BARREL DIA.	PRICE
#819-200-833AK	.833"843"	9A193V07 \$ 241.99
#819-200-590AK	Mossberg 590 only	9A193V15 \$ 241.99
#819-200-880AK	.880"890"	9A193V07 \$ 241.99

SCATTERGUNTECHNOLOGIES REMINGTON TRAK-LOCK® II GHOST RING



SIGHT SET **Tritium Provides Excellent Sight** Acquisition, Day Or Night

Self-illuminating, Tritium dot front sight combined with a large

light gathering rear ghost ring provides extremely fast sight acquisition during day or low light conditions. Rear ghost ring is available with or without tritium. Trak-Lock rear sight features a single set-screw for windage and elevation adjustments. Rugged, low-profile steel body has black parkerized finish for durability. TF20 & TF12 contains tritium dot front sight with standard rear ghost ring. TFR20 & TFR12 includes tritium dot front sight with tritium two dot rear ghost ring for precise alignment while aiming. Both models available for 12 and 20 gauge. TF12F0 contains Tritium front sight only. Fits 12 gauge.

SPECS: Steel, black parkerized. Fits plain barrel Rem. 870, 1100, 11-87, SPT-12. Adapts to fit other guns. Requires drilling and tapping of receiver; front sight epoxies over factory front. Includes rear mounting screws. **TF20 -** Tritium front sight with standard rear ghost ring. Fits 20 gauge. TF12 - Tritium front sight with standard rear ghost ring. Fits 12 gauge. **TFR20 -** Tritium front sight with tritium rear ahost ring. Fits 20 gauge. TFR12 - Tritium front sight with tritium rear ghost ring. Fits 12 gauge. TF12F0 - Tritium front sight

		The second secon
only. Fits 12 gaug	e.	
#800-110-000AK	TF12 Trak-Lock II Tritium Front w/Std	Steel, screw-on/sold
	Rear, 12 Ga. 8Z99V99 \$ 114.99	and a checkered rear s
#800-000-007AK	TFR12 Trak-Lock II Tritium Front/Rear,	for 12 gauge barrels w
	12 Ga. <i>8Z119V95</i> 149.99	SPECS: Steel, blued,
#800-000-009AK	TF12F0 Trak-Lock II Tritium Front	(15.5mm) wide. Height
	Sight, only, 8Z55V14 69.99	3/8" (9.5mm). Accepts n
#800-000-006AK	TF20 Trak-Lock II Tritium Front w/Std	#962-011-125AK Sho
	Rear, 20 Ga. 8Z99V95 124.99	#962-011-187AK Sho
#800-000-008AK	TFR20 Trak-Lock II Tritium Front/Rear,	#962-011-281AK Sho
	20 Ga. <i>8Z119V95</i> 149.99	#962-011-375AK Short
	0.471054.071044.044	
	SATISFACTION GUA	A <i>KAN I EED</i>

TRIJICON SHOTGUN ADJUSTABLE NIGHT SIGHT

Low Light. **Tactical Sight System** Rugged, steel rear sight has quick-

to-use, single screw adjustment for windage and elevation that won't work loose with recoil. Ghost ring aperture has two tritium inserts for fast sight pickup. Steel, post front sight has single, glowing tritium dot that puts you on target fast in daylight or darkness. Glass lamps, sealed in aluminum cylinders with polished sapphire windows for a crisp

outline of light. SPECS: Steel, matte finish, black. Fits plain barrel Rem. 870, 1100 and 11-87. Can be adapted to other models. Requires drilling and tapping receiver. Front sight epoxies over factory sight. Includes

#892-004-004AK Adi. Night Sight 2H104V25..... \$ 109.65

TRUGLO TRU-POINT XTREME **SHOTGUN SIGHT SET**

Fast & Accurate Sighting

Highly visible, fiber optic sight brings your eye quickly to the sight in all ight conditions. Improves accuracy for slug and turkey guns. Contrasting red front and green rear fiber optic rods are easy to locate in low-light. All steel front and rear sights clamp solidly to rib. Maintains sight



settings, prevents shifting under recoil. Adjustable for windage and elevation. Magnum Pro Gobble Dot features a conventional rifle-style rear sight with square notch that works well in most light conditions. Models available for 5/16" (7.9mm), 3/8" (9.5mm). 6mm, and 8mm wide ventilated ribs. **Tru-Point Xtreme** features a rear sight that includes a square notch sight blade and an easily interchangeable ghost ring. Fits all shotguns equipped with ¹¼", 5/16", or 3%" wide ventilated ribs. **=**

SPECS: Magnum Pro Gobble Dot - Steel, black. Front Sight -1.4" (3.5cm) long. Rod - Polymer, red, 15/16" (23.6mm) long x .029" (.7mm) dia. Rear Sight - 1.4" long. Rod - Green, .035" (.89mm) dia. Fits $\frac{5}{16}$ " (7.9mm), $\frac{3}{8}$ " (9.5mm), 6mm, and 8mm wide ventilated ribs. Tru-Point Xtreme - Aluminum, anodized, matte black, Front Sight-15/16" (3.3cm) long. Rod-Red, 1" (2.5cm) long x.060" (1.5mm) dia. Rear Sight - 17/16" (3.6cm) long. Ghost Ring - 1/4" (6.4mm) I.D. Rods - Green, .029" (.7mm) dia. Fits ¼" (6.4 mm), 5/16", or 3/8" wide ventilated ribs

#902-000-002AK	.312" Magnum Pro Sight,
	2K43T22
#902-000-003AK	.375" Magnum Pro Sight 2K44T62 62.99
#902-000-004AK	6mm Magnum Pro Sight 2K44T5162.99
#902-000-028AK	Benelli Magnum Pro Sight,
	2K43T22
#902-000-119AK	Tru-Point Xtreme Sight 2K43X2354.99

WILLIAMS SHOTGUN SHORTY RAMP



Mounts Rifle Sights On Plain Barrel Shotguns

Steel, screw-on/solder-on ramps with standard 3/8" dovetail and a checkered rear surface to cut glare. .4375" radius designed for 12 gauge barrels with .875" outside diameter.

SPECS: Steel, blued, matte finish. 13/4" (4.4cm) long x .612" (15.5mm) wide, Heights - 1/8" (3.1mm), 3/16" (4.7mm), 9/32" (7.1mm), 3/8" (9.5mm). Accepts parrow ramp sight blades.

	#962-011-125AK Shorty Ramp, 1/8" 2F19B99	\$ 22.49
)	#962-011-187AK Shorty Ramp, 3/16" 2F16B28	18.99
	#962-011-281AK Shorty Ramp, %32" 2F16B28	18.99
)	#962-011-375AK Shorty Ramp, 3/8" 2F19B99	24.49

WILLIAMS UNIVERSAL "SLUGGER" FIRE SIGHT



Quickly Turns Rib-Equipped Shotguns Into Slug Guns

Give your favorite shotgun a more accurate, rifle-style sight picture in only minutes. Clamps to vent-rib; fast to install and

fast to remove. Adjusts for windage and elevation. Front sight provides a red dot that glows in all ambient light conditions. The more light, the brighter it glows; won't "wash out", even in direct sunlight. U-Notch rear blade is equipped with a bright green rod on either side of the notch for precise, low-light sight alignment.

SPECS: Machined aluminum, black, anodized, matte. Universal fit for all shotguns equipped with $\frac{1}{4}$ " (6.3mm), $\frac{5}{16}$ " (7.9mm) and $\frac{3}{8}$ " (9.5mm) wide, vent ribs. Rear - "U" notch fiber optic. Front - Fluorescent red front bead on sheared-style blade. Includes wrench and instructions.

#962-000-014AK Universal Slugger Fire Sight,

SHOTGUN FIRE SIGHTS - Models for Browning BPS, pre-2003 Remington 870/1100, Mossberg 500 and Winchester 1300 guns equipped with slug or turkey





barrels and factory sight bases. Front sight provides a glowing red dot that's easily seen in all ambient light conditions. Fully adjustable, U-notch rear has two glowing green dots for precise sight alignment.

SPECS: Machined aluminum, black, anodized, Rear - "U" notch fiber optic. Front - Fluorescent red front bead on sheared-style blade. Includes instructions. **Browning** fits BPS shotgun with slug barrel; does not fit vent rib barrel. Remington fits Remington shotguns with 3/8" dovetail front sight ramp.

#962-000-023AK Browning Fire Sights,

	2F26B15
#962-565-300AK	Remington Fire Sights 2F21D39 24.99
#962-000-001AK	Mossberg Fire Sights $2F23B39$ 27.99
#962-000-002AK	Winchester Fire Sights 2F24B15 27.99

REMINGTON GHOST RING FIRE SIGHTS - Bright, high contrast fiber optic sights with large aperture, rear ghost ring provide fast, accurate sight alignment in all light conditions. The more light, the brighter the beads glow. Front sight has a single red insert, rear ghost ring has two green inserts to form an easy-to-align, 3-dot sight picture. Fits Remington shotguns with 3/8"

dovetail front sight ramp. SPECS: Steel front 3/8" dovetail sight. Aluminum rear sight. Black, matte fin-

ish. Fiber optic insert. Bead - 1/16" (1.6mm) dia. Ghost Ring - .15' (3.8mm) dia. aperature. #962-000-083AK Rem. Ghost Ring Fire Sights,

ITHACA 37 FIRE SIGHT - Contrasting, green rear and red front dots provide excellent sight visibility. Eye-catching colors give fast, accurate sight alignment against dark backgrounds. Fully adjustable for windage and elevation; replaces factory rear sight and front



bead. Fits Deerslayer models, no gunsmithing required. Metal body construction for durable service.

SPECS: Aluminum, anodized, matte black, Rear - 21/2" (6.4cm) long. fits nominal 3/8" dovetail. **Front blade -** 5/8" (15.9mm) long. #962-000-017AK Ithaca 37 Fire Sight 2F29B99 \$ 34.99



Need a Replacement Part?

Shop the Factory Parts section in this catalog

Schematics also available online

BROWNELLS PAGE 294

SINCE 1939



VANG COMP SYSTEMS REM 870/1100/11-87 **GHOST RING SIGHTS**

Extremely Rugged; Provides Fast Target Acquisition

Heavy duty Picatinny rail with integral ghost ring sight naturally centers for fast target acquisition during tactical ops. Front sight features a blade with white dot and solid steel side guards for maximum pro-



tection. Aperature is fully adjustable for windage and elevation using clearly marked adjustment screws that hold under heavy recoil. Front sight is adjustable for elevation with included tool. Rail allows mounting or scopes and red dot sights. Designed for non-ribbed barrels.

SPECS: Fits Remington 870/1100/11-87 shotguns with non-ribbed barrels. Front sight requires soldering with Silvaloy 355 (not included). Ghost ring/rail requires drilling and tapping receiver for 8-40 tpi screws. Includes mounting hardware and instructions. Front Sight - Steel, in-the-white, .110" (2.8mm) diameter white dot. Ghost Ring/Rail - One-piece, hard anodized aluminum sight body and rail. 2.2 oz.(62.4g) weight. Rail - 23/4" (7cm) long x .830" (21mm) wide. Aperature - Steel, black. .23" (5.8mm) I.D. .5" (mm) high from top of receiver to center of aperature.

	Front Sight 6K56Y34	. \$ 69.99
#100-004-335AK	Rear Ghost Ring Sight w/Rail,	
	<i>6K165H52</i>	189.99

XS SIGHT SYSTEMS REMINGTON SHOTGUN TACTICAL GHOST RING SIGHT SET



Speeds Sight Acquisition

Convert your shotgun to a tactical workhorse. Banded front sight features green, tritium dot surrounded by a white ring. Supplied shims ensure barrel band clamps snugly around muzzle. Contoured rear sight requires drilling

and tapping; includes two interchangeable aperture sizes. Completely adjustable for windage and elevation.

SPECS: Steel, black, matte finish. Front Sight - Tritium dot with white ring, 3/4" (19mm) high from top of barrel. Rear Sight - Base, 1½" (38mm) long, ¾" wide, 1" (25mm) long. Small aperture I.D., 3/16" (4.8mm); large aperture I.D., 7/32" (5.6mm). Fits Rem 870, 1100, 11-87 shotguns with .860-.885" (21.8-22.5mm) muzzle diameters. #006-000-107AK Tactical Ghost Ring Sight Set.

	6K120V00	\$ 144.00
#006-000-118AK	Banded Front Sight, only,	
	6K52V50	63.00



XS SIGHT SYSTEMS SHOTGUN TACTICAL GHOST RING SIGHT SET

For Tactical & Hunting Use

Includes green tritium front sight and two, interchangeable, fully adjustable, rear ghost ring apertures to accommodate long- and short-range shooting. Steel wings give added rear



sight protection. Dovetailed front sight fits factory sight ramp with minor fitting.

SPECS: Steel, blue, matte finish. Tritium dot/white ring front sight, 3/8" (10mm) high. **Rear Sight –** base, 11/2" (38mm) long, 3/4" (19mm) wide, 1" (25mm) long, Small Aperture I.D. - 3/16" (4.8mm); Large Aperture I.D. - 7/32" (5.6mm). Rear sight requires drilling and tapping, front sight requires sight ramp.

STOCK #	FITS	
#006-000-108AK	Rem. 870/1100/11-87	
#006-000-109AK	Mossberg 500/590, Ithaca 3	7
Advise # Testing	1 Sight Set CV119V50	0 00

XS SIGHT SYSTEMS SHOTGUN **BIG DOTTRITIUM FRONT SIGHT**

Installs Easily Over

The Existing Bead Sight High-visibility Tritium dot

front sight surrounded by a large white ring epoxies over the existing front bead sight to help improve target focus and low light sight acquisition and sight recovery after muzzle flash. Installs over front sight beads from .125" - .140" diameter by filling the cavity on the underside of the sight with Brownells Acraglas Gel, then pressing the sight over the bead and allowing it to fully cure. If existing bead is too small or too large, replace with Brownells #6 bead for 3-56 threads or #26 for 6-48 threads. Some shotgun barrels may require drilling and tapping of existing hole to 6-48 for installation of #26 Brownells bead. Remington Pedestal model with stepped bottom fits Remington shotgun barrels with front sight pedestal. Vent Rib model with flat bottom fits shotgun barrels with ven-

shotgun barrels. Includes instructions. SPECS: Machined steel, black, matte finish. Big Dot .161" (4mm) diameter. Fits beads from .125" (3.2mm) to .140" (3.5mm). Remington Pedestal fits Remington front sight pedestals. Vent Rib fits ventilated ribs. Plain Barrel fits round barrels. Includes instruc-

tilated ribs. Plain Barrel model with cupped bottom fits round

tiono.	
#006-000-158AK	I
	6

Remington Pedestal Big Dot Tritium, 6K45V00 . #006-000-159AK Vent Rib Big Dot Tritium 6K45V00 . 54.00 #006-000-160AK Plain Barrel Big Dot Tritium, 6K45V00......**54.00**



BROWNELLS -

Make Inserts Quickly & Easily In A Variety Of Colors



It's been several years since there was a good, do-it-yourself product on the market for making sight inserts, so we decided the best way to fill the gap was to go out and develop our own. The result is our latest "assist" for the professional gunsmith and serious hobbyist - a kit with everything you need to add, change, or rebuild colored front sight inserts on

revolvers quickly and easily. Although primarily designed for wheelguns, it'll also let you make custom inserts for a variety of rifles, shotguns, and pistols. Sight inserts offer many benefits for target shooters and hunters, especially in situations requiring fast, accurate front sight acquisition, like dawn and dusk, when game is more likely to be active. Never again replace a perfectly good front sight because it's too hard to see in low light, your eyes aren't as good as they used to be, or because the insert has faded, broken, or fallen out.

Our kit contains everything you need to make professionallooking inserts formed to the exact contours of your gun's front sight. Mix the liquid acrylic and powdered activator with the concentrated dye to create bright, high-contrast inserts that are stronger and more durable than factory originals at a fraction of the cost of replacement or custom sights. Kit includes dyes in five popular colors-red, green, orange, yellow, and white.

Step-by-step instruction booklet show you how to mix the ingredients (the ratios aren't that critical so it's tough to screw up) and create forms to install inserts that won't shoot loose, even on the hardest recoiling guns. We also explain, in detail, how to hand cut a dovetail for an insert on a gun that doesn't already have one. With a hardening time of around 20 minutes, it's so fast and easy you'll want to add inserts to get the best accuracy and maximum versatility from all your iron-sighted guns. Refill supplies sold separately, so you can replace only the ingredients you use up rather then buy a whole new kit.

SPECS: Kit contains: 1 oz. (29.57 ml) Liquid Acrylic: 2 oz. (59.15 - Advise # - Tactical Sight Set 6K112V50..... \$ 150.00 ml) Powdered Activator; .05 oz. (1.5 g) each of red, green, orange,

BIRCHWOOD CASEY SIGHT BLACK

Easy-To-Use Aerosol

Flat-black coating stops glare and reflections on sights. Goes on easily, dries quickly. Won't hurt finishes. SPECS: 3.5 oz. (103 q) net contents aerosol can. #167-127-000AK Sight Black,

Sight Black, per each,

Cannot ship outside Continental U.S. Ship UPS or FedEx Ground only within U.S.

BRIGHTSIGHTS GUN SIGHT COATING



High-Visibility Paint Improves Sight Contrast For Better Shot Placement

Tough, flexible coating provides a highly visible contrast between sights and target. Provides more accurate shot placement, improves sight

picture and focal concentration on front sight. Durable, won't harm firearms finish. Easy-to-apply Five Color Kit for use on rifle, pistol and handgun sights. Three color, Ghost Glow Kit contains a light activated, luminescent coating for use in reduced visibility situations.

SPECS: 3cc glass bottles. Five Color Kit - Red. White, Green, Orange and Yellow, plus cleaner. Ghost Glow Kit - Green, Yellow and Orange colors plus Green, Yellow and Orange luminescent, light

#100-000-243AK	Gun Sight Five Color Kit,
	<i>3K09X50</i>
#100-000-244AK	Gun Sight Ghost Glow Kit,
	3K14X00

Brownells SIGHT INSERT KIT

Easily Install Colored Plastic Front Sight Inserts

Everything you need to install or replace a colored plastic front sight insert. Enough material for 228 Sight Inserts, plus files and complete, illustrated instructions.

SPECS: Kit Contains: PLASTIC SHEETS, 7 pieces, 2" (5.1cm) x 6" (15.2cm), one each, Black, White, Yellow, Orange, Traditional Red (matches

factory front sights). Fluorescent Red. and Fluorescent Green: 3-SQUARE NEEDLE FILES, one fine cut, one medium cut; NEE-DLE FILE HANDLES, 2; INSTRUCTIONS.

STOCK #	COLOR	STOCK	# COLOR	
#080-068-069AK	Black	#080-068-0	72AK Orange	
#080-068-070AK	White	#080-068-0	73AK Red	
#080-068-071AK	Yellow	#080-068-0	74AK Flo. Red	
#080-068-075AK	Flo. Green			
- Advise # - Sight Insert Sheet 8K08A28 \$ 10.99 #080-068-000AK Sight Insert Kit 8K40A87 52.99				
#076-200-115AK	Instructions	$4B00YJJ \dots$	NC	

yellow, and . 19oz. (5.3g) of white pigment; 5 mixing cups; complete

1	mondettons.	
)	#081-000-370AK	Front Sight Insert Kit 1H41A84 \$ 60.99
7	#081-000-371AK	Powdered Activator, 2 oz.,
)		1H06A9512.47
7	#081-000-372AK	Liquid Acrylic, 1 oz. 1H14A81 20.97
l	#081-000-375AK	Red Pigment, .05 oz. 1H03A33 4.99
3	#081-000-376AK	Orange Pigment, .05 oz. 1H03A33 4.99
	#081-000-377AK	White Pigment, .19 oz. 1H03A52 4.99
5	#081-000-002AK	Mixing Cup Refill, 25-pak,
,		1H02X13

KG INDUSTRIES SITE KOTE



Change Sight Colors Instantly; Great For Touch-Up Or Changing ColorsTo Match Conditions

High-pigment sight paints allow the iron sight shooter to add, change or touch-up sight colors in as little as 60 minutes. Greatly improves sight acquisition, shooter focus, and helps shooters

tailor their sights for competition, hunting or self defense. Coating dries flexible to resist chipping and will not fade over time. Great for adding color to new gun sights and archery sight pins, or touching up worn, or chipped sights on all types of weapons. Easy-to-use needle applicator bottle puts the exact amount of paint right where you want it - no waste and no paint brush required. Shake bottle, apply and allow 1 hour to dry. One bottle paints a lifetime of sights.


SPECS: ¼ oz. (7.4 ml) needle applicator bottle. Available in Red,

White, Neon Gree	en, Neon Yellow and Safety Orange.	
#665-000-010AK	Red Site Kote 5F09P23	\$ 12.9
#665-000-011AK	White Site Kote 5F09P23	12.9
#665-000-012AK	Orange Site Kote,	
	5F09P23	12.9
#665-000-016AK	Neon Yellow Site Kote,	
	5F09P23	12.9
#665-000-015AK	Neon Green Site Kote,	
	5F09P23	12.9

BROWNELLS REPLACEMENT FIBER OPTIC RODS

Super Bright For Enhanced Sight Picture

Refurbish fiber optic sights by replacing broken or damaged rods, or change sight colors to enhance the sight picture with these super-bright replacement rods. Sold in 6" lengths; cut to fit your needs. Available in red or green in four common diameters (see



DIA.	STOCK # RED	STOCK # GREEN	PRICE
.020" (.5mm)	#080-000-727AK	#080-000-728AK	9A03Y04 \$ 3.99
.030" (.75mm)	#080-000-725AK	#080-000-726AK	9A03Y04 \$ 3.99
.040" (1mm)	#080-000-729AK	#080-000-730AK	9A03Y63 \$ 4.99
.060" (1.5mm)	#080-000-731AK	#080-000-732AK	9A03Y63 \$ 4.99

MOUNTING SOLUTIONS PLUS FIBER OPTIC SIGHT RODS

Restore Fiber Optic Sight's Bright, Glowing Dot

Optical-grade, acrylic rods replace lost or broken rods on popular fiber optic sights. Pak includes one each: red, green, and amber fiber optic rods. Available in four diameters: .060" diameter rod fits most shotgun sights and .125" wide pistol sights. .040" fits most rifle and some shotgun sights, plus .090" wide pistol sights. .030" and .020" rods fit competition-style, rifle sights. SPECS: Optical-grade, acrylic rod. One each in red, green, amber. 6" (15.2cm) long. .060" (1.5mm), .040" (1mm), .030" (.75mm), or

.020 (.311111) ula.		
#100-001-459AK	.060" Fiber Optic Rod, 3-pak,	
	1K17X88	9
#100-001-460AK	.040" Fiber Optic Rod, 3-pak,	
	1K13X86	9
#100-001-461AK	.030" Fiber Optic Rod, 3-pak,	
	1K06X709.	7
#100-001-462AK	.020" Fiber Optic Rod, 3-pak,	
	1K05X50	2

order on the web

www.brownells.com