



Trijicon[®]


TRIJICON MRO[™]

(Miniature Rifle Optic)

- 
- **LARGE VIEWING AREA**
Allows faster target acquisition and engagement with reduced "tube effect".
 - **ADJUSTABLE BRIGHTNESS SETTINGS**
Eight brightness settings with a mid-position "Off" feature.
 - **AMBIDEXTROUS BRIGHTNESS CONTROL**
Brightness dial is equally usable by left or right-handed operators without having to remove hand from fire control.
 - **EASY-TO-SET ADJUSTERS**
Adjusters provide positive-click reticle movement in ½ MOA increments and require no special tools for operation.
 - **AIRCRAFT-GRADE ALUMINIUM HOUSING**
Forged 7075 housing and fully-sealed construction protect against the toughest elements.
 - **SURFACE-FLUSH ADJUSTERS**
Eliminates snag hazards and ensures against inadvertent adjustment or loss of zero.
 - **SUPERIOR QUALITY GLASS LENSES**
Multi-coated lenses provide superior clarity and light gathering capabilities with zero distortion and provide for a crisp dot reticle.
 - **PARALLAX-FREE**
 - **WATERPROOF TO 30 METERS (100FT.)**
Dry-nitrogen filled to eliminate fogging.
 - **SINGLE LITHIUM BATTERY**
5 years of continuous use at day-setting 3 (setting 5 of 8) at 70°F with supplied lithium battery.
 - **LIMITED LIFETIME WARRANTY**



MODEL SPECIFICATIONS



2.0 MOA Dot

MAGNIFICATION	1x
OBJECTIVE LENS	25mm
CLEAR APERTURE	0.805 in. 20.4mm
EYE RELIEF	Infinite
ADJUSTMENTS	1 click = 1/2 MOA
ADJUSTMENT RANGE	70 MOA Total Travel
DIMENSIONS (L x W x H)	2.6 x 1.7 x 2.0 in. (w/o mount) 66 x 43 x 51mm
WEIGHT	4.1 oz. (w/ supplied lithium battery and w/o mount) 116g
ILLUMINATION SOURCE	LED Powered by CR2032 Battery
BATTERY LIFE	5 years of continuous use*, at day-setting 3
BRIGHTNESS SETTINGS	8 Total Settings NV1, NV2, Day 1, Day 2, Day 3, Day 4, Day 5, Day 6 (Super-Bright)

*When used at 70°F (21°C). Extreme temperatures (high or low) will affect lithium battery performance.



PARALLAX-FREE / WATERPROOF TO 30 METERS

WWW.TRIJICON.COM